SIEMENS

Data sheet 6AV7882-0CA30-1LA0

SIMATIC IPC277E (Nanopanel PC); 12" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 3x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply Celeron N2807 (2C/2T) 8 GB RAM; WIN Embedded Standard 7E SP1, English; 32 bit 8 GB CFAST; without SIMATIC software

Display	
Design of display	12" TFT touch
Screen diagonal	12 in
Resolution (pixels)	
● Horizontal image resolution	1 280 pixel
● Vertical image resolution	800 pixel
Backlighting	
● MTBF backlighting (at 25 °C)	80 000 h
Control elements	
Touch operation	
● Design as touch screen	Yes; analog, resistive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	32 W
Dimensions	
Width of the housing front	330 mm
Height of housing front	241 mm
Mounting cutout, width	310 mm
Mounting cutout, height	221 mm
mounting depth	73 mm
Weights	
Weight, approx.	2.75 kg
Approvals / Certificates	

General Product Approval

CE EG-Konf. UKCA [Manufacturer Declaration] [Miscellaneous] EAC [China RoHS]

General Product Approval	Maritime application

CE EG-Konf. UKCA ABS BUREAU VERITAS DNV Lloyd's Register LRS

Maritime application	Dangerous goods

[NK / Nippon Kaiji Kyokai] [KR (Korean Register of Shipping)] [Dangerous goods information] [Test Summary Report UN 38.3]

last modified: 12/24/2025

Subject to change without notice
© Copyright PIctop1

© Copyright Plctop1