



SIPLUS ET 200SP DI 8x24 V DC standard based on 6ES7131-6BF01-0BA0 with conformal coating, -40...+70 °C, digital input module, suitable for BU type A0, color code CC01, sink input, (PNP, sinking input), input type 3 (IEC 61131), input delay 0.05..20 ms module diagnostics for: short-circuit encoder supply, wire break, supply voltage

| General information | |
|--|--|
| Product type designation | DI 8x24 VDC ST |
| Firmware version | |
| • FW update possible | No |
| based on | 6ES7131-6BF01-0BA0 |
| usable BaseUnits | BU type A0 |
| Color code for module-specific color-coded label | CC01 |
| Product function | |
| • I&M data | Yes; I&M0 to I&M3 |
| • Isochronous mode | No |
| • suitable for operation on PROFINET R1 IMs | Yes |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275 |
| Operating mode | |
| • DI | Yes |
| • Counter | No |
| • Oversampling | No |
| • MSI | No |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption, max. | 50 mA; All channels are supplied from the encoder supply |
| Encoder supply | |
| Number of outputs | 8 |
| Output voltage, min. | 19.2 V |
| Short-circuit protection | Yes; per module |
| 24 V encoder supply | |
| • 24 V | Yes |
| • Short-circuit protection | Yes |
| • Output current, max. | 700 mA |
| • Output current per channel, max. | 700 mA |
| • Output current per module, max. | 700 mA |
| Power loss | |
| Power loss, typ. | 1 W; 24 V, 8 inputs supplied via encoder supply |
| Address area | |
| Address space per module | |

| | |
|---|---|
| • Inputs | 1 byte; + 1 byte for QI information |
| Hardware configuration | |
| Automatic encoding | Yes |
| • Mechanical coding element | Yes |
| • Type of mechanical coding element | Type A |
| Selection of BaseUnit for connection variants | |
| • 1-wire connection | BU type A0 |
| • 2-wire connection | BU type A0 |
| • 3-wire connection | BU type A0 with AUX terminals or potential distributor module |
| • 4-wire connection | BU type A0 + Potential distributor module |
| Digital inputs | |
| Number of digital inputs | 8 |
| Digital inputs, parameterizable | Yes |
| Sourcing/sinking input | P-reading |
| Input characteristic curve in accordance with IEC 61131, type 3 | Yes |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | -30 to +5 V |
| • for signal "1" | +11 to +30V |
| Input current | |
| • for signal "1", typ. | 2.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 to 500 µs, depending on line length) |
| — at "0" to "1", min. | 0.05 ms |
| — at "0" to "1", max. | 20 ms |
| — at "1" to "0", min. | 0.05 ms |
| — at "1" to "0", max. | 20 ms |
| Cable length | |
| • shielded, max. | 1 000 m |
| • unshielded, max. | 600 m |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| • Diagnostic alarm | Yes |
| Diagnoses | |
| • Diagnostic information readable | Yes |
| • Monitoring the supply voltage | Yes |
| — parameterizable | Yes |
| • Monitoring of encoder power supply | Yes; Module-by-module, optional protective circuit for preventing wire-break diagnostics in the case of simple encoder contacts: 25 kOhm to 45 kOhm |
| • Wire break | Yes; module-wise |
| • Short-circuit | Yes; module-wise |
| Diagnostics indication LED | |
| • Monitoring of the supply voltage (PWR-LED) | Yes; green PWR LED |
| • Channel status display | Yes; green LED |
| • for channel diagnostics | No |
| • for module diagnostics | Yes; green/red DIAG LED |
| Potential separation | |
| Potential separation channels | |
| • between the channels | No |
| • between the channels and backplane bus | Yes |
| • between the channels and the power supply of the electronics | No |

| Isolation | |
|---|---|
| Isolation tested with | 707 V DC (type test) |
| Standards, approvals, certificates | |
| Suitable for safety functions | No |
| Ecological footprint | |
| <ul style="list-style-type: none"> environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 15.9 kg |
| — global warming potential, (during production) [CO2 eq] | 3.69 kg |
| — global warming potential, (during operation) [CO2 eq] | 12.7 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.495 kg |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> horizontal installation, min. | -40 °C; = Tmin (incl. condensation/frost) |
| <ul style="list-style-type: none"> horizontal installation, max. | 70 °C; = Tmax |
| <ul style="list-style-type: none"> vertical installation, min. | -40 °C; = Tmin |
| <ul style="list-style-type: none"> vertical installation, max. | 50 °C; = Tmax |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> Installation altitude above sea level, max. | 5 000 m |
| <ul style="list-style-type: none"> Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| <ul style="list-style-type: none"> With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; incl. condensation / frost permitted (no commissioning under condensation conditions) |
| Resistance | |
| Coolants and lubricants | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| — Against mechanical environmental conditions acc. to EN 60721-3-3 | Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| — Against mechanical environmental conditions acc. to EN 60721-3-6 | Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| Conformal coating | |
| <ul style="list-style-type: none"> Coatings for printed circuit board assemblies acc. to EN 61086 | Yes; Class 2 for high reliability |
| <ul style="list-style-type: none"> Protection against fouling acc. to EN 60664-3 | Yes; Type 1 protection |
| <ul style="list-style-type: none"> Military testing according to MIL-I-46058C, Amendment 7 | Yes; Discoloration of coating possible during service life |

• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Conformal coating, Class A

Dimensions

| | |
|--------|-------|
| Width | 15 mm |
| Height | 73 mm |
| Depth | 58 mm |

Weights

| | |
|-----------------|------|
| Weight, approx. | 28 g |
|-----------------|------|

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-26-04 |
| eClass | 12 | 27-24-26-04 |
| eClass | 9.1 | 27-24-26-04 |
| eClass | 9 | 27-24-26-04 |
| eClass | 8 | 27-24-26-04 |
| eClass | 7.1 | 27-24-26-04 |
| eClass | 6 | 27-24-26-04 |
| ETIM | 10 | EC001599 |
| ETIM | 9 | EC001599 |
| ETIM | 8 | EC001599 |
| ETIM | 7 | EC001599 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval



[China RoHS](#)

[Manufacturer Declaration](#)



| | | | |
|--------------------------|-----|--------------------------------|----------------------|
| General Product Approval | EMV | For use in hazardous locations | Maritime application |
|--------------------------|-----|--------------------------------|----------------------|

[China RoHS](#)



[CCC-Ex](#)



Environment



last modified:

3/10/2026