



Figure similar

SIPLUS ET 200SP DI 8xNAMUR HF based on 6ES7131-6TF00-0CA0 with conformal coating, -40...+70 °C, digital input module, suitable for BU type A0, color code CC01, channel diagnostics

General information	
Product type designation	DI 8xNAMUR HF
Firmware version	
• FW update possible	Yes
based on	<a href="#">6ES7131-6TF00-0CA0</a>
usable BaseUnits	BU type A0
Color code for module-specific color-coded label	CC01
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• suitable for operation on PROFINET R1 IMs	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Operating mode	
• DI	Yes
• Counter	Yes
• Oversampling	No
• MSI	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	70 mA
Encoder supply	
Number of outputs	8
Short-circuit protection	Yes
24 V encoder supply	
• 24 V	No
• Short-circuit protection	No
NAMUR encoder supply	
• 8.2 V	Yes
• Short-circuit protection	Yes
• Output current per channel, max.	8 mA
• Output current per module, max.	64 mA
Power loss	
Power loss, typ.	1.5 W

Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	1 byte
<ul style="list-style-type: none"> <li>Inputs</li> </ul>	42 byte; 1 byte + 1 byte for QI information in DI mode; 42 bytes in Counter mode
<ul style="list-style-type: none"> <li>Outputs</li> </ul>	20 byte; 0 in DI mode; 20 bytes in Counter mode
Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> <li>Mechanical coding element</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Type of mechanical coding element</li> </ul>	Type A
Submodules	
<ul style="list-style-type: none"> <li>Number of configurable submodules, max.</li> </ul>	1
Selection of BaseUnit for connection variants	
<ul style="list-style-type: none"> <li>2-wire connection</li> </ul>	BU type A0
<ul style="list-style-type: none"> <li>3-wire connection</li> </ul>	BU type A0
Digital inputs	
Number of digital inputs	8; NAMUR
Digital inputs, parameterizable	Yes
Sourcing/sinking input	P-reading
Pulse extension	Yes; 0.5 s, 1 s, 2 s
Edge evaluation	Yes; rising edge, falling edge, edge change
Signal change flutter	Yes; 2 to 32 signal changes
Flutter observation window	Yes; 0.5 s, 1 s to 100 s in 1-s steps
Digital input functions, parameterizable	
<ul style="list-style-type: none"> <li>Gate start/stop</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Freely usable digital input</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Counter</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Number, max.</li> </ul>	4; See manual for details
<ul style="list-style-type: none"> <li>— Counting frequency, max.</li> </ul>	5 kHz
<ul style="list-style-type: none"> <li>— Counting width</li> </ul>	32 bit
<ul style="list-style-type: none"> <li>— Counting direction up/down</li> </ul>	Yes
Input voltage	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	8.2 V
Input current	
for 10 k switched contact	
<ul style="list-style-type: none"> <li>— for signal "0", min.</li> </ul>	0.35 mA
<ul style="list-style-type: none"> <li>— for signal "0", max.</li> </ul>	1.2 mA
<ul style="list-style-type: none"> <li>— for signal "1", min.</li> </ul>	2.1 mA
<ul style="list-style-type: none"> <li>— for signal "1", max.</li> </ul>	7 mA
for unswitched contact	
<ul style="list-style-type: none"> <li>— for signal "0", max. (permissible quiescent current)</li> </ul>	0.5 mA
<ul style="list-style-type: none"> <li>— for signal "1", typ.</li> </ul>	8 mA
for NAMUR encoders	
<ul style="list-style-type: none"> <li>— for signal "0", min.</li> </ul>	0.35 mA
<ul style="list-style-type: none"> <li>— for signal "0", max.</li> </ul>	1.2 mA
<ul style="list-style-type: none"> <li>— for signal "1", min.</li> </ul>	2.1 mA
<ul style="list-style-type: none"> <li>— for signal "1", max.</li> </ul>	7 mA
Input delay (for rated value of input voltage)	
<ul style="list-style-type: none"> <li>tolerated changeover time for changeover contacts</li> </ul>	300 ms
for standard inputs	
<ul style="list-style-type: none"> <li>— parameterizable</li> </ul>	No
for NAMUR inputs	
<ul style="list-style-type: none"> <li>— at "0" to "1", max.</li> </ul>	20 ms; See manual for details
<ul style="list-style-type: none"> <li>— at "1" to "0", max.</li> </ul>	20 ms; See manual for details
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	200 m; 50 m for Counter mode
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> <li>NAMUR encoder/changeover contact according to EN</li> </ul>	Yes

60947

- Single contact / changeover contact unconnected
- Single contact / changeover contact connected with 10 k $\Omega$

Yes  
Yes

### Interrupts/diagnostics/status information

Diagnostics function Yes

#### Alarms

- Diagnostic alarm Yes; channel by channel
- Hardware interrupt Yes; Parameterizable, channels 0 to 7

#### Diagnoses

- Diagnostic information readable Yes
- Monitoring the supply voltage Yes
  - parameterizable Yes
- Monitoring of encoder power supply No
- Wire break Yes; channel by channel
- Short-circuit Yes; channel by channel

#### Diagnostics indication LED

- Monitoring of the supply voltage (PWR-LED) Yes; green PWR LED
- Channel status display Yes; green LED
  - for channel diagnostics Yes; red LED
  - for module diagnostics Yes; green/red DIAG LED

### Potential separation

#### Potential separation channels

- between the channels No
- between the channels and backplane bus Yes
- Between the channels and load voltage L+ Yes
- between the channels and the power supply of the electronics Yes

### Isolation

Isolation tested with 707 V DC (type test)

### Standards, approvals, certificates

Suitable for safety functions No

### Ambient conditions

#### Ambient temperature during operation

- horizontal installation, min. -40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C
- horizontal installation, max. 70 °C; = Tmax; > +60 °C number of simultaneously controllable inputs max. 4 (no adjacent points)
- vertical installation, min. -40 °C; = Tmin
- vertical installation, max. 50 °C; = Tmax

#### Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m
- Ambient air temperature-barometric pressure-altitude Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

#### Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max. 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation

### Resistance

#### Coolants and lubricants

- Resistant to commercially available coolants and lubricants Yes; Incl. diesel and oil droplets in the air

#### Use in stationary industrial systems

- to biologically active substances according to EN 60721-3-3 Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
- to chemically active substances according to EN 60721-3-3 Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); \*
- to mechanically active substances according to EN 60721-3-3 Yes; Class 3S4 incl. sand, dust, \*
- Against mechanical environmental conditions acc. to EN 60721-3-3 Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)

#### Use on ships/at sea

- to biologically active substances according to EN Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on

60721-3-6	request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
— Against mechanical environmental conditions acc. to EN 60721-3-6	Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)

<b>Usage in industrial process technology</b>	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

<b>Remark</b>	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!

<b>Conformal coating</b>	
<ul style="list-style-type: none"> <li>• Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>• Protection against fouling acc. to EN 60664-3</li> <li>• Military testing according to MIL-I-46058C, Amendment 7</li> <li>• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul>	<p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>

<b>Dimensions</b>	
Width	15 mm
Height	73 mm
Depth	58 mm

<b>Weights</b>	
Weight, approx.	32 g

<b>Classifications</b>			
		<b>Version</b>	<b>Classification</b>
	eClass	14	27-24-26-04
	eClass	12	27-24-26-04
	eClass	9.1	27-24-26-04
	eClass	9	27-24-26-04
	eClass	8	27-24-26-04
	eClass	7.1	27-24-26-04
	eClass	6	27-24-26-04
	ETIM	10	EC001599
	ETIM	9	EC001599
	ETIM	8	EC001599
	ETIM	7	EC001599
	IDEA	4	3566
	UNSPSC	15	32-15-17-05

<b>Approvals / Certificates</b>	
<b>General Product Approval</b>	

[Manufacturer Declaration](#)



[China RoHS](#)



<b>General Product Approval</b>	<b>EMV</b>	<b>For use in hazardous locations</b>	<b>Maritime application</b>
---------------------------------	------------	---------------------------------------	-----------------------------

[China RoHS](#)



[CCC-Ex](#)



---

last modified:

10/23/2025 