



Figure similar

spare part SIPLUS ET 200SP DQ 4x24VDC/2A Standard based on 6ES7132-6BD20-0BA0 with conformal coating, -40...+70 °C, digital output module, suitable for BU type A0, color code CC02, channel diagnostics,

| General information | |
|----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Product type designation | DQ 4x24 V DC/2 A ST |
| based on | 6ES7132-6BD20-0BA0 |
| usable BaseUnits | BU type A0 |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275 |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Power loss | |
| Power loss, typ. | 1 W |
| Address area | |
| Address space per module | |
| <ul style="list-style-type: none"> Address space per module, max. | 32 byte |
| Digital outputs | |
| Type of digital output | Source output (PNP, current-sourcing) |
| Number of digital outputs | 4; > +60 °C number of simultaneously controllable outputs max. 2x 0.25 A or max. 4x 0.125 A, max. total current 0.5 A |
| Short-circuit protection | Yes |
| <ul style="list-style-type: none"> Response threshold, typ. | 2.8 to 5.2 A |
| Limitation of inductive shutdown voltage to | Typ. L+ (-50 V) |
| Controlling a digital input | Yes |
| Switching capacity of the outputs | |
| <ul style="list-style-type: none"> with resistive load, max. on lamp load, max. | 2 A 10 W |
| Load resistance range | |
| <ul style="list-style-type: none"> lower limit upper limit | 12 Ω 3 400 Ω |
| Output current | |
| <ul style="list-style-type: none"> for signal "1" rated value | 2 A |
| Output delay with resistive load | |
| <ul style="list-style-type: none"> "0" to "1", max. "1" to "0", max. | 50 μs 100 μs |
| Parallel switching of two outputs | |
| <ul style="list-style-type: none"> for uprating for redundant control of a load | No Yes |
| Switching frequency | |

| | |
|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • with resistive load, max. | 100 Hz |
| <ul style="list-style-type: none"> • with inductive load, max. | 2 Hz |
| <ul style="list-style-type: none"> • on lamp load, max. | 10 Hz |
| Cable length | |
| <ul style="list-style-type: none"> • shielded, max. | 1 000 m |
| <ul style="list-style-type: none"> • unshielded, max. | 200 m |
| Interrupts/diagnostics/status information | |
| Diagnoses | |
| <ul style="list-style-type: none"> • Monitoring the supply voltage | Yes |
| <ul style="list-style-type: none"> • Wire break | Yes |
| <ul style="list-style-type: none"> • Short-circuit | Yes |
| <ul style="list-style-type: none"> • Group error | Yes |
| Permissible potential difference | |
| between different circuits | 75 V DC/60 V AC |
| Isolation | |
| Isolation tested with | 707 V DC |
| Standards, approvals, certificates | |
| Suitable for safety functions | No |
| Ecological footprint | |
| <ul style="list-style-type: none"> • environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 29.3 kg |
| — global warming potential, (during production) [CO2 eq] | 3.98 kg |
| — global warming potential, (during operation) [CO2 eq] | 25.6 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.245 kg |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • horizontal installation, min. | -40 °C; = Tmin (incl. condensation/frost) |
| <ul style="list-style-type: none"> • horizontal installation, max. | 70 °C; = Tmax; > +60 °C number of simultaneously controllable outputs max. 2x 0.25 A or max. 4x 0.125 A, max. total current 0.5 A |
| <ul style="list-style-type: none"> • vertical installation, min. | -40 °C; = Tmin |
| <ul style="list-style-type: none"> • vertical installation, max. | 50 °C; = Tmax |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> • Installation altitude above sea level, max. | 5 000 m |
| <ul style="list-style-type: none"> • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| <ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation |
| Resistance | |
| Coolants and lubricants | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| — Against mechanical environmental conditions acc. to EN 60721-3-3 | Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |

— Against mechanical environmental conditions acc. to EN 60721-3-6

Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)

Usage in industrial process technology

— Against chemically active substances acc. to EN 60654-4

Yes; Class 3 (excluding trichlorethylene)

— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04

Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

Remark

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

* The supplied plug covers must remain in place over the unused interfaces during operation!

Conformal coating

- Coatings for printed circuit board assemblies acc. to EN 61086
- Protection against fouling acc. to EN 60664-3
- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Class 2 for high reliability

Yes; Type 1 protection

Yes; Discoloration of coating possible during service life

Yes; Conformal coating, Class A

Dimensions

| | |
|--------|-------|
| Width | 15 mm |
| Height | 73 mm |
| Depth | 58 mm |

Weights

| | |
|-----------------|------|
| Weight, approx. | 30 g |
|-----------------|------|

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-26-04 |
| eClass | 12 | 27-24-26-04 |
| eClass | 9.1 | 27-24-26-04 |
| eClass | 9 | 27-24-26-04 |
| eClass | 8 | 27-24-26-04 |
| eClass | 7.1 | 27-24-26-04 |
| eClass | 6 | 27-24-26-04 |
| ETIM | 10 | EC001599 |
| ETIM | 9 | EC001599 |
| ETIM | 8 | EC001599 |
| ETIM | 7 | EC001599 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[China RoHS](#)



| | | | |
|-----|--------------------------------|----------------------|-------------|
| EMV | For use in hazardous locations | Maritime application | Environment |
|-----|--------------------------------|----------------------|-------------|



[CCC-Ex](#)



last modified:

9/24/2025