



SIPLUS ET 200S EM 2AI high speed based on 6ES7134-4GB52-0AB0 with conformal coating, -25...+60 °C,

Figure similar

General information	
Product function	
<ul style="list-style-type: none"> • Isochronous mode 	Yes
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V
<ul style="list-style-type: none"> • Short-circuit protection 	Yes
<ul style="list-style-type: none"> • Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	225 mA
from backplane bus 3.3 V DC, max.	10 mA
Output voltage	
Power supply to the transmitters	
<ul style="list-style-type: none"> • present 	Yes
<ul style="list-style-type: none"> • short-circuit proof 	Yes
Power loss	
Power loss, typ.	2.5 W
Address area	
Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	4 byte
Analog inputs	
Number of analog inputs	2
Cycle time (all channels) max.	0.25 ms
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA — Input resistance (0 to 20 mA) 	Yes 106 Ω
<ul style="list-style-type: none"> • 4 mA to 20 mA 	Yes
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	16 bit
Smoothing of measured values	
<ul style="list-style-type: none"> • parameterizable 	Yes
<ul style="list-style-type: none"> • Step: None 	Yes; 1x cycle time
<ul style="list-style-type: none"> • Step: low 	Yes; 4x cycle time
<ul style="list-style-type: none"> • Step: Medium 	Yes; 16x cycle time
<ul style="list-style-type: none"> • Step: High 	Yes; 32x cycle time

Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.3 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.2 %
Interrupts/diagnostics/status information	
Alarms	
• Hardware interrupt	Yes
Diagnoses	
• Wire break	Yes; at 4 to 20 mA
• Group error	Yes
• Overflow/Underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Diagnostics wire break	at 4 to 20 mA
Group diagnostics	1
Overflow/Underflow	1
Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	60 °C; = Tmax
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

* The supplied plug covers must remain in place over the unused interfaces during operation!

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

Classifications

	Version	Classification
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[China RoHS](#)



[Metrological Approval](#)

General Product Approval

EMV

For use in hazardous locations



[CCC-Ex](#)

last modified:

3/12/2024