



Figure similar

SIPLUS ET 200S EM 2AI TC HF based on 6ES7134-4NB01-0AB0 with conformal coating, 0...+70 °C, 15 mm width, 15 bit+sign with internal temperature compensation

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V; From power module
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	4 byte
Analog inputs	
Number of analog inputs	2
permissible input voltage for voltage input (destruction limit), max.	20 V; ±20 V, continuous
Cycle time (all channels) max.	Number of active channels per module x basic conversion time
Technical unit for temperature measurement adjustable	Yes; Celsius / Fahrenheit
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>-80 mV to +80 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (-80 mV to +80 mV)</li> </ul>	1 MΩ
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> <li>Type B</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (Type B)</li> </ul>	1 MΩ
<ul style="list-style-type: none"> <li>Type C</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (Type C)</li> </ul>	1 MΩ
<ul style="list-style-type: none"> <li>Type E</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (Type E)</li> </ul>	1 MΩ
<ul style="list-style-type: none"> <li>Type J</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (type J)</li> </ul>	1 MΩ
<ul style="list-style-type: none"> <li>Type K</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (Type K)</li> </ul>	1 MΩ
<ul style="list-style-type: none"> <li>Type L</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (Type L)</li> </ul>	1 MΩ
<ul style="list-style-type: none"> <li>Type N</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (Type N)</li> </ul>	1 MΩ
<ul style="list-style-type: none"> <li>Type R</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Input resistance (Type R)</li> </ul>	1 MΩ

<ul style="list-style-type: none"> <li>• Type S <ul style="list-style-type: none"> <li>— Input resistance (Type S)</li> </ul> </li> <li>• Type T <ul style="list-style-type: none"> <li>— Input resistance (Type T)</li> </ul> </li> </ul>	<p>Yes</p> <p>1 MΩ</p> <p>Yes</p> <p>1 MΩ</p>
<b>Thermocouple (TC)</b>	
Temperature compensation	
<ul style="list-style-type: none"> <li>— internal temperature compensation</li> <li>— external temperature compensation with compensations socket</li> </ul>	<p>Yes; possible with TM-E15S24-AT, TM-E15C24-AT</p> <p>Yes; one external compensating box per channel</p>
Characteristic linearization	
<ul style="list-style-type: none"> <li>• parameterizable <ul style="list-style-type: none"> <li>— for thermocouples</li> </ul> </li> </ul>	<p>Yes</p> <p>Type B, C, E, J, K, L, N, R, S, T to IEC 584</p>
Cable length	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	50 m
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> <li>• Integration time (ms)</li> <li>• Interference voltage suppression for interference frequency f1 in Hz</li> <li>• Conversion time (per channel)</li> </ul>	<p>16 bit</p> <p>16,7 / 20 ms</p> <p>50 / 60 Hz</p> <p>66 ms; 66 / 80 ms; additional conversion time for diagnostic wire break test</p>
Smoothing of measured values	
<ul style="list-style-type: none"> <li>• parameterizable</li> <li>• Step: None</li> <li>• Step: low</li> <li>• Step: Medium</li> <li>• Step: High</li> </ul>	<p>Yes; In four stages by means of digital filtering</p> <p>Yes; 1x cycle time</p> <p>Yes; 4x cycle time</p> <p>Yes; 32x cycle time</p> <p>Yes; 64x cycle time</p>
<b>Errors/accuracies</b>	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> </ul>	0.1 %; ±1.5 K for thermocouples, ±7 K for thermocouples type C, ±2.5 K with static thermal state (ambient temperature change < 0.3 K/min)
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> </ul>	0.05 %; ±1 K with thermocouples, ±5 K with thermocouples type C, ±1.5 K with static thermal state (ambient temperature change < 0.3 K/min)
<b>Interrupts/diagnostics/status information</b>	
Diagnoses	
<ul style="list-style-type: none"> <li>• Wire break</li> <li>• Group error</li> <li>• Overflow/Underflow</li> </ul>	<p>Yes; only thermocouples</p> <p>Yes</p> <p>Yes</p>
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>• Group error SF (red)</li> </ul>	Yes
<b>Parameter</b>	
Remark	4 byte
Diagnostics wire break	Disable / enable (wire break is detected only in thermocouples)
Group diagnostics	Disable / enable
Overflow/Underflow	Disable / enable
Comparison point	none / yes, internal
<b>Potential separation</b>	
Potential separation analog inputs	
<ul style="list-style-type: none"> <li>• between the channels</li> <li>• between the channels and backplane bus</li> <li>• Between the channels and load voltage L+</li> </ul>	<p>No</p> <p>Yes</p> <p>Yes</p>
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Standards, approvals, certificates</b>	
CE mark	Yes
<b>Ambient conditions</b>	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>• min.</li> </ul>	0 °C; = Tmin

• max.	70 °C; = Tmax	
<b>Altitude during operation relating to sea level</b>		
• Installation altitude above sea level, max.	5 000 m	
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)	
<b>Relative humidity</b>		
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)	
<b>Resistance</b>		
<b>Use in stationary industrial systems</b>		
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request	
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *	
<b>Use on ships/at sea</b>		
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request	
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *	
<b>Usage in industrial process technology</b>		
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)	
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)	
<b>Remark</b>		
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!	
<b>Dimensions</b>		
Width	15 mm	
Height	81 mm	
Depth	52 mm	
<b>Weights</b>		
Weight, approx.	40 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05
<b>Approvals / Certificates</b>		
<b>General Product Approval</b>		



[Manufacturer Declaration](#)



[China RoHS](#)



[Metrological Approval](#)

General Product Approval

EMV

For use in hazardous locations



[CCC-Ex](#)

last modified:

5/13/2024