



Figure similar

SIPLUS ET 200SP AI 4xRTD/TC high feature based on 6ES7134-6JD00-0CA1 with conformal coating, -40...+60 °C, analog input module, suitable for BU type A0, A1, color code CC00, channel diagnostics, 16-bit, +/-0.1%, 2/3/4-wire

General information	
Product type designation	AI 4xRTD/TC 2-/3-/4-wire HF
Firmware version	
• FW update possible	Yes
based on	<a href="#">6ES7134-6JD00-0CA1</a>
usable BaseUnits	BU type A0, A1
Color code for module-specific color-coded label	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Operating mode	
• Oversampling	No
• MSI	No
CIR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	30 mA
Current consumption, max.	32 mA
Power loss	
Power loss, typ.	0.75 W
Address area	
Address space per module	
• Address space per module, max.	8 byte; + 1 byte for QI information
Hardware configuration	
Automatic encoding	
• Mechanical coding element	Yes
• Type of mechanical coding element	Type A
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	30 V

Constant measurement current for resistance-type transmitter, typ.	2 mA
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels); for line compensation in case of a three-wire connection, an additional cycle is necessary
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
<b>Input ranges (rated values), voltages</b>	
<ul style="list-style-type: none"> <li>• -1 V to +1 V <ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul> </li> <li>• -250 mV to +250 mV <ul style="list-style-type: none"> <li>— Input resistance (-250 mV to +250 mV)</li> </ul> </li> <li>• -50 mV to +50 mV <ul style="list-style-type: none"> <li>— Input resistance (-50 mV to +50 mV)</li> </ul> </li> <li>• -80 mV to +80 mV <ul style="list-style-type: none"> <li>— Input resistance (-80 mV to +80 mV)</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> </ul>
<b>Input ranges (rated values), thermocouples</b>	
<ul style="list-style-type: none"> <li>• Type B <ul style="list-style-type: none"> <li>— Input resistance (Type B)</li> </ul> </li> <li>• Type C <ul style="list-style-type: none"> <li>— Input resistance (Type C)</li> </ul> </li> <li>• Type E <ul style="list-style-type: none"> <li>— Input resistance (Type E)</li> </ul> </li> <li>• Type J <ul style="list-style-type: none"> <li>— Input resistance (type J)</li> </ul> </li> <li>• Type K <ul style="list-style-type: none"> <li>— Input resistance (Type K)</li> </ul> </li> <li>• Type L <ul style="list-style-type: none"> <li>— Input resistance (Type L)</li> </ul> </li> <li>• Type N <ul style="list-style-type: none"> <li>— Input resistance (Type N)</li> </ul> </li> <li>• Type R <ul style="list-style-type: none"> <li>— Input resistance (Type R)</li> </ul> </li> <li>• Type S <ul style="list-style-type: none"> <li>— Input resistance (Type S)</li> </ul> </li> <li>• Type T <ul style="list-style-type: none"> <li>— Input resistance (Type T)</li> </ul> </li> <li>• Type U <ul style="list-style-type: none"> <li>— Input resistance (Type U)</li> </ul> </li> <li>• Type TXK/TXK(L) to GOST <ul style="list-style-type: none"> <li>— Input resistance (Type TXK/TXK(L) to GOST)</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> </ul>
<b>Input ranges (rated values), resistance thermometer</b>	
<ul style="list-style-type: none"> <li>• Cu 10 <ul style="list-style-type: none"> <li>— Input resistance (Cu 10)</li> </ul> </li> <li>• Ni 100 <ul style="list-style-type: none"> <li>— Input resistance (Ni 100)</li> </ul> </li> <li>• Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (Ni 1000)</li> </ul> </li> <li>• LG-Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (LG-Ni 1000)</li> </ul> </li> <li>• Ni 120 <ul style="list-style-type: none"> <li>— Input resistance (Ni 120)</li> </ul> </li> <li>• Ni 200 <ul style="list-style-type: none"> <li>— Input resistance (Ni 200)</li> </ul> </li> <li>• Ni 500 <ul style="list-style-type: none"> <li>— Input resistance (Ni 500)</li> </ul> </li> <li>• Pt 100 <ul style="list-style-type: none"> <li>— Input resistance (Pt 100)</li> </ul> </li> <li>• Pt 1000 <ul style="list-style-type: none"> <li>— Input resistance (Pt 1000)</li> </ul> </li> <li>• Pt 200</li> </ul>	<ul style="list-style-type: none"> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign 1 MΩ</li> <li>Yes; 16 bit incl. sign</li> </ul>

— Input resistance (Pt 200)	1 MΩ
● Pt 500	Yes; 16 bit incl. sign
— Input resistance (Pt 500)	1 MΩ
<b>Input ranges (rated values), resistors</b>	
● 0 to 150 ohms	Yes; 15 bit
— Input resistance (0 to 150 ohms)	1 MΩ
● 0 to 300 ohms	Yes; 15 bit
— Input resistance (0 to 300 ohms)	1 MΩ
● 0 to 600 ohms	Yes; 15 bit
— Input resistance (0 to 600 ohms)	1 MΩ
● 0 to 3000 ohms	Yes; 15 bit
— Input resistance (0 to 3000 ohms)	1 MΩ
● 0 to 6000 ohms	Yes; 15 bit
— Input resistance (0 to 6000 ohms)	1 MΩ
● PTC	Yes; 15 bit
— Input resistance (PTC)	1 MΩ
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— parameterizable	Yes
— Reference channel of the module	Yes
— internal comparison point	Yes; with BaseUnit type A1
— Reference channel of the group	Yes
— Number of reference channel groups	4; Group 0 to 3
— fixed reference temperature	Yes
<b>Cable length</b>	
● shielded, max.	200 m; 50 m with thermocouples
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating (Sigma-Delta)
<b>Integration and conversion time/resolution per channel</b>	
● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes
● Basic conversion time, including integration time (ms)	
— additional processing time for wire-break check	2 ms; In the ranges resistance thermometers, resistors and thermocouples
— additional power line wire-break check	2 ms; for 3/4 wire transducer (resistance thermometer and resistor)
● Interference voltage suppression for interference frequency f1 in Hz	16.6 / 50 / 60 Hz
● Conversion time (per channel)	180 / 60 / 50 / (67.5 / 22.5 / 18.75) ms
<b>Smoothing of measured values</b>	
● Number of smoothing levels	4; None; 4/8/16 times
● parameterizable	Yes
<b>Encoder</b>	
<b>Connection of signal encoders</b>	
● for voltage measurement	Yes
● for resistance measurement with two-wire connection	Yes
● for resistance measurement with three-wire connection	Yes
● for resistance measurement with four-wire connection	Yes
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.0009 %/K; ±0.005 % / K at thermocouple
Crosstalk between the inputs, min.	50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
<b>Operational error limit in overall temperature range</b>	
● Voltage, relative to input range, (+/-)	0.2 %
● Resistance, relative to input range, (+/-)	0.2 %
<b>Basic error limit (operational limit at 25 °C)</b>	
● Voltage, relative to input range, (+/-)	0.05 %
● Resistance, relative to input range, (+/-)	0.05 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$ , f1 = interference frequency	

<ul style="list-style-type: none"> <li>Series mode interference (peak value of interference &lt; rated value of input range), min.</li> </ul>	70 dB
<ul style="list-style-type: none"> <li>Common mode voltage, max.</li> </ul>	10 V
<ul style="list-style-type: none"> <li>Common mode interference, min.</li> </ul>	90 dB
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Limit value alarm</li> </ul>	Yes; two upper and two lower limit values in each case
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Wire break</li> </ul>	Yes; channel by channel
<ul style="list-style-type: none"> <li>Group error</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Overflow/Underflow</li> </ul>	Yes; channel by channel
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>Monitoring of the supply voltage (PWR-LED)</li> </ul>	Yes; green PWR LED
<ul style="list-style-type: none"> <li>Channel status display</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>for channel diagnostics</li> </ul>	Yes; red LED
<ul style="list-style-type: none"> <li>for module diagnostics</li> </ul>	Yes; green/red DIAG LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
<ul style="list-style-type: none"> <li>between the channels</li> </ul>	No
<ul style="list-style-type: none"> <li>between the channels and backplane bus</li> </ul>	Yes
<ul style="list-style-type: none"> <li>between the channels and the power supply of the electronics</li> </ul>	Yes
<b>Permissible potential difference</b>	
between the inputs (UCM)	10 V DC
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> </ul>	-40 °C; = Tmin (incl. condensation/frost)
<ul style="list-style-type: none"> <li>horizontal installation, max.</li> </ul>	60 °C; = Tmax; +70 °C with spacing modules (6AG1193-6BN00-7BA0) or configured slots to the left and right of the module
<ul style="list-style-type: none"> <li>vertical installation, min.</li> </ul>	-40 °C; = Tmin (incl. condensation/frost)
<ul style="list-style-type: none"> <li>vertical installation, max.</li> </ul>	50 °C; = Tmax
<b>Altitude during operation relating to sea level</b>	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	5 000 m
<ul style="list-style-type: none"> <li>Ambient air temperature-barometric pressure-altitude</li> </ul>	Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
<b>Resistance</b>	
<b>Coolants and lubricants</b>	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
<b>Use in stationary industrial systems</b>	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
— Against mechanical environmental conditions acc. to EN 60721-3-3	Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *

— to mechanically active substances according to EN 60721-3-6

Yes; Class 6S3 incl. sand, dust; \*

— Against mechanical environmental conditions acc. to EN 60721-3-6

Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)

**Usage in industrial process technology**

— Against chemically active substances acc. to EN 60654-4

Yes; Class 3 (excluding trichlorethylene)

— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04

Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

**Remark**

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

\* The supplied plug covers must remain in place over the unused interfaces during operation!

**Conformal coating**

• Coatings for printed circuit board assemblies acc. to EN 61086

Yes; Class 2 for high reliability

• Protection against fouling acc. to EN 60664-3

Yes; Type 1 protection

• Military testing according to MIL-I-46058C, Amendment 7

Yes; Discoloration of coating possible during service life

• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Conformal coating, Class A

**Dimensions**

Width	15 mm
Height	73 mm
Depth	58 mm

**Weights**

Weight, approx.	30 g
-----------------	------

**Classifications**

	Version	Classification
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**

[Manufacturer Declaration](#)



[China RoHS](#)



**General Product Approval**

EMV	For use in hazardous locations	Maritime application
-----	--------------------------------	----------------------

[China RoHS](#)



[CCC-Ex](#)



last modified:

10/23/2025

