



Figure similar

SIPLUS ET 200S PM-E 24V-48V based on 6ES7138-4CA50-0AB0 with conformal coating, -25...+60 °C,

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) Short-circuit protection Reverse polarity protection 	24 to 48 V DC No; external (e.g. automatic circuit breaker), tripping characteristic B, C Yes
Input current	
from load voltage L+ (without load), max.	12 mA
Current carrying capacity	
up to 60 °C, max.	10 A
Power loss	
Power loss, typ.	0.5 W
Interrupts/diagnostics/status information	
Diagnoses	
<ul style="list-style-type: none"> missing load voltage 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> Rated load voltage PWR (green) Group error SF (red) 	Yes Yes
Parameter	
Remark	3 byte
missing load voltage	Disable / enable
Potential separation	
primary/secondary	Yes; between rated load voltage and backplane bus, between power modules
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	-25 °C; = Tmin 60 °C; = Tmax
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. Ambient air temperature-barometric pressure-altitude 	5 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
<ul style="list-style-type: none"> With condensation, tested in accordance with IEC 60068- 	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed)

2-38, max.	state)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

Weights

Weight, approx.	35 g
-----------------	------

Classifications

	Version	Classification
eClass	14	27-24-26-11
eClass	12	27-24-26-11
eClass	9.1	27-24-26-11
eClass	9	27-24-26-11
eClass	8	27-24-26-11
eClass	7.1	27-24-26-11
eClass	6	27-24-26-11
ETIM	10	EC002583
ETIM	9	EC002583
ETIM	8	EC002583
ETIM	7	EC002583
IDEA	4	3575
UNSPSC	15	32-15-17-06

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)



[China RoHS](#)



EMV For use in hazardous locations



[CCC-Ex](#)

last modified:

5/13/2024