



Figure similar

SIPLUS ET 200SP BU15-P16+A0+12B/T based on 6ES7193-6BP40-0BA1 with conformal coating, -40...+70 °C, BU type A1, push-in terminals, with 2x5 add-on terminals, bridged to the left, WxH: 15 mm x141 mm, with temperature acquisition

| General information | |
|---|---|
| Product type designation | BU type A1 |
| based on | 6ES7193-6BP40-0BA1 |
| Supply voltage | |
| Rated value (DC) | 24 V |
| external protection for power supply lines | Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic |
| Current carrying capacity | |
| For P1 and P2 bus, max. | 10 A |
| For process terminals, max. | 2 A |
| Hardware configuration | |
| Additional terminals | Yes |
| Temperature sensor | Yes |
| Formation of potential groups | |
| • New potential group | No |
| • Potential group continued from the left | Yes |
| Slots | |
| • Number of slots | 1; Type A1 |
| Analog inputs | |
| Thermocouple (TC) | |
| Temperature compensation | |
| — internal temperature compensation | Yes |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Ambient conditions | |
| Ambient temperature during operation | |
| • horizontal installation, min. | -40 °C; = Tmin (incl. condensation/frost) |
| • horizontal installation, max. | 70 °C; = Tmax |
| • vertical installation, min. | -40 °C; = Tmin |
| • vertical installation, max. | 50 °C; = Tmax |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 5 000 m |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) |
| Resistance | |

| | | |
|---|---|-----------------------|
| Coolants and lubricants | | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air | |
| Use in stationary industrial systems | | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request | |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * | |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * | |
| Use on ships/at sea | | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request | |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * | |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * | |
| Usage in industrial process technology | | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) | |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) | |
| Remark | | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! | |
| Conformal coating | | |
| <ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 • Protection against fouling acc. to EN 60664-3 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | <p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p> | |
| Accessories | | |
| Color coding labels | | |
| <ul style="list-style-type: none"> • for process terminals • for AUX terminals • for add-on terminals | <p>CC00 to CC09</p> <p>does not exist</p> <p>CC74</p> | |
| Connection method | | |
| Terminals | | |
| <ul style="list-style-type: none"> • Terminal type • system-integrated shield connection • Conductor cross-section, min. • Conductor cross-section, max. • Number of process terminals to I/O module • Number of terminals to AUX bus • Number of add-on terminals • Number of terminals with connection to P1 and P2 bus | <p>Push-in terminal</p> <p>Yes; Optional</p> <p>0.14 mm²; AWG 26</p> <p>2.5 mm²; AWG 14</p> <p>16</p> <p>0</p> <p>2x5</p> <p>2</p> | |
| Dimensions | | |
| Width | 15 mm | |
| Height | 141 mm | |
| Depth | 35 mm | |
| Weights | | |
| Weight, approx. | 50 g | |
| Classifications | | |
| | Version | Classification |
| eClass | 14 | 27-24-26-03 |
| eClass | 12 | 27-24-26-03 |
| eClass | 9.1 | 27-24-26-03 |
| eClass | 9 | 27-24-26-03 |

| | | |
|--------|-----|-------------|
| eClass | 8 | 27-24-26-03 |
| eClass | 7.1 | 27-24-26-03 |
| eClass | 6 | 27-24-26-03 |
| ETIM | 10 | EC001598 |
| ETIM | 9 | EC001598 |
| ETIM | 8 | EC001598 |
| ETIM | 7 | EC001598 |
| IDEA | 4 | 3560 |
| UNSPSC | 15 | 32-15-17-04 |

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[China RoHS](#)



| | | | | |
|---------------------------------|------------|---------------------------------------|--|-----------------------------|
| General Product Approval | EMV | For use in hazardous locations | | Maritime application |
|---------------------------------|------------|---------------------------------------|--|-----------------------------|

[China RoHS](#)



[CCC-Ex](#)



last modified:

10/23/2025