



Figure similar

SIPLUS S7-1200 SM 1231 TC 8 AI based on 6ES7231-5QF32-0XB0 with conformal coating, -20...+60 °C, analog input, SM 1231 TC 8 AI thermocouples

General information	
Product type designation	SM 1231, AI 8x16 bit TC
based on	<a href="#">6ES7231-5QF32-0XB0</a>
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	40 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	4; Thermocouples
permissible input voltage for voltage input (destruction limit), max.	±35 V
Technical unit for temperature measurement adjustable	Degrees Celsius/degrees Fahrenheit
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> <li>• Current</li> <li>• Thermocouple</li> <li>• Resistance thermometer</li> <li>• Resistance</li> </ul>	<ul style="list-style-type: none"> <li>No</li> <li>No</li> <li>Yes; J, K, T, E, R &amp; S, B, N, C, TXK/XK(L); voltage range: ±80 mV</li> <li>No</li> <li>No</li> </ul>
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• -80 mV to +80 mV</li> <li>— Input resistance (-80 mV to +80 mV)</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>≥1 MOhm</li> </ul>
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> <li>• Type B</li> <li>• Type C</li> <li>• Type E</li> <li>• Type J</li> <li>• Type K</li> <li>• Type N</li> <li>• Type R</li> <li>• Type S</li> <li>• Type T</li> <li>• Type TXK/TXK(L) to GOST</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> </ul>
Thermocouple (TC)	
Temperature compensation	
— parameterizable	No

Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>Resolution with overrange (bit including sign), max.</li> <li>Integration time, parameterizable</li> <li>Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> </ul>	15 bit; + sign No 85 dB at 50 / 60 / 400 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> <li>parameterizable</li> </ul>	Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C ±0.1%, to 55 °C ±0.2% total measurement range
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.5 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1$ = interference frequency	
<ul style="list-style-type: none"> <li>Common mode interference, min.</li> </ul>	120 dB
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes; Can be read out
Alarms	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
Diagnoses	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> <li>Wire break</li> </ul>	Yes Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>for status of the inputs</li> <li>for maintenance</li> </ul>	Yes Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Ecological footprint	
<ul style="list-style-type: none"> <li>environmental product declaration</li> </ul>	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	43.1 kg
— global warming potential, (during production) [CO2 eq]	7.62 kg
— global warming potential, (during operation) [CO2 eq]	36 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.544 kg
Ambient conditions	
Free fall	
<ul style="list-style-type: none"> <li>Fall height, max.</li> </ul>	0.3 m; five times, in product package
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-20 °C; = Tmin (incl. condensation/frost); start-up @ 0 °C 60 °C; = Tmax
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-40 °C 70 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> <li>Ambient air temperature-barometric pressure-altitude</li> </ul>	5 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
<ul style="list-style-type: none"> <li>With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	

— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request	
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *	
<b>Use on ships/at sea</b>		
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request	
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *	
<b>Usage in industrial process technology</b>		
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)	
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)	
<b>Remark</b>		
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!	
<b>Conformal coating</b>		
<ul style="list-style-type: none"> <li>• Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>• Protection against fouling acc. to EN 60664-3</li> <li>• Military testing according to MIL-I-46058C, Amendment 7</li> <li>• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul>	<p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>	
<b>Connection method</b>		
required front connector	Yes	
<b>Mechanics/material</b>		
Enclosure material (front) <ul style="list-style-type: none"> <li>• Plastic</li> </ul>	Yes	
<b>Dimensions</b>		
Width	45 mm	
Height	100 mm	
Depth	75 mm	
<b>Weights</b>		
Weight, approx.	220 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05
<b>Approvals / Certificates</b>		
<b>General Product Approval</b>		



[Manufacturer Declaration](#)

[China RoHS](#)



[Metrological Approval](#)

General Product Approval

EMV



[China RoHS](#)



For use in hazardous locations

Maritime application

Environment



IECEX



CCC



DNV



last modified:

10/9/2024