



Figure similar

spare part SIPLUS S7-300 SM 321 based on 6ES7321-1CH20-0AA0 with conformal coating, -25...+70 °C, digital input isolated 16 DI, 48-125 V DC, 1x 20-pole

General information	
based on	6ES7321-1CH20-0AA0
Product function	
<ul style="list-style-type: none"> • Isochronous mode 	No
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) 	48 V
<ul style="list-style-type: none"> • permissible range, lower limit (DC) 	48 V
<ul style="list-style-type: none"> • permissible range, upper limit (DC) 	125 V
Input current	
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	4.3 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 60 °C, max.	8; 6 @ Ue 146 V
— up to 70 °C, max.	6; 4 @ Ue 146 V
horizontal installation	
— up to 50 °C, max.	8
— up to 60 °C, max.	8; 6 to Ue 146 V
Input voltage	
<ul style="list-style-type: none"> • Type of input voltage 	DC
<ul style="list-style-type: none"> • Rated value (DC) 	48 V; 48 V DC to 125 V DC
<ul style="list-style-type: none"> • for signal "0" 	-146 V DC to +15 V DC
<ul style="list-style-type: none"> • for signal "1" 	30 V DC to 146 V DC
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	3.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	0.1 ms
— at "0" to "1", max.	3.5 ms
— at "1" to "0", min.	0.7 ms
— at "1" to "0", max.	3 ms
Cable length	

<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
Interrupts/diagnostics/status information	
Alarms	No
Diagnostics function	No
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	No
<ul style="list-style-type: none"> • Hardware interrupt 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) 	No
<ul style="list-style-type: none"> • Status indicator digital input (green) 	Yes
Potential separation	
Potential separation digital inputs	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels, in groups of 	8
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes; Optocoupler
Isolation	
Isolation tested with	1 500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
<ul style="list-style-type: none"> • EN 50155 	Yes; Sections 4, 5 and 12; no further agreements apply; T1, Category 1, Class A/B, EN 50155:2007 (see SIOS entry 109755985)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	-25 °C; = Tmin
<ul style="list-style-type: none"> • max. 	70 °C; = Tmax; for use on railway vehicles according to EN50155, the rated temperature range -25 ... +55 °C (T1) or 60 °C @ UL/ULhaz/ATEX/FM use applies
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. 	-40 °C
<ul style="list-style-type: none"> • max. 	70 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	2 000 m
<ul style="list-style-type: none"> • Ambient air temperature-barometric pressure-altitude 	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *

Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!

Connection method

required front connector	20-pin
--------------------------	--------

Dimensions

Width	40 mm
Height	125 mm
Depth	120 mm

Weights

Weight, approx.	200 g
-----------------	-------

Classifications

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)

[Declaration of Conformity](#)



[China RoHS](#)



General Product Approval EMV



last modified:

5/29/2024