



Figure similar

SIPLUS S7-300 SM 321 4DI NAMUR based on 6ES7321-7RD00-0AB0 with conformal coating, 0...+60 °C, digital input isolated 4 DI; 24 V DC, NAMUR/DIN 19234, for signals from the hazardous area, diagnostics-capable, PTB tested

General information	
based on	<a href="#">6ES7321-7RD00-0AB0</a>
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	50 mA
from backplane bus 5 V DC, max.	80 mA
Encoder supply	
Type of output voltage	via the inputs
Power loss	
Power loss, typ.	1.1 W
Digital inputs	
Number of digital inputs	4
Number of NAMUR inputs	4
Input voltage	
<ul style="list-style-type: none"> <li>Type of input voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	8.2 V; from internal power circuit supply
Input current	
<ul style="list-style-type: none"> <li>on wire-break, max.</li> </ul>	0.1 mA
<ul style="list-style-type: none"> <li>on short-circuit, max.</li> </ul>	8.5 mA
for NAMUR encoders	
<ul style="list-style-type: none"> <li>for signal "0", min.</li> </ul>	0.35 mA
<ul style="list-style-type: none"> <li>for signal "0", max.</li> </ul>	1.2 mA
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	2.1 mA
<ul style="list-style-type: none"> <li>for signal "1", max.</li> </ul>	7 mA
Input delay (for rated value of input voltage)	
<ul style="list-style-type: none"> <li>Input frequency (with a time delay of 0.1 ms), max.</li> </ul>	2 kHz
for NAMUR inputs	
<ul style="list-style-type: none"> <li>parameterizable</li> </ul>	Yes; 0.1 / 0.5 / 3 / 15 / 20 ms (plus 0.25 ms preparation time)
Cable length	
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	200 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> <li>NAMUR encoder</li> </ul>	Yes; Two-wire connection
Interrupts/diagnostics/status information	
Diagnostics function	Yes

<b>Diagnoses</b>	
• Diagnostic information readable	Yes
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
• Channel fault indicator F (red)	Yes
<b>Ex(i) characteristics</b>	
Module for Ex(i) protection	Yes
<b>maximum values for connecting terminals for gas group IIC</b>	
• Uo (no-load voltage), max.	10 V
• Io (short-circuit current), max.	14.1 mA
• Po (power output), max.	33.7 mW
• Co (permissible external capacity), max.	3 µF
• Lo (permissible external inductivity), max.	100 mH
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
• between the channels	Yes; 60 V DC/30 V AC when used in the hazardous area; 400 V DC/250 V AC when used in NON-hazardous area
• between the channels, in groups of	1
• between the channels and backplane bus	Yes; 60 V DC/30 V AC when used in the hazardous area; 400 V DC/250 V AC when used in NON-hazardous area
• Between the channels and load voltage L+	Yes; 60 V DC/30 V AC when used in the hazardous area; 400 V DC/250 V AC when used in NON-hazardous area
<b>Standards, approvals, certificates</b>	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
<b>Use in hazardous areas</b>	
• ATEX marking	ATEX II 3 G (2) GD Ex nA [ib Gb] [ib IIIC Db] IIC T4 Gc
• ATEX certificate	10 ATEX 0062X
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	0 °C; = Tmin
• max.	60 °C; = Tmax
<b>Ambient temperature during storage/transportation</b>	
• min.	-40 °C
• max.	70 °C
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
<b>Relative humidity</b>	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
<b>Resistance</b>	
<b>Use in stationary industrial systems</b>	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *

<b>Usage in industrial process technology</b>	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

<b>Remark</b>	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!

<b>Connection method</b>	
required front connector	20-pin

<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm

<b>Weights</b>	
Weight, approx.	230 g

<b>Classifications</b>			
		<b>Version</b>	<b>Classification</b>
	eClass	14	27-24-22-04
	eClass	12	27-24-22-04
	eClass	9.1	27-24-22-04
	eClass	9	27-24-22-04
	eClass	8	27-24-22-04
	eClass	7.1	27-24-22-04
	eClass	6	27-24-22-04
	ETIM	10	EC001419
	ETIM	9	EC001419
	ETIM	8	EC001419
	ETIM	7	EC001419
	IDEA	4	3566
	UNSPSC	15	32-15-17-05

<b>Approvals / Certificates</b>	
<b>General Product Approval</b>	<b>EMV</b>

[Manufacturer Declaration](#)

[China RoHS](#)



last modified:

5/29/2024