

### product type designation



Figure similar

### CP 443-5 Extended

SIPLUS NET CP 443-5 based on 6GK7443-5DX05-0XE0 with conformal coating, 0...+60 °C, communications processor extended for connection of SIMATIC S7-400 on PROFIBUS, DP, S5-compatible PG/OP and S7 communication

Technical Product Detail Page

<https://l.siemens.com/1P6AG1443-5DX05-4XE0>

### transfer rate

transfer rate

- at the 1st interface / according to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### interfaces

number of interfaces / according to Industrial Ethernet

0

number of electrical connections

- at the 1st interface / according to PROFIBUS

1

type of electrical connection

- at the 1st interface / according to PROFIBUS

9-pin Sub-D socket (RS485)

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage / 1 / from backplane bus

5 V

relative symmetrical tolerance / at DC

- at 5 V

5 %

consumed current

- from backplane bus / at DC / at 5 V / typical

0.6 A

power loss [W]

3 W

### ambient conditions

ambient temperature

- during operation
- during storage
- during transport

0 ... 60 °C

-40 ... +70 °C

-40 ... +70 °C

installation altitude / at height above sea level / maximum

5000 m

ambient condition / relating to ambient temperature - air pressure - installation altitude

Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

relative humidity

- with condensation / according to IEC 60068-2-38 / maximum

100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation

chemical resistance / to commercially available cooling lubricants

Yes; incl. airborne diesel and oil droplets

resistance to biologically active substances

- conformity according to EN 60721-3-3
- conformity according to EN 60721-3-6

Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request

Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)

resistance to chemically active substances

- conformity according to EN 60721-3-3

Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused

<ul style="list-style-type: none"> <li>conformity according to EN 60721-3-6</li> </ul>	interfaces during operation. Yes
resistance to mechanically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation. Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
<b>design, dimensions and weights</b>	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.65 kg
<b>product features, product functions, product components / general</b>	
number of units <ul style="list-style-type: none"> <li>per CPU / maximum</li> <li>note</li> </ul>	14 The number of CPs that can be operated as DP masters depends on the number of CP 443-1 Advanced processors operating in the S7-400 station as PROFINET IO controllers. Up to 10 CPs can be operated in total: up to 4 as PROFINET IO controllers (CP 443-1 Advanced); up to 10 as DP masters (CP 443-5 Extended)
<b>performance data / open communication</b>	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	32
data volume <ul style="list-style-type: none"> <li>as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	240 byte
<b>performance data / PROFIBUS DP</b>	
service / as DP master <ul style="list-style-type: none"> <li>DPV1</li> </ul>	Yes
number of DP devices <ul style="list-style-type: none"> <li>on DP master / operable</li> </ul>	125
data volume <ul style="list-style-type: none"> <li>of the address range of the inputs / as DP master / total</li> <li>of the address range of the outputs / as DP master / total</li> <li>of the address range of the inputs / per DP device</li> <li>of the address range of the outputs / per DP device</li> </ul>	4096 byte 4096 byte 244 byte 244 byte
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication <ul style="list-style-type: none"> <li>maximum</li> </ul>	48
<b>performance data / multi-protocol mode</b>	
number of active connections / with multi-protocol mode <ul style="list-style-type: none"> <li>without DP / maximum</li> <li>with DP / maximum</li> </ul>	59 54
<b>product functions / management, configuration, engineering</b>	
configuration software <ul style="list-style-type: none"> <li>required</li> </ul>	STEP 7 V5.4 SP4 or higher / STEP 7 Professional V12 (TIA Portal) or higher
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
<b>product functions / routing</b>	
number of possible connections / with data set routing / maximum	30
<b>product functions / time</b>	
product function / pass on time synchronization	Yes

protocol / is supported	
<ul style="list-style-type: none"> <li>• SIMATIC time synchronization (SIMATIC Time)</li> </ul>	Yes

**further information / internet links**

internet link	
<ul style="list-style-type: none"> <li>• to website: Selection guide for cables and connectors</li> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to web page: SiePortal</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://siemens.com/cax">https://siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**security information**

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>
----------------------	---

**Approvals / Certificates**

**General Product Approval**



[Manufacturer Declaration](#)

[China RoHS](#)



[China RoHS](#)

**General Product Approval**      **EMV**      **For use in hazardous locations**



[CCC-Ex](#)



IECEX

**For use in hazardous locations**



last modified:

3/10/2026