

### product type designation



Figure similar

### TIM 4R-IE DNP3

\*\*\*spare part\*\*\* SIPLUS NET TIM 4R-IE DNP3 based on 6NH7803-4BA00-0AA0 with conformal coating, -25...+70 °C, TIM 4R-IE DNP3 communications module for SIMATIC S7-300, S7-400, PC; with two RS 232/RS 485 interfaces for DNP3 communication via classic wide area networks and two RJ45 interfaces for DNP3 communication via IP- based networks (WAN or LAN)

Technical Product Detail Page

<https://l.siemens.com/1P6AG1803-4BA00-7AA0>

### transfer rate

transfer rate

- for Industrial Ethernet
- according to RS 232

10 ... 100 Mbit/s  
9600 ... 115200 bit/s

### interfaces

number of interfaces / according to Industrial Ethernet

2

number of electrical connections

- for external data transmission / according to RS 232
- for power supply

2  
1

type of electrical connection

- of Industrial Ethernet interface

RJ45 port

type of electrical connection

- at interface 1 / for external data transmission
- at interface 2 / for external data transmission
- for power supply

9 pin Sub-D-connector, RS232 switchable to RS485  
9-pole D-sub connector, RS232 can be switched to RS485  
2-pole plugable terminal block

design of the removable storage

- C-PLUG

Yes

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage

24 V

supply voltage

20.4 ... 28.8 V

supply voltage / external / at DC / rated value

24 V

supply voltage / external / at DC / rated value

20.4 ... 28.8 V

consumed current

- from backplane bus / at DC / at 24 V / maximum
- from external supply voltage / at DC / at 24 V / maximum

0.2 A  
0.17 A

power loss [W]

4.6 W

product extension / optional / backup battery

Yes

type of battery

Lithium AA / 3.6 V / 2.3 Ah

backup current

- typical
- maximum

100 µA  
160 µA

### ambient conditions

ambient temperature

- during operation
- during storage

-25 ... +70 °C  
-40 ... +70 °C

<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity <ul style="list-style-type: none"> <li>with condensation / according to IEC 60068-2-38 / maximum</li> </ul>	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation. Yes
resistance to mechanically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation. Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
<b>design, dimensions and weights</b>	
module format	Compact module S7-300 double width
width	80 mm
height	125 mm
depth	120 mm
net weight	0.4 kg
<b>product features, product functions, product components / general</b>	
number of units <ul style="list-style-type: none"> <li>note</li> </ul>	Number of TIMs per S7-300 / S7-400: 1
wire length <ul style="list-style-type: none"> <li>with RS 232 interface / maximum</li> <li>with RS 485 interface / maximum</li> </ul>	6 m 30 m
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication <ul style="list-style-type: none"> <li>maximum</li> <li>with PG connections / maximum</li> <li>with OP connections / maximum</li> </ul>	5; only via LAN 2 1
service <ul style="list-style-type: none"> <li>PG/OP communication</li> </ul>	Yes
<b>performance data / telecontrol</b>	
suitability for use <ul style="list-style-type: none"> <li>node station</li> <li>substation</li> <li>TIM control center</li> </ul>	Yes Yes Yes
protocol / is supported <ul style="list-style-type: none"> <li>DNP3</li> <li>Modbus RTU</li> </ul>	Yes Yes
product function / data buffering if connection is aborted	Yes; 200,000 data points with one master
number of DNP3 masters	

• for Ethernet / maximum	8
• with RS 232 interface / maximum	1
number of Modbus RTU devices / maximum	1

**product functions / management, configuration, engineering**

configuration software	
• required	SINAUT ST7 ES
storage location / of TIM configuration data	on the CPU or TIM

**product functions / time**

product component / hardware real time clock	Yes
product feature / hardware real time clock w. battery backup	Yes
accuracy / of the hardware real time clock / per day / maximum	4 s
time synchronization	
• from NTP-server	Yes

**further information / internet links**

internet link	
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="https://siemens.com/cax">https://siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**security information**

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert.">https://www.siemens.com/cert.</a> (V4.7)
----------------------	--

**Approvals / Certificates**


**General Product Approval**

[Manufacturer Declaration](#)


[China RoHS](#)



**General Product Approval**



last modified: 3/10/2026 