



SIPLUS ET 200SP AI 4xU/I 2-wire ST TX rail based on 6ES7134-6HD01-0BA1 with conformal coating, -40...+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), analog input module, suitable for BU type A0, A1, color code CC03, module diagnostics, 16-bit, +/-0.3%

| General information | |
|--|---|
| Product type designation | AI 4x U/I 2-wire |
| Firmware version | |
| • FW update possible | Yes |
| based on | 6ES7134-6HD01-0BA1 |
| usable BaseUnits | BU type A0, A1 |
| Color code for module-specific color-coded label | CC03 |
| Product function | |
| • I&M data | Yes; I&M0 to I&M3 |
| • Isochronous mode | No |
| • Measuring range scalable | No |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275 |
| Operating mode | |
| • Oversampling | No |
| • MSI | No |
| CiR - Configuration in RUN | |
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN | No |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption, max. | 37 mA; without sensor supply |
| Encoder supply | |
| 24 V encoder supply | |
| • 24 V | Yes |
| • Short-circuit protection | Yes |
| • Output current, max. | 20 mA; max. 50 mA per channel for a duration < 10 s |
| Power loss | |
| Power loss, typ. | 0.85 W; Without encoder supply voltage |
| Address area | |
| Address space per module | |
| • Address space per module, max. | 8 byte; + 1 byte for QI information |
| Hardware configuration | |
| Automatic encoding | Yes |
| • Mechanical coding element | Yes |

| | |
|--|--|
| • Type of mechanical coding element | Type A |
| Selection of BaseUnit for connection variants | |
| • 2-wire connection | BU type A0, A1 |
| Analog inputs | |
| Number of analog inputs | 4; > 60 °C max. 1x ±20 mA or 4x ±10 V permissible |
| permissible input voltage for voltage input (destruction limit), max. | 30 V |
| permissible input current for current input (destruction limit), max. | 50 mA |
| Cycle time (all channels), min. | Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels) |
| Input ranges (rated values), voltages | |
| • 0 to +10 V — Input resistance (0 to 10 V) | Yes; 15 bit 120 kΩ |
| • 1 V to 5 V — Input resistance (1 V to 5 V) | Yes; 15 bit 120 kΩ |
| • -10 V to +10 V — Input resistance (-10 V to +10 V) | Yes; 16 bit incl. sign 120 kΩ |
| • -5 V to +5 V — Input resistance (-5 V to +5 V) | Yes; 16 bit incl. sign 120 kΩ |
| Input ranges (rated values), currents | |
| • 0 to 20 mA — Input resistance (0 to 20 mA) | Yes; 15 bit 100 Ω; + approx. 0.7 V diode forward voltage |
| • 4 mA to 20 mA — Input resistance (4 mA to 20 mA) | Yes; 15 bit 100 Ω; + approx. 0.7 V diode forward voltage |
| Cable length | |
| • shielded, max. | 1 000 m; 200 m for voltage measurement |
| Analog value generation for the inputs | |
| Measurement principle | integrating (Sigma-Delta) |
| Integration and conversion time/resolution per channel | |
| • Resolution with overrange (bit including sign), max. | 16 bit |
| • Integration time, parameterizable | Yes |
| • Interference voltage suppression for interference frequency f1 in Hz | 16.6 / 50 / 60 Hz |
| • Conversion time (per channel) | 180 / 60 / 50 ms |
| Smoothing of measured values | |
| • Number of smoothing levels | 4; None; 4/8/16 times |
| • parameterizable | Yes |
| Encoder | |
| Connection of signal encoders | |
| • for voltage measurement | Yes |
| • for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max. | Yes 650 Ω |
| • for current measurement as 4-wire transducer | No |
| Errors/accuracies | |
| Linearity error (relative to input range), (+/-) | 0.01 % |
| Temperature error (relative to input range), (+/-) | 0.005 %/K |
| Crosstalk between the inputs, min. | 50 dB |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-) | 0.05 % |
| Operational error limit in overall temperature range | |
| • Voltage, relative to input range, (+/-) | 0.7 % |
| • Current, relative to input range, (+/-) | 0.7 % |
| Basic error limit (operational limit at 25 °C) | |
| • Voltage, relative to input range, (+/-) | 0.3 % |
| • Current, relative to input range, (+/-) | 0.3 % |
| Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency | |
| • Series mode interference (peak value of interference < rated value of input range), min. | 70 dB |
| • Common mode voltage, max. | 10 V |

| | |
|---|--|
| • Common mode interference, min. | 90 dB |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| • Diagnostic alarm | Yes |
| • Limit value alarm | No |
| Diagnoses | |
| • Monitoring the supply voltage | Yes |
| • Wire break | Yes; at 4 to 20 mA |
| • Short-circuit | Yes; with 1 to 5 V or 2-wire mode: Short-circuit of the encoder supply to ground or of an input to the encoder supply |
| • Group error | Yes |
| • Overflow/Underflow | Yes |
| Diagnostics indication LED | |
| • Monitoring of the supply voltage (PWR-LED) | Yes; green LED |
| • Channel status display | Yes; green LED |
| • for channel diagnostics | No |
| • for module diagnostics | Yes; green/red LED |
| Potential separation | |
| Potential separation channels | |
| • between the channels | Yes; channel group-specific between 2-wire current input group and voltage input group |
| • between the channels and backplane bus | Yes |
| • between the channels and the power supply of the electronics | Yes; only for voltage inputs |
| Permissible potential difference | |
| between the inputs (UCM) | 10 V DC |
| Isolation | |
| Isolation tested with | 750 V DC (type test) and according to EN 50155 (routine test) |
| Standards, approvals, certificates | |
| Suitable for applications according to AMS 2750 | Yes; Declaration of Conformity, see online support entry 109757262 |
| Suitable for applications according to CQI-9 | Yes |
| Railway application | |
| • EN 50121-3-2 | Yes; EMC for rail vehicles |
| • EN 50121-4 | Yes; EMC for signal and telecommunications systems |
| • EN 50121-5 | Yes; EMC for fixed installations and railway power supply equipment |
| • EN 50124-1 | Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC |
| • EN 50125-1 | Yes; Rail vehicles - see ambient conditions |
| • EN 50125-2 | Yes; Stationary electrical equipment - see ambient conditions |
| • EN 50125-3 | Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track) |
| • EN 50155 | Yes; Rail vehicles - temperature class OT4, ST1/ST2, horizontal mounting position |
| • EN 61373 | Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B |
| • Fire protection acc. to EN 45545-2 | Yes; For proof of conformity, see Service & Support |
| Ambient conditions | |
| Ambient temperature during operation | |
| • horizontal installation, min. | -40 °C; = Tmin (incl. condensation/frost) |
| • horizontal installation, max. | 70 °C; = Tmax; +85 °C for 10 min (OT4, ST1/ST2 acc. to EN 50155) |
| • vertical installation, min. | -40 °C; = Tmin |
| • vertical installation, max. | 50 °C; = Tmax |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 2 000 m |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) |
| Relative humidity | |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation |
| Resistance | |
| Coolants and lubricants | |

| | | |
|---|---|-----------------------|
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air | |
| Use in stationary industrial systems | | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request | |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * | |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * | |
| — Against mechanical environmental conditions acc. to EN 60721-3-3 | Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) | |
| Use on land craft, rail vehicles and special-purpose vehicles | | |
| — to biologically active substances according to EN 60721-3-5 | Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request | |
| — to chemically active substances according to EN 60721-3-5 | Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * | |
| — to mechanically active substances according to EN 60721-3-5 | Yes; Class 5S3 incl. sand, dust; * | |
| — Against mechanical environmental conditions acc. to EN 60721-3-5 | Yes; Class 5M2 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) | |
| — against mechanical environmental conditions in agriculture acc. to ISO 15003 | Yes; level 1 (Location LE) using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) | |
| Usage in industrial process technology | | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) | |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) | |
| Remark | | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! | |
| Conformal coating | | |
| • Coatings for printed circuit board assemblies acc. to EN 61086 | Yes; Class 2 for high reliability | |
| • Protection against fouling acc. to EN 60664-3 | Yes; Type 1 protection | |
| • Electronic equipment on rolling stock acc. to EN 50155 | Yes; Class PC2 protective coating acc. to EN 50155:2017 | |
| • Military testing according to MIL-I-46058C, Amendment 7 | Yes; Discoloration of coating possible during service life | |
| • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A | |
| Dimensions | | |
| Width | 15 mm | |
| Height | 73 mm | |
| Depth | 58 mm | |
| Weights | | |
| Weight, approx. | 31 g | |
| Other | | |
| Note: | for use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A, Online Support article 109736776 | |
| Classifications | | |
| | Version | Classification |
| eClass | 14 | 27-24-26-01 |
| eClass | 12 | 27-24-26-01 |
| eClass | 9.1 | 27-24-26-01 |
| eClass | 9 | 27-24-26-01 |
| eClass | 8 | 27-24-26-01 |
| eClass | 7.1 | 27-24-26-01 |
| eClass | 6 | 27-24-26-01 |
| ETIM | 10 | EC001596 |
| ETIM | 9 | EC001596 |
| ETIM | 8 | EC001596 |

| | | |
|--------|----|-------------|
| ETIM | 7 | EC001596 |
| IDEA | 4 | 3562 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[China RoHS](#)



General Product Approval **EMV** **Railway**

[China RoHS](#)



[Confirmation](#)

last modified:

10/23/2025