



SIPLUS ET 200SP BU20-P16+A0+2D TX rail based on 6ES7193-6BP00-0DU0 with conformal coating, -40...+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), BU type U0, push-in terminals, without AUX terminals, new load group, WxH: 20 mm x 117 mm

Figure similar

| General information | |
|---|---|
| Product type designation | BU type U0 |
| based on | 6ES7193-6BP00-0DU0 |
| Supply voltage | |
| Rated value (DC) | See manual |
| <ul style="list-style-type: none"> For P1 and P2 bus For AUX bus for process terminals | 120 V 120 V; Equal potential group to P1/P2 bus or PE 120 V |
| Rated value (AC) | See manual |
| <ul style="list-style-type: none"> For P1 and P2 bus For AUX bus for process terminals | 277 V 277 V; Equal potential group to P1/P2 bus or PE 277 V |
| external protection for power supply lines | Yes |
| Mains filter | |
| <ul style="list-style-type: none"> integrated | No |
| Current carrying capacity | |
| up to 60 °C, max. | 10 A |
| For P1 and P2 bus, max. | 10 A |
| For AUX bus, max. | 10 A |
| For process terminals, max. | 10 A; Point of contact, derating depends on the module |
| Hardware configuration | |
| Automatic encoding | Yes |
| Formation of potential groups | |
| <ul style="list-style-type: none"> New potential group Potential group continued from the left | Yes No |
| Slots | |
| <ul style="list-style-type: none"> Number of slots | 1 |
| Potential separation | |
| between backplane bus and supply voltage | Yes |
| between process terminals and supply voltage | Yes; Not applicable for process terminals 15 and 16 |
| between power bus and supply voltage | No |
| Isolation | |
| Isolation tested with | 2 545 V DC (type test) and according to EN 50155 (routine test) |
| Standards, approvals, certificates | |
| Ecological footprint | |
| <ul style="list-style-type: none"> environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 0.873 kg |

| | |
|--|---|
| — global warming potential, (during production) [CO2 eq] | 0.866 kg |
| — global warming potential, (during operation) [CO2 eq] | 0 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.0011 kg |
| Railway application | |
| • EN 50121-3-2 | Yes; EMC for rail vehicles |
| • EN 50121-4 | Yes; EMC for signal and telecommunications systems |
| • EN 50121-5 | Yes; EMC for fixed installations and railway power supply equipment |
| • EN 50124-1 | Yes; Railway applications - overvoltage category OV3; pollution degree PD2; UNm = 230 V AC |
| • EN 50125-1 | Yes; Rail vehicles - see ambient conditions |
| • EN 50125-2 | Yes; Stationary electrical equipment - see ambient conditions |
| • EN 50125-3 | Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track) |
| • EN 50155 | Yes; Rail vehicles - temperature class OT4, ST1/ST2, horizontal mounting position |
| • EN 61373 | Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B |
| • Fire protection acc. to EN 45545-2 | Yes; For proof of conformity, see Service & Support |
| Ambient conditions | |
| Ambient temperature during operation | |
| • horizontal installation, min. | -40 °C; = Tmin (incl. condensation/frost) |
| • horizontal installation, max. | 70 °C; = Tmax; +85 °C for 10 min (OT4, ST1/ST2 acc. to EN 50155) |
| • vertical installation, min. | -40 °C; = Tmin |
| • vertical installation, max. | 50 °C; = Tmax |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 2 000 m |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) |
| Relative humidity | |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation |
| Resistance | |
| Coolants and lubricants | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| — Against mechanical environmental conditions acc. to EN 60721-3-3 | Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) |
| Use on land craft, rail vehicles and special-purpose vehicles | |
| — to biologically active substances according to EN 60721-3-5 | Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request |
| — to chemically active substances according to EN 60721-3-5 | Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-5 | Yes; Class 5S3 incl. sand, dust; * |
| — Against mechanical environmental conditions acc. to EN 60721-3-5 | Yes; Class 5M2 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) |
| — against mechanical environmental conditions in agriculture acc. to ISO 15003 | Yes; level 1 (Location LE) using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0) |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental | * The supplied plug covers must remain in place over the unused interfaces |

conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

during operation!

| Conformal coating | |
|---|--|
| <ul style="list-style-type: none"> Coatings for printed circuit board assemblies acc. to EN 61086 Protection against fouling acc. to EN 60664-3 Electronic equipment on rolling stock acc. to EN 50155 Military testing according to MIL-I-46058C, Amendment 7 Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | <p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Class PC2 protective coating acc. to EN 50155:2017</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p> |

Connection method

| Terminals | |
|---|---|
| <ul style="list-style-type: none"> Terminal type system-integrated shield connection Conductor cross-section, min. Conductor cross-section, max. Number of process terminals to I/O module Number of terminals to AUX bus Number of add-on terminals Number of terminals with connection to P1 and P2 bus | <p>Push-in terminal</p> <p>Yes; Optional</p> <p>0.14 mm²; 0.2 mm² without wire end ferrule</p> <p>2.5 mm²; 1.5 mm² with wire end ferrule</p> <p>16</p> <p>0</p> <p>0</p> <p>2</p> |

Dimensions

| | |
|--------|--------|
| Width | 20 mm |
| Height | 117 mm |
| Depth | 35 mm |

Weights

| | |
|-----------------|------|
| Weight, approx. | 50 g |
|-----------------|------|

Other

| | |
|-------|--|
| Note: | for use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A, Online Support article 109736776 |
|-------|--|

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-26-03 |
| eClass | 12 | 27-24-26-03 |
| eClass | 9.1 | 27-24-26-03 |
| eClass | 9 | 27-24-26-03 |
| eClass | 8 | 27-24-26-03 |
| eClass | 7.1 | 27-24-26-03 |
| eClass | 6 | 27-24-26-03 |
| ETIM | 10 | EC001598 |
| ETIM | 9 | EC001598 |
| ETIM | 8 | EC001598 |
| ETIM | 7 | EC001598 |
| IDEA | 4 | 3560 |
| UNSPSC | 15 | 32-15-17-04 |

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[China RoHS](#)

[China RoHS](#)



| General Product Approval | EMV | Railway | Environment |
|--------------------------|-----|---------|-------------|
| | | | |



[Confirmation](#)



last modified:

10/23/2025