

SIMATIC IPC347G (rack PC, 19", 4 U); 2x Gbit Ethernet, 1x DP, 1x VGA, 2x USB on the front, 4x USB on the rear, 2x USB internal, 2x serial, 2x PS/2, audio; no DVD +/-RW; 100/240 V industrial power supply, without power supply cable
 Pentium Dual Core G4400 (2C/2T, 3.3 GHz, 3 MB cache); 1 TB HDD; 8 GB DDR4; PS 350W; without operating system, drivers & documentation on USB flash drive

Installation type/mounting	
Mounting	For horizontal and vertical mounting
Design	Rack PC, 19", 4U
Supply voltage	
Type of supply voltage	100 - 240 V AC
Line frequency	<ul style="list-style-type: none"> • Rated value 50 Hz Yes • Rated value 60 Hz Yes
Processor	
Processor type	Core i7-6700 (4C/4T, 3.6 (4.0) GHz, 8 MB Cache)
Chipset	Intel H110
Drives	
Hard disk	HDD & SSD
Memory	
Main memory	4 / 8 / 16 GB, supports up to 32 GB
Capacity of main memory, max.	32 Gbyte
Hardware configuration	
Slots	<ul style="list-style-type: none"> • free slots 3x PCI, 1x PCIe (x16), 1xPCIe (x4) (4 or 2 lanes), 2x PCIe (x4) (1 lane)
Interfaces	
USB port	4x USB 3.0 on rear panel, 2x USB 2.0 on front panel, 2x USB 2.0 internal and 2x pin header USB
Connection for keyboard/mouse	2x PS/2
Multimedia	<ul style="list-style-type: none"> • Audio In/Out Yes • Microphone In Yes
Video interfaces	<ul style="list-style-type: none"> • Graphics interface 1x DisplayPort, 1x VGA
Industrial Ethernet	<ul style="list-style-type: none"> • Industrial Ethernet interface <ul style="list-style-type: none"> — 100 Mbps Yes — 1000 Mbps Yes
EMC	
Interference immunity against discharge of static electricity	<ul style="list-style-type: none"> • Interference immunity against discharge of static electricity ±4 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2
Interference immunity against high-frequency electromagnetic fields	<ul style="list-style-type: none"> • Interference immunity against high frequency radiation 10 V/m, 80 MHz to 2 GHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2 GHz to 2.7 GHz, 80 % AM acc. to IEC 61000-4-3; 10 V, 10 kHz to 80 MHz, 80 % AM acc. to IEC 61000-4-6
Interference immunity to cable-borne interference	<ul style="list-style-type: none"> • Interference immunity on supply cables ±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric • Interference immunity on signal cables >30m ±2 kV acc. to IEC 61000-4-4, burst; length > 30 m; ±2 kV acc. to IEC 61000-4-5, surge; length > 30 m • Interference immunity on signal cables < 30m ±1 kV acc. to IEC 61000-4-4, Burst
Interference immunity against voltage surge	<ul style="list-style-type: none"> • asymmetric interference ±2 kV acc. to IEC 61000-4-5, surge asymmetric • symmetric interference ±1 kV acc. to IEC 61000-4-5, surge symmetric

Emission of conducted and non-conducted interference	
• Interference emission via line/AC current cables	IEC 61000-6-4, CISPR 22, FCC Class A
Compliance with line harmonic distortion limits	
• Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3	Yes; EN 61000-3-2 Class D; EN 61000-3-3
Degree and class of protection	
IP (at the front)	IP20
IP (rear)	IP20
Ambient conditions	
Ambient temperature during operation	
• min.	5 °C
• max.	40 °C
Dimensions	
Width	430 mm
Height	176 mm
Depth	465.8 mm
Approvals / Certificates	
General Product Approval	

[Miscellaneous](#)

[Manufacturer Declaration](#)



[Miscellaneous](#)

General Product Approval	EMV
--------------------------	-----



[BIS CRS](#)



[China RoHS](#)



other



last modified:

11/24/2025