

SIMATIC IPC347G (rack PC, 19", 4 U); 2x Gbit Ethernet, 1x DP, 1x VGA, 2x USB on the front, 4x USB on the rear, 2x USB internal, 2x serial, 2x PS/2, audio; no DVD +/-RW; 100/240 V industrial power supply, without power supply cable
Pentium Dual Core G4400 (2C/2T, 3.3 GHz, 3 MB cache); 256 GB SSD; 4 GB DDR4; PS 350W; Windows 10 IoT Enterprise for Pentium/i3/i5;

Installation type/mounting	
Mounting	For horizontal and vertical mounting
Design	Rack PC, 19", 4U
Supply voltage	
Type of supply voltage	100 - 240 V AC
Line frequency	<ul style="list-style-type: none"> • Rated value 50 Hz • Rated value 60 Hz
Yes	Yes
Yes	Yes
Processor	
Processor type	Core i7-6700 (4C/4T, 3.6 (4.0) GHz, 8 MB Cache)
Chipset	Intel H110
Drives	
Hard disk	HDD & SSD
Memory	
Main memory	4 / 8 / 16 GB, supports up to 32 GB
Capacity of main memory, max.	32 Gbyte
Hardware configuration	
Slots	<ul style="list-style-type: none"> • free slots
3x PCI, 1x PCIe (x16), 1xPCIe (x4) (4 or 2 lanes), 2x PCIe (x4) (1 lane)	
Interfaces	
USB port	4x USB 3.0 on rear panel, 2x USB 2.0 on front panel, 2x USB 2.0 internal and 2x pin header USB
Connection for keyboard/mouse	2x PS/2
Multimedia	<ul style="list-style-type: none"> • Audio In/Out • Microphone In
Yes	Yes
Yes	Yes
Video interfaces	<ul style="list-style-type: none"> • Graphics interface
1x DisplayPort, 1x VGA	
Industrial Ethernet	<ul style="list-style-type: none"> • Industrial Ethernet interface
— 100 Mbps	Yes
— 1000 Mbps	Yes
EMC	
Interference immunity against discharge of static electricity	<ul style="list-style-type: none"> • Interference immunity against discharge of static electricity
±4 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2	
Interference immunity against high-frequency electromagnetic fields	<ul style="list-style-type: none"> • Interference immunity against high frequency radiation
10 V/m, 80 MHz to 2 GHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2 GHz to 2.7 GHz, 80 % AM acc. to IEC 61000-4-3; 10 V, 10 kHz to 80 MHz, 80 % AM acc. to IEC 61000-4-6	
Interference immunity to cable-borne interference	<ul style="list-style-type: none"> • Interference immunity on supply cables • Interference immunity on signal cables >30m • Interference immunity on signal cables < 30m
±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric	
±2 kV acc. to IEC 61000-4-4, burst; length > 30 m; ±2 kV acc. to IEC 61000-4-5, surge; length > 30 m	
±1 kV acc. to IEC 61000-4-4, Burst	
Interference immunity against voltage surge	<ul style="list-style-type: none"> • asymmetric interference • symmetric interference
±2 kV acc. to IEC 61000-4-5, surge asymmetric	
±1 kV acc. to IEC 61000-4-5, surge symmetric	

Emission of conducted and non-conducted interference	
• Interference emission via line/AC current cables	IEC 61000-6-4, CISPR 22, FCC Class A
Compliance with line harmonic distortion limits	
• Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3	Yes; EN 61000-3-2 Class D; EN 61000-3-3
Degree and class of protection	
IP (at the front)	IP20
IP (rear)	IP20
Ambient conditions	
Ambient temperature during operation	
• min.	5 °C
• max.	40 °C
Dimensions	
Width	430 mm
Height	176 mm
Depth	465.8 mm
Approvals / Certificates	
General Product Approval	

[Miscellaneous](#)

[Manufacturer Declaration](#)



[Miscellaneous](#)

General Product Approval	EMV
--------------------------	-----



[BIS CRS](#)



[China RoHS](#)



other



last modified:

5/6/2026