



SIMATIC IPC347G (rack PC, 19", 4 U); 2x Gbit Ethernet, 1x DP, 1x VGA, 2x USB on the front, 4x USB on the rear, 2x USB internal, 2x serial, 2x PS/2, audio; no DVD +/-RW; 100/240 V industrial power supply, without power supply cable
Pentium Dual Core G4400 (2C/2T, 3.3 GHz, 3 MB cache); 256 GB SSD; 4 GB DDR4; PS 350W; without operating system, drivers & documentation on USB flash drive

| Installation type/mounting | |
|---|---|
| Mounting | For horizontal and vertical mounting |
| Design | Rack PC, 19", 4U |
| Supply voltage | |
| Type of supply voltage | 100 - 240 V AC |
| Line frequency | <ul style="list-style-type: none"> Rated value 50 Hz Yes Rated value 60 Hz Yes |
| Processor | |
| Processor type | Core i7-6700 (4C/4T, 3.6 (4.0) GHz, 8 MB Cache) |
| Chipset | Intel H110 |
| Drives | |
| Hard disk | HDD & SSD |
| Memory | |
| Main memory | 4 / 8 / 16 GB, supports up to 32 GB |
| Capacity of main memory, max. | 32 Gbyte |
| Hardware configuration | |
| Slots | <ul style="list-style-type: none"> free slots 3x PCI, 1x PCIe (x16), 1xPCIe (x4) (4 or 2 lanes), 2x PCIe (x4) (1 lane) |
| Interfaces | |
| USB port | 4x USB 3.0 on rear panel, 2x USB 2.0 on front panel, 2x USB 2.0 internal and 2x pin header USB |
| Connection for keyboard/mouse | 2x PS/2 |
| Multimedia | <ul style="list-style-type: none"> Audio In/Out Yes Microphone In Yes |
| Video interfaces | <ul style="list-style-type: none"> Graphics interface 1x DisplayPort, 1x VGA |
| Industrial Ethernet | <ul style="list-style-type: none"> Industrial Ethernet interface <ul style="list-style-type: none"> 100 Mbps Yes 1000 Mbps Yes |
| EMC | |
| Interference immunity against discharge of static electricity | <ul style="list-style-type: none"> Interference immunity against discharge of static electricity ±4 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2 |
| Interference immunity against high-frequency electromagnetic fields | <ul style="list-style-type: none"> Interference immunity against high frequency radiation 10 V/m, 80 MHz to 2 GHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2 GHz to 2.7 GHz, 80 % AM acc. to IEC 61000-4-3; 10 V, 10 kHz to 80 MHz, 80 % AM acc. to IEC 61000-4-6 |
| Interference immunity to cable-borne interference | <ul style="list-style-type: none"> Interference immunity on supply cables ±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric Interference immunity on signal cables >30m ±2 kV acc. to IEC 61000-4-4, burst; length > 30 m; ±2 kV acc. to IEC 61000-4-5, surge; length > 30 m Interference immunity on signal cables < 30m ±1 kV acc. to IEC 61000-4-4, Burst |
| Interference immunity against voltage surge | <ul style="list-style-type: none"> asymmetric interference ±2 kV acc. to IEC 61000-4-5, surge asymmetric |

| | |
|---|--|
| • symmetric interference | ±1 kV acc. to IEC 61000-4-5, surge symmetric |
| Emission of conducted and non-conducted interference | |
| • Interference emission via line/AC current cables | IEC 61000-6-4, CISPR 22, FCC Class A |
| Compliance with line harmonic distortion limits | |
| • Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3 | Yes; EN 61000-3-2 Class D; EN 61000-3-3 |

Degree and class of protection

| | |
|-------------------|------|
| IP (at the front) | IP20 |
| IP (rear) | IP20 |

Ambient conditions

| | |
|---|-------|
| Ambient temperature during operation | |
| • min. | 5 °C |
| • max. | 40 °C |

Dimensions

| | |
|--------|----------|
| Width | 430 mm |
| Height | 176 mm |
| Depth | 465.8 mm |

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



[Miscellaneous](#)

General Product Approval **EMV**



[BIS CRS](#)



[China RoHS](#)



other



IECEX

last modified:

5/6/2026