

SIMATIC IPC647E (Rack PC, 19", 2U); 3x Gbit Ethernet (IE/PN), RJ45; 1x DVI-D, 2x displayport, 1x COM1, audio, 4x USB 3.1, 2x USB 3.1 (Typ C) rear side; 2x USB 3.0 front, 1x USB3.1 internally; 1x M.2 Slot internally; temperature and fan monitoring, watchdog; card retainer; Core i7-8700 (6C/12T, 3.2 (4.6) GHz, 12 MB cache, TB, VT-D, AMT); Board 4 slots: 2x PCI, 2x PCIe x16 (8 L); 480 GB SSD 2.5" SATA; Enclosure with drive support Type A (for rack units on the front); 100/240 V AC industrial power supply unit; 8 GB DDR4 SDRAM (2x 4 GB), Dual Channel; Without expansion (HW); Windows 10 IoT Enterprise 2019 LTSC MUI (de, en, fr, it, es), 64-bit (for Core i7/Xeon); Without expansions; Power supply cable China

| General information | |
|--|--|
| Product type designation | IPC647E |
| Installation type/mounting | |
| Mounting | For horizontal installation; prepared for telescopic rails; 19" mounting bracket can be removed externally |
| Design | Rack PC, 19", 2U |
| Supply voltage | |
| Type of supply voltage | 100/240 V AC (autorange) 50 / 60 Hz; optional redundant 100/240 V AC |
| Line frequency | |
| <ul style="list-style-type: none"> Rated value 50 Hz Rated value 60 Hz | Yes Yes |
| Mains buffering | |
| <ul style="list-style-type: none"> Mains/voltage failure stored energy time | 20 ms |
| Processor | |
| Processor type | Intel Xeon E-2278GE (8C/16T, 3.3 (4.7) GHz, 16 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Xeon E-2176G (6C/12T, 3.7 (4.7) GHz, 12 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Core i7-8700 (6C/12T, 3.2 (4.6) GHz, 12 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Core i5-8500 (6C/6T, 3.0 (4.1) GHz, 9 MB Cache, Turbo Boost 2.0, VT-x/-d-Technology, iAMT); Intel Core i3-8100 (4C/4T, 3.6 GHz, 6 MB Cache, VT-x/-d-Technology) |
| Chipset | Intel C246 |
| Graphic | |
| Graphics controller | Onboard Intel UHD graphics P630/630 integrated in processor; graphics card NVIDIA Quadro P400 PCIe (x16) triple head (optional) |
| Drives | |
| Hard disk | 1x 1 TB 3.5" SATA HDD, 2x 1 TB 3.5" SATA HDD, RAID1 2x 1 TB 3.5" SATA HDD, RAID1 2x 1 TB 3.5" SATA HDD (Enterprise), RAID1 2x 2 TB 3.5" SATA HDD (Enterprise), RAID1 2x 2 TB 3.5" SAS HDD (Enterprise) with PCIe x8 RAID controller incl. ZMCP module |
| SSD | Yes; 1x 480 GB 2.5" SATA SSD, 1x 960 GB 2.5" SATA SSD, 2x 480 GB 2.5" SATA SSD, RAID1 2x 480 GB 2.5" SATA SSD; 1x 512 GB M.2 NVMe SSD, 1x 1 024 GB M.2 NVMe SSD |
| Slot for drives | Mounting internally in vibration/shock-absorbing drive cage Type B or mounting on the front in removable trays (hot swap in RAID configurations) in drive cage Type A; mounting internally on the fixed drive cage optional |
| Memory | |
| Main memory | 4 GB to 128 GB DDR4 2666 SDRAM DIMM, ECC optional |
| Capacity of main memory, max. | 128 Gbyte |
| Interfaces | |
| Interfaces/bus type | 1x COM1, 1x COM2 (optional), 2x DisplayPort, 1x DVI-D, audio (microphone in, line in, line out), 9x USB, 3x Gigabit Ethernet |
| serial interface | COM1: 1x RS 232, COM2 (optional): 1x RS 232 |
| Video interfaces | |
| <ul style="list-style-type: none"> Graphics interface | 2x DisplayPort and 1x DVI-D onboard; 1x VGA via DP-VGA adapter cable (optional); graphics card PCIe (x16), Triple Head (3x mini DisplayPort, 2 GB graphics memory, 3x mini DisplayPort to DisplayPort adapter cable) (optional) |
| Industrial Ethernet | |
| <ul style="list-style-type: none"> Industrial Ethernet interface | |

| | |
|---|--|
| — 100 Mbps | Yes |
| — 1000 Mbps | Yes |
| Interrupts/diagnostics/status information | |
| LED status display | Power, HDD, Ethernet 1, Ethernet 2, Ethernet 3, Watchdog, Temp, Fan, HDD1 alarm, HDD0 alarm |
| Integrated Functions | |
| Monitoring functions | |
| • Temperature monitoring | Yes |
| • Fan | Yes |
| • Monitoring function via network | Optional |
| Degree and class of protection | |
| IP (at the front) | IP41 |
| IP (rear) | IP20 |
| Standards, approvals, certificates | |
| CE mark | Yes; For use in industrial areas as well as domestic, business and commercial environments (emitted interference: EN 61000-6-3:2007 +A1:2011, noise immunity: EN 61000-6-2:2005) |
| CSA approval | Yes; CAN/CSA-C22.2 No. 61010-2-201 Second Edition |
| UL approval | Yes; UL 61010-2-201 Second Edition, File E85972 |
| cULus | Yes; UL 61010-2-201 Second Edition; CAN/CSA-C22.2 No. 61010-2-201 Second Edition |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| Dust protection | With front door closed: G2 EN 779, 99% of particles > 0.5 mm are filtered |
| Marine approval | |
| • Germanischer Lloyd (GL) | Yes; Only with SSD |
| • American Bureau of Shipping (ABS) | Yes; Only with SSD |
| • Bureau Veritas (BV) | Yes; Only with SSD |
| • Det Norske Veritas (DNV) | Yes; Only with SSD |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | 0 °C; Max. 10 °C/h (no condensation) |
| • max. | 50 °C |
| Ambient temperature during storage/transportation | |
| • min. | -20 °C; Max. 20 °C/h (no condensation) |
| • max. | 60 °C |
| Vibrations | |
| • Vibration resistance during operation acc. to IEC 60068-2-6 | Tested according to IEC 60068-2-6: 10 cycles, 10 Hz to 58 Hz: 0.0375 mm, 58 Hz to 500 Hz: 4.9 m/s ² (0.5 g) |
| Operating systems | |
| pre-installed operating system | Windows 10 Enterprise 2016 LTSB, multi-language (64-bit); Windows 10 IoT Enterprise 2019 LTSC, multi-language (64-bit); Windows Server 2016 Standard Edition incl. 5 multi-language clients (64-bit); Windows Server 2019 Standard Edition incl. 5 multi-language clients (64-bit) |
| without operating system | Yes |
| Dimensions | |
| Width | 430 mm |
| Height | 88 mm; 2U |
| Depth | 444 mm |
| Approvals / Certificates | |
| General Product Approval | |



[Manufacturer Declaration](#)



[Miscellaneous](#)

General Product Approval



[BIS CRS](#)



EMV

Maritime application



[NK / Nippon Kaiji Kyokai](#)

Dangerous goods

Environment

[Dangerous goods information](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

last modified:

5/22/2026