



Figure similar

connection cable PN for KTPX00(F) Mobile (PROFINET) length: 10 m, scope of supply: 1 connection cable

General information		
Product type designation	Connecting cable	
Standards, approvals, certificates		
CE mark	Yes	
cULus	Yes	
RCM (formerly C-TICK)	Yes	
KC approval	Yes	
Suitable for safety functions	Yes	
Ambient conditions		
Ambient temperature during operation		
• min.	0 °C	
• max.	55 °C	
Ambient temperature during storage/transportation		
• min.	-20 °C	
• max.	60 °C	
Cables		
Cable length	10 m	
Maximum tensile load	300 N	
Color of cable sheath		
• green	Yes	
Scope of supply		
Delivery quantity in pieces	1	
Other		
Merchandise	Yes	
Manufacturer name	On request	
Note:	halogen-free according to EN 50267-2-1	
Classifications		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584

ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

#### Approvals / Certificates

##### General Product Approval



#### Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

9/10/2025 