



spare key type 10 for key-operated switches Mobile Panel, scope of supply: 10 spare keys

General information		
Product type designation	Spare key Mobile Panel 1st Generation	
Standards, approvals, certificates		
CE mark	Yes	
RoHS conformity	Yes	
Ambient conditions		
Ambient temperature during operation		
• min.	-40 °C	
• max.	80 °C	
Ambient temperature during storage/transportation		
• min.	-40 °C	
• max.	80 °C	
Relative humidity		
• Operation, max.	90 %	
Mechanics/material		
Material		
• Sheet steel	Yes; Handle made of plastic	
Dimensions		
Width	35 mm	
Height	18 mm	
Thickness	4 mm	
Weights		
Weight (without packaging)	30 g	
Scope of supply		
Delivery quantity in pieces	10; Coupled with key ring	
Other		
Merchandise	No	
Manufacturer name	SIEMENS AG	
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany	
Target devices	For Mobile Panel 1st Generation	
Classifications		
	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03

eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

5/22/2024 