

PC card adapter for CF memory card for SIMATIC HMI Panel with PC card slot, scope of supply: 1 PC card adapter



General information	
Product type designation	PC card adapter
Control elements	
Frame size/design	
• Standard	Yes
• Flat	Yes
Installation type/mounting	
Mounting position	Any, dependent on target device
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Input current	
Current consumption (rated value)	0 mA; No additional power consumption
Memory	
Type of memory	Personal computer memory card type II
Memory size	0 byte; Only adapter
Write protection switch	No
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
UL approval	No
cULus	No
KC approval	No
EAC (formerly Gost-R)	No
RoHS conformity	Yes
China RoHS compliance	Yes
Marine approval	Yes; Passive component, therefore dependent on target device
Use in hazardous areas	
• ATEX Zone 2	Yes; Always comply with the operating instructions of the target device.
• ATEX Zone 22	Yes; Always comply with the operating instructions of the target device.
• IECEx Zone 2	Yes; Always comply with the operating instructions of the target device.
• IECEx Zone 22	Yes; Always comply with the operating instructions of the target device.
• cULus Class I Zone 2, Division 2	Yes; Always comply with the operating instructions of the target device.
• FM Class I Division 2	Yes; Always comply with the operating instructions of the target device.
Marine approval	
• Germanischer Lloyd (GL)	Yes; Always comply with the operating instructions of the target device.
• American Bureau of Shipping (ABS)	Yes; Always comply with the operating instructions of the target device.
• Bureau Veritas (BV)	Yes; Always comply with the operating instructions of the target device.
• Det Norske Veritas (DNV)	Yes; Always comply with the operating instructions of the target device.
• Lloyds Register of Shipping (LRS)	Yes; Always comply with the operating instructions of the target device.

- Nippon Kaiji Kyokai (Class NK)
- Polski Rejestr Statkow (PRS)
- Chinese Classification Society (CCS)
- Compass working clearance

Yes; Always comply with the operating instructions of the target device.
 Yes; Always comply with the operating instructions of the target device.
 Yes; Always comply with the operating instructions of the target device.
 5 m

Ambient conditions

Suited for indoor use	Yes
Ambient temperature during operation	
• min.	0 °C; Indoor
• max.	50 °C; Indoor
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	90 %
• Condensation permissible	No; Condensation not permissible

Operating systems

Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
• Linux	No
• other	No

Mechanics/material

Enclosure material (front)	
• Sheet steel	Yes

Dimensions

Width	54 mm
Height	85.6 mm
Thickness	5 mm

Weights

Weight (without packaging)	24 g
----------------------------	------

Scope of supply

Delivery quantity in pieces	1
-----------------------------	---

Other

Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	for SIMATIC HMI devices with PC card slot

Classifications

	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

**Further information**

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

4/3/2025 