

touch pen system ELO for capacitive or resistive touch screen, ELO pen, including holder, for screwing on or gluing, for capacitive and resistive touch screens, scope of supply: 1 touch pen with cap resistive/capacitive, 1 resistive cap (in touch pen), 1 holding cord, 1 wall holder



Figure similar

General information	
Product type designation	universal touch pen system (resistive/capacitive), including support
Control elements	
Touch operation	
<ul style="list-style-type: none"> <li>operator help touch operation design (resistive)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>operator help touch operation design (capacitive)</li> </ul>	Yes
Frame size/design	
<ul style="list-style-type: none"> <li>Standard</li> </ul>	Yes; For industrial applications
<ul style="list-style-type: none"> <li>Exceptional</li> </ul>	Yes; Spare caps can be stowed in the pen
<ul style="list-style-type: none"> <li>Ergonomic</li> </ul>	Yes; With holder
Installation type/mounting	
Mounting type	Wall-mounting bracket can be mounted with mounting disk, 2x M3 screw or adhesive pads
Mounting position	Horizontal
Front mounting	Yes; also optimized for PRO Extension Unit 22.5 mm opening (from HS01)
Wall mounting/direct mounting	Yes; using approx. 60 cm retaining cord
Degree and class of protection	
IP (at the front)	IP65 (depending on mounting)
Standards, approvals, certificates	
CE mark	No; No CE marking obligation
REACH	Yes; Threaded insert screw tip - according to Article 33 of the REACH Regulation, we hereby inform you that the threaded insert supplied by us contains a substance included on the REACH Candidate List (SVHC). The substance in question is lead. CAS number: 7439-92-1 / EC number: 231-100-4
RoHS conformity	Yes
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	Yes; only suitable under certain conditions due to different environmental conditions; replacement cycle can be increased
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>min.</li> </ul>	-40 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
<ul style="list-style-type: none"> <li>max.</li> </ul>	80 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> <li>min.</li> </ul>	-40 °C
<ul style="list-style-type: none"> <li>max.</li> </ul>	80 °C
Relative humidity	
<ul style="list-style-type: none"> <li>Operation, max.</li> </ul>	95 %
Mechanics/material	

Material	
• Plastic	Yes; Attachment cord
• Aluminum	Yes; pen, anodized
Enclosure material (front)	
• Plastic	Yes; pen holder
Color	black, anodized
Enclosure color (front)	Black

#### Dimensions

Length	150 mm
Diameter	14 mm
Enclosure diameter	37 mm; Diameter wall-mounting bracket
Mounting cutout, height	39 mm; Height wall-mounting bracket

#### Weights

Weight (without packaging)	0.13 kg
Weight (with packaging)	0.14 kg

#### Scope of supply

Delivery quantity in pieces	1; 1x touch pen, 1x attachment cord, 1x resistive/capacitive cap, 1x resistive cap (in the touch pen), 1x complete wall bracket
-----------------------------	---

#### Other

Merchandise	Yes; ELO touch pen, small
Manufacturer name	QUERUM products UG
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
contacting the manufacturer	email: <a href="mailto:querumproducts@web.de">querumproducts@web.de</a>
Target devices	For common capacitive and resistive touch systems
Note:	length of the interconnecting lead approx. 55 cm ... 62 cm

#### Classifications

	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

#### Approvals / Certificates

other

[Miscellaneous](#)

#### Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

5/22/2024 