



SIMATIC Flat Panel accessories, DisplayPort cable, 15m, VESA compatible

General information	
Product type designation	DisplayPort cable
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Cables	
Cable length	15 m
Mechanics/material	
Material of cable sheath	Special PUR, flame-resistant acc. to VDE 0472 Part 804 Test Type B, Shore A 88 Flame-Retardant UR Style 20963
Material of core insulation	PP
Material property	other
• Halogen-free	Yes
• Silicone-free	Yes
Weights	
Weight, approx.	3 kg
Scope of supply	
Delivery quantity in pieces	1

Classifications			
		Version	Classification
	eClass	14	19-05-10-04
	eClass	12	19-05-10-04
	eClass	9.1	19-05-92-05
	eClass	9	19-05-92-05
	eClass	8	19-05-92-05
	eClass	7.1	19-05-92-05
	eClass	6	19-05-92-90
	ETIM	10	EC001408
	ETIM	9	EC001408
	ETIM	8	EC001408
	ETIM	7	EC001408
	IDEA	4	6599
	UNSPSC	15	43-20-22-22

Approvals / Certificates	
General Product Approval	



last modified:

8/2/2023 