



SIMATIC IFP1500 Basic Flat Panel 15" display (16:9) Touch, 1366 x 768 pixels, standard up to 5 m, for 24V DC, DisplayPort/VGA interface

General information	
Product type designation	IFP1500 Basic
Short designation	Basic Flat Panel 15" Touch
Display	
Design of display	TFT display, LED backlighting
Screen diagonal	15.6 in; 15"
On Screen Display (OSD) configuration	No
Number of colors	16 000 000; 16 million
Resolution (pixels)	
• Image resolution	1 366 x 768
• Horizontal image resolution	1 366 pixel
• Vertical image resolution	768 pixel
General features	
• Detachable from computer unit	5 m
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	50 000 h
• Backlight dimmable	Yes; 0-100 %
Control elements	
Control elements	single-touch screen
Input device	
• Integrated mouse cursor control	No
Touch operation	
• Design as touch screen	Yes; Analog-resistive
Installation type/mounting	
Design	Built-in unit
Front mounting	Yes
VESA mounting	Yes; VESA 100 x 100 integrated
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	45°
maximum permitted backward tilt angle from vertical	45°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Power loss	

Power loss, typ.	17 W	
Power loss, max.	60 W	
Interfaces		
Number of USB interfaces	2; USB 2.0 (downstream)	
USB on the rear	Yes; 2x onboard	
Video interfaces		
• DisplayPort	Yes	
Touch interfaces		
• USB	Yes; USB Type A	
Degree and class of protection		
IP (at the front)	IP65	
Standards, approvals, certificates		
CE mark	Yes	
cULus	Yes; UL 61010-1, UL 61010-2-201	
RCM (formerly C-TICK)	Yes	
KC approval	Yes	
EAC (formerly Gost-R)	Yes	
FCC	Yes	
Ambient conditions		
Ambient temperature during operation		
• min.	0 °C	
• max.	45 °C	
Ambient temperature during storage/transportation		
• min.	-20 °C	
• max.	60 °C	
Relative humidity		
• Operation, max.	85 %	
Vibrations		
• Vibration load in operation	5 m/s ²	
• Vibration load during transport/storage	10 m/s ²	
Shock testing		
• Shock load during operation	150 m/s ²	
• shock acceleration during storage/transport	250 m/s ²	
Mechanics/material		
Enclosure material (front)		
• Aluminum	Yes	
Dimensions		
Width of the housing front	406 mm	
Height of housing front	258 mm	
Mounting cutout, width	388.4 mm	
Mounting cutout, height	240.5 mm	
mounting depth	59 mm	
Weights		
Weight (without packaging)	4.1 kg	
Classifications		
	Version	Classification
eClass	14	19-20-02-01
eClass	12	19-20-02-01
eClass	9.1	19-20-02-01
eClass	9	19-20-02-01
eClass	8	19-20-02-01
eClass	7.1	19-20-02-01
eClass	6	19-20-02-01
ETIM	10	EC004862
ETIM	9	EC001428
ETIM	8	EC001428

ETIM	7	EC001428
IDEA	4	6675
UNSPSC	15	43-21-19-02

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



General Product Approval

EMV

For use in hazardous locations

[China RoHS](#)



last modified:

3/25/2025