

SIMATIC IPC277E (Nanopanel PC); 7" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 2x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply Celeron N2930 (4C/4T) 8 GB RAM; Windows 7 Ultimate SP1, 64 bit; MUI (de, en, fr, es, it) 240 GB SSD without SIMATIC software

General information	
Product type designation	IPC277E
Display	
Design of display	7" TFT touch
Screen diagonal	7 in
Resolution (pixels)	
• Horizontal image resolution	800 pixel
• Vertical image resolution	480 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	80 000 h
Control elements	
Touch operation	
• Design as touch screen	Yes; analog, resistive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	26 W
Dimensions	
Width of the housing front	214 mm
Height of housing front	158 mm
Mounting cutout, width	197 mm
Mounting cutout, height	141 mm
mounting depth	77 mm
Weights	
Weight, approx.	1.5 kg
Classifications	

	Version	Classification
eClass	14	19-20-01-03
eClass	12	19-20-01-03
eClass	9.1	19-20-01-03
eClass	9	19-20-01-03
eClass	8	27-24-23-01
eClass	7.1	27-24-23-01
eClass	6	27-24-23-01
ETIM	10	EC001414
ETIM	9	EC001414
ETIM	8	EC001414
ETIM	7	EC001414


Approvals / Certificates	
General Product Approval	EMV

[Miscellaneous](#)



[Confirmation](#)



Maritime application	other	Environment		
	Miscellaneous	Confirmation	Environmental Con- firmations	Environmental Con- firmations

last modified:

11/25/2025 