

SIMATIC IPC277E (Nanopanel PC); 9" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 2x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply Celeron N2807 (2C/2T) 4 GB RAM; WIN Embedded Standard 7E SP1, English; 32 bit 8 GB CFAST; without SIMATIC software

Display	
Design of display	9" TFT touch
Screen diagonal	9 in
Resolution (pixels)	
• Horizontal image resolution	800 pixel
• Vertical image resolution	480 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	80 000 h
Control elements	
Touch operation	
• Design as touch screen	Yes; analog, resistive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Dimensions	
Width of the housing front	274 mm
Height of housing front	190 mm
Mounting cutout, width	251 mm
Mounting cutout, height	166 mm
mounting depth	77 mm
Weights	
Weight, approx.	1.95 kg
Approvals / Certificates	
General Product Approval	



[Manufacturer Declaration](#)

[Miscellaneous](#)



[China RoHS](#)

General Product Approval

Maritime application



Maritime application

Dangerous goods

[NK / Nippon Kaiji Kyokai](#)

[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

[Dangerous goods information](#)

[Test Summary Report UN 38.3](#)

last modified:

2/7/2026