

SIMATIC IPC277E (Nanopanel PC); 9" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 2x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply Celeron N2930 (4C/4T) 4 GB with NVRAM without operating system 240 GB SSD without SIMATIC software

| Display | |
|--------------------------------------|------------------------|
| Design of display | 9" TFT touch |
| Screen diagonal | 9 in |
| Resolution (pixels) | |
| • Horizontal image resolution | 800 pixel |
| • Vertical image resolution | 480 pixel |
| Backlighting | |
| • MTBF backlighting (at 25 °C) | 80 000 h |
| Control elements | |
| Touch operation | |
| • Design as touch screen | Yes; analog, resistive |
| Installation type/mounting | |
| central design | Yes |
| Mounting in portrait format possible | Yes |
| Dimensions | |
| Width of the housing front | 274 mm |
| Height of housing front | 190 mm |
| Mounting cutout, width | 251 mm |
| Mounting cutout, height | 166 mm |
| mounting depth | 77 mm |
| Weights | |
| Weight, approx. | 1.95 kg |
| Approvals / Certificates | |
| General Product Approval | |



[Manufacturer Declaration](#)

[Miscellaneous](#)



[China RoHS](#)

General Product Approval

Maritime application



Maritime application

Dangerous goods

[NK / Nippon Kaiji Kyokai](#)

[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

[Dangerous goods information](#)

[Test Summary Report UN 38.3](#)

last modified:

12/24/2025