



spare part SIPLUS HCS4000 I/O module DI/DQ with 8 digital outputs and 8 configurable digital inputs or outputs

General information	
Product type designation	PM4000 DI/DO
Installation type/mounting	
Mounting type	Screw mounting to CIM
Mounting position	vertical
Type of ventilation	Forced ventilation
Supply voltage	
Design of the power supply	Power supply via CIM
Power	
Active power input, max.	1 W
Digital inputs	
Number of digital inputs	8
Connection method	
<ul style="list-style-type: none"> • Design of electrical connection at the digital inputs <ul style="list-style-type: none"> — Connectable conductor cross-sections, solid — Connectable conductor cross-sections, finely stranded with wire end processing — Connectable conductor cross-sections for AWG cables 	plug, 18-pin with spring-type terminal, push-in 1x (0.2 ... 1.5 mm ²) 1x (0.25 ... 1.5 mm ²) 1x (24 ... 16)
Digital outputs	
Type of digital output	semiconductor output (high side switch)
Number of digital outputs	16
Switching performance	monostable
short-circuit proof	Yes
Output voltage	
<ul style="list-style-type: none"> • Type of output voltage • Rated value (DC) • permissible voltage at output, min. • permissible voltage at output, max. 	DC 24 V 19.2 V 28.8 V
Output current	
<ul style="list-style-type: none"> • for signal "1" permissible range, max. 	500 mA
Connection method	
<ul style="list-style-type: none"> • Design of electrical connection at the digital outputs <ul style="list-style-type: none"> — Connectable conductor cross-sections, solid — Connectable conductor cross-sections, finely stranded with wire end processing — Connectable conductor cross-sections for AWG cables • Design of electrical connection for control supply voltage <ul style="list-style-type: none"> — Connectable conductor cross-sections with wire end 	plug, 18-pin with spring-type terminal, push-in 1x (0.2 ... 1.5 mm ²) 1x (0.25 ... 1.5 mm ²) 1x (24 ... 16) plug, 18-pin with spring-type terminal, push-in 1x (0.25 ... 1.5 mm ²)

processing
 — Connectable conductor cross-sections for AWG cables

1x (24 ... 16)

Interfaces

Interfaces/bus type system interface

Interrupts/diagnostics/status information

Number of status displays 18
 LED status display LED green = Ready, LED red = Error display, 1 LED yellow per output: LED on - H status; LED off -L status

Potential separation

between outputs and system interface Yes

Isolation

Overvoltage category III
 Degree of pollution 2

EMC

EMC interference emission Limit value in accordance with IEC 61000-6-4:2007 + A1:2011
 Electrostatic discharge acc. to IEC 61000-4-2 4 kV contact discharge / 8 kV air discharge
 Field-related interference acc. to IEC 61000-4-3 10 V/m (80 ... 1 000 MHz), 3 V/m (1.4 ... 2.0 GHz), 1 V/m (2.0 ... 2.7 GHz)
 Conducted interference due to burst acc. to IEC 61000-4-4 2 kV signal lines
 Conducted interference due to surge acc. to IEC 61000-4-5 DC supply cables: 0.5 kV balanced and unbalanced
 Conducted interference due to high-frequency radiation acc. to IEC 61000-4-6 10 V (0.15 ... 80 MHz)

Degree and class of protection

IP degree of protection IP20

Standards, approvals, certificates

CE mark Yes
 UL approval Yes
 RCM (formerly C-TICK) Yes
 KC approval Yes
 EAC (formerly Gost-R) Yes
 China RoHS compliance Yes
 reference designation according to IEC 81346-2 (2009) K

Ambient conditions

Ambient temperature during operation
 • min. 0 °C
 • max. 55 °C

Ambient temperature during storage/transportation
 • Storage, min. -25 °C
 • Storage, max. 70 °C
 • Transportation, min. -25 °C
 • Transportation, max. 70 °C

Air pressure acc. to IEC 60068-2-13
 • Operation, min. 860 hPa
 • Operation, max. 1 080 hPa
 • Storage, min. 660 hPa
 • Storage, max. 1 080 hPa

Altitude during operation relating to sea level
 • Installation altitude above sea level, max. 2 000 m

Relative humidity
 • Operation at 25 °C, max. 95 %
 • Operation at 50 °C, max. 50 %; 95 % at 25 °C, decreasing linearly to 50 % at 50 °C

Vibrations
 • Vibration resistance during operation acc. to IEC 60068-2-6 10 ... 58 Hz / 0.075 mm, 58 ... 150 Hz / 1 g
 • Vibration resistance during storage acc. to IEC 60068-2-6 5 ... 8.5 Hz / 3.5 mm, 8.5 ... 500 Hz / 1 g

Shock testing
 • Shock resistance during operation acc. to IEC 60068-2-27 15 g / 11 ms / 3 shocks/axis
 • Shock resistance during storage acc. to IEC 60068-2-29 25 g / 6 ms / 1 000 shocks/axis

Dimensions

Width	27 mm
Height	141 mm
Depth	110 mm

Classifications

	Version	Classification
eClass	14	27-24-40-04
eClass	12	27-24-40-04
eClass	9.1	27-24-40-04
eClass	9	27-24-40-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC002984
ETIM	9	EC002984
ETIM	8	EC002984
ETIM	7	EC002984
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----



last modified:

7/1/2025