



\*\*\*spare part\*\*\* SIPLUS HCS4300 POM4320 rear panel mounting (UL) with 9 outputs each max. 6000 W (at 400 V AC)

General information	
Product type designation	POM4320 rear panel mounting (UL)
Installation type/mounting	
Mounting type	Backplane mounting
Mounting position	vertical
Type of ventilation	Self-ventilation
Supply voltage	
Type of supply voltage	AC
Rated value (AC)	400 V; Phase - phase
<ul style="list-style-type: none"> <li>Relative negative tolerance</li> <li>Relative positive tolerance</li> </ul>	10 % 30 %
2nd rated value (AC)	480 V; Phase - phase
<ul style="list-style-type: none"> <li>Relative negative tolerance</li> <li>Relative positive tolerance</li> </ul>	25 % 8 %
Line frequency	
<ul style="list-style-type: none"> <li>Rated value 50 Hz</li> <li>Rated value 60 Hz</li> <li>Relative symmetrical tolerance</li> </ul>	Yes Yes 5 %
Mains buffering	
<ul style="list-style-type: none"> <li>Recovery time after power failure, typ.</li> </ul>	1 s
Connection method	
<ul style="list-style-type: none"> <li>Design of electrical connection for supply voltage</li> </ul>	Busbar mounting, 3-pole + PE
Input voltage	
device version of the power supply for electronics	Power supply via CIM
Power	
Active power input, max.	8 W
Power electronics	
Type of load	Ohmic load
Power capacity, max.	64.8 kW; At 480 V AC
<ul style="list-style-type: none"> <li>For phase against phase with fan at 40 °C, max.</li> </ul>	64.8 kW; At 480 V AC
Switching capacity current per phase, max.	80 A
Short-time withstand current (SCCR) acc. to UL 508A	100 kA
Control of heating elements	
<ul style="list-style-type: none"> <li>Half-wave control</li> <li>Soft start</li> <li>Phase control</li> </ul>	Yes Yes Yes
Load connection type	
<ul style="list-style-type: none"> <li>Star connection with neutral conductor (single-phase)</li> <li>Open delta connection (single-phase)</li> </ul>	No Yes; Incoming fuse contained in the device

• closed delta connection (2-phase)	No
• Closed delta connection (3-phase)	No
• Star connection with neutral conductor (2-phase)	No
• star connection without neutral conductor (3-phase)	No
• 2-pole switching	No
<b>Setpoint input</b>	
• Percent	Yes
• Watts	No
<b>Heating power</b>	
• Number of digital outputs	9
• Number of heating elements per output, max.	1
• Output voltage for heating power	400 V
• 2nd output voltage for heating power	480 V
• Power carrying capacity per output, min.	240 W; At 480 V AC
• Power carrying capacity per output, max.	7 200 W; At 480 V AC
— for heating elements with high inrush current, max.	4 000 W; At 480 V AC
• Output current for heating power	15 A; max.
• Melting I2t value	400 A <sup>2</sup> ·s
• Design of short-circuit protection per output	Melting fuse 20 A
• Design of overvoltage protection	Transil Diode
<b>Connection method</b>	
• Design of electrical connection at output for heating and fan	plug, 3-pole with spring-type terminal, push-in
— Connectable conductor cross-sections, solid	1x (0.2 ... 10 mm <sup>2</sup> )
— Connectable conductor cross-sections, finely stranded with wire end processing	1x (0.25 ... 6 mm <sup>2</sup> )
— Connectable conductor cross-sections for AWG cables, stranded	1x (24 ... 8)
<b>Interfaces</b>	
Interfaces/bus type	system interface
<b>Interrupts/diagnostics/status information</b>	
Number of status displays	12
LED status display	LED green = ready, LED yellow = heating on/off, LED red = error display, LED red = error for each channel
Diagnostics function	Voltage diagnostics
<b>Diagnoses</b>	
• Fuse blown	Yes
• Load failure	Yes
• Triac error	Yes
• Switch-off threshold for internal device temperature	Yes
• Parallel-connected heating elements	No
• Rotating field fault	Yes
• Communication error	Yes
• Supply voltage not connected	Yes
• Line voltage outside the permissible range	Yes
• Frequency outside the permissible range	Yes
• Fault current too high	No
<b>Integrated Functions</b>	
<b>Monitoring functions</b>	
• Temperature monitoring	Yes
• Type of temperature monitoring	NTC thermistor
<b>Measuring functions</b>	
• Voltage measurement	Yes
• Current measurement	No
• Fault current detection	No
<b>Potential separation</b>	
Design of electrical isolation between the outputs	Optocoupler and/or protective impedance between main circuit and PELV
	No
<b>Isolation</b>	
Overvoltage category	III

Degree of pollution	2	
<b>EMC</b>		
EMC interference emission	Limit value in accordance with IEC 61000-6-4:2007 + A1:2011	
Electrostatic discharge acc. to IEC 61000-4-2	4 kV contact discharge / 8 kV air discharge	
Field-related interference acc. to IEC 61000-4-3	10 V/m (80 ... 1 000 MHz), 3 V/m (1.4 ... 2.0 GHz), 1 V/m (2.0 ... 2.7 GHz)	
Conducted interference due to burst acc. to IEC 61000-4-4	2 kV power supply lines, 2 kV load lines	
Conducted interference due to surge acc. to IEC 61000-4-5	on supply and load lines: 1 kV symmetric, 2 kV unsymmetric	
Conducted interference due to high-frequency radiation acc. to IEC 61000-4-6	10 V (0.15 ... 80 MHz)	
<b>Degree and class of protection</b>		
IP degree of protection	IP20	
<b>Standards, approvals, certificates</b>		
CE mark	Yes	
UL approval	Yes	
RCM (formerly C-TICK)	Yes	
KC approval	Yes	
EAC (formerly Gost-R)	Yes	
China RoHS compliance	Yes	
reference designation according to IEC 81346-2 (2009)	Q	
<b>Ambient conditions</b>		
Ambient temperature during operation		
• min.	0 °C	
• max.	55 °C	
Ambient temperature during storage/transportation		
• Storage, min.	-25 °C	
• Storage, max.	70 °C	
• Transportation, min.	-25 °C	
• Transportation, max.	70 °C	
Air pressure acc. to IEC 60068-2-13		
• Operation, min.	860 hPa	
• Operation, max.	1 080 hPa	
• Storage, min.	660 hPa	
• Storage, max.	1 080 hPa	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	2 000 m	
Relative humidity		
• Operation at 25 °C, max.	95 %	
• Operation at 50 °C, max.	50 %; 95 % at 25 °C, decreasing linearly to 50 % at 50 °C	
Vibrations		
• Vibration resistance during operation acc. to IEC 60068-2-6	10 ... 58 Hz / 0.075 mm, 58 ... 150 Hz / 1 g	
• Vibration resistance during storage acc. to IEC 60068-2-6	5 ... 8.5 Hz / 3.5 mm, 8.5 ... 500 Hz / 1 g	
Shock testing		
• Shock resistance during operation acc. to IEC 60068-2-27	15 g / 11 ms / 3 shocks/axis	
• Shock resistance during storage acc. to IEC 60068-2-29	25 g / 6 ms / 1 000 shocks/axis	
<b>Dimensions</b>		
Width	104 mm	
Height	344 mm	
Depth	217 mm	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-40-01
eClass	12	27-24-40-01
eClass	9.1	27-24-40-01
eClass	9	27-24-40-01
eClass	8	27-24-26-90
eClass	7.1	27-24-26-90

eClass	6	27-24-26-90
ETIM	10	EC002982
ETIM	9	EC002982
ETIM	8	EC002982
ETIM	7	EC002982
IDEA	4	3567
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

EMV



last modified:

3/13/2026