



LOGO! DM8 24R expansion module, PS/I/O: 24V/24V/relay, 2 MW 4 DI/4 DO, AC/DC/NPN input for LOGO! 8

Installation type/mounting	
Mounting	on 35 mm DIN rail, 2 spacing units wide
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Rated value (AC)	
• 24 V AC	Yes
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Digital inputs	
Number of digital inputs	4
Input voltage	
• Type of input voltage	AC/DC
• for signal "0"	< 5 V AC/DC
• for signal "1"	> 12 V AC/DC
Input current	
• for signal "0", max. (permissible quiescent current)	1.1 mA
• for signal "1", typ.	2.63 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	1.5 ms
— at "1" to "0", max.	15 ms
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	1 000 W
Output current	
• for signal "1" rated value	5 A
• for signal "1" minimum load current	100 mA
Parallel switching of two outputs	
• for uprating	No
Switching frequency	
• with resistive load, max.	2 Hz
• with inductive load, max.	0.5 Hz

• mechanical, max.	10 Hz	
<b>Relay outputs</b>		
Switching capacity of contacts		
— with inductive load, max.	3 A	
— with resistive load, max.	5 A	
<b>EMC</b>		
Emission of radio interference acc. to EN 55 011		
• Limit class B, for use in residential areas	Yes	
<b>Degree and class of protection</b>		
IP degree of protection	IP20	
<b>Standards, approvals, certificates</b>		
CE mark	Yes	
CSA approval	Yes	
UL approval	Yes	
FM approval	Yes	
developed in accordance with IEC 61131	Yes	
according to VDE 0631	Yes	
Marine approval	Yes	
<b>Ecological footprint</b>		
• environmental product declaration	Yes	
Global warming potential		
— global warming potential, (total) [CO2 eq]	59.1 kg	
— global warming potential, (during production) [CO2 eq]	5.82 kg	
— global warming potential, (during operation) [CO2 eq]	53.6 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.373 kg	
<b>Ambient conditions</b>		
Ambient temperature during operation		
• min.	-20 °C; No condensation	
• max.	55 °C	
<b>Dimensions</b>		
Width	35.5 mm	
Height	90 mm	
Depth	58 mm	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05
<b>Approvals / Certificates</b>		
<b>General Product Approval</b>	<b>Maritime application</b>	



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

Environment

[KR \(Korean Register of Shipping\)](#)



last modified:

7/2/2025