

Siemens
EcoTech



SIMATIC ET 200SP, relay module, RQ CO ni 3x120VDC..230VAC/5A ST, 3 CO contacts non-isolated contacts, packing unit: 1 unit, suitable for BU type U0, color code CC20, substitute value output, module diagnostics for supply voltage

General information	
Product type designation	RQ 3x120VDC-230VAC/5A CO n.i. ST
Firmware version	V0.0
<ul style="list-style-type: none"> FW update possible 	No
usable BaseUnits	BU type U0
Color code for module-specific color-coded label	CC20
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Isochronous mode 	No
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	TIA V19 or higher with HSP0463 / integrated as of TIA V20
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	One GSD file each, Revision 3 and 5 and higher
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	GSDML V2.45
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	40 mA; without load
Current consumption, max.	55 mA
Output voltage	
Rated value (AC)	230 V
Power loss	
Power loss, typ.	1.4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Inputs 	+ 1 byte for QI information
<ul style="list-style-type: none"> Outputs 	1 byte
Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> Mechanical coding element 	Yes
<ul style="list-style-type: none"> Type of mechanical coding element 	type C
Selection of BaseUnit for connection variants	
<ul style="list-style-type: none"> 2-wire connection 	BU type U0
<ul style="list-style-type: none"> 3-wire connection 	BU type U0

Digital outputs	
Type of digital output	Relays
Number of digital outputs	3
Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	No
Switching capacity of the outputs	
<ul style="list-style-type: none"> with resistive load, max. 	5 A; for an additional description, see the Technical Data in the Equipment Manual
<ul style="list-style-type: none"> with inductive load, max. 	2 A; for an additional description, see the Technical Data in the Equipment Manual
Parallel switching of two outputs	
<ul style="list-style-type: none"> for logic links 	Yes
<ul style="list-style-type: none"> for uprating 	No
<ul style="list-style-type: none"> for redundant control of a load 	Yes
Switching frequency	
<ul style="list-style-type: none"> with resistive load, max. 	2 Hz
<ul style="list-style-type: none"> with inductive load, max. 	0.5 Hz
<ul style="list-style-type: none"> on lamp load, max. 	2 Hz
Total current of the outputs	
<ul style="list-style-type: none"> Current per channel, max. 	5 A
<ul style="list-style-type: none"> Current per module, max. 	5 A
Total current of the outputs (per module)	
horizontal installation	
— up to 50 °C, max.	5 A
— up to 60 °C, max.	5 A
vertical installation	
— up to 40 °C, max.	5 A
— up to 50 °C, max.	5 A
Relay outputs	
<ul style="list-style-type: none"> Number of relay outputs 	3; Changeover contact, non-floating
<ul style="list-style-type: none"> Rated supply voltage of relay coil L+ (DC) 	24 V
<ul style="list-style-type: none"> Current consumption of relays (coil current of all relays), max. 	40 mA
<ul style="list-style-type: none"> external protection for relay outputs 	yes, with miniature fuse max. 6.3 A tripping current, quick-response tripping characteristic and 1 500 A breaking capacity
<ul style="list-style-type: none"> Number of operating cycles, max. 	1 000 000; see additional description in the manual
Switching capacity of contacts	
— with inductive load, max.	2 A; see additional description in the manual
— with resistive load, max.	5 A; see additional description in the manual
— Thermal continuous current, max.	5 A; Max. 1 385 VA, 150 W
— Switching current, min.	10 mA; 5 V DC
— Rated switching voltage (DC)	24 V DC to 120 V DC
— Rated switching voltage (AC)	24V AC to 230V AC
Cable length	
<ul style="list-style-type: none"> shielded, max. 	1 000 m
<ul style="list-style-type: none"> unshielded, max. 	200 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
<ul style="list-style-type: none"> Diagnostic alarm 	Yes
Diagnoses	
<ul style="list-style-type: none"> Monitoring the supply voltage 	Yes
<ul style="list-style-type: none"> Wire break 	No
<ul style="list-style-type: none"> Short-circuit 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> Channel status display 	Yes; green LED

<ul style="list-style-type: none"> • for channel diagnostics • for module diagnostics 	No Yes; green/red DIAG LED	
Potential separation		
Potential separation channels		
<ul style="list-style-type: none"> • between the channels • between the channels and backplane bus • between the channels and the power supply of the electronics 	No Yes Yes	
Isolation		
Isolation tested with	2 000 V DC (routine test)	
tested with		
<ul style="list-style-type: none"> • between channels and backplane bus/supply voltage • between backplane bus and supply voltage 	2 000 V DC (routine test) 707 V DC (type test)	
Standards, approvals, certificates		
Suitable for safety functions	No	
Ecological footprint		
<ul style="list-style-type: none"> • environmental product declaration 	Yes	
Global warming potential		
— global warming potential, (total) [CO2 eq]	25.5 kg	
— global warming potential, (during production) [CO2 eq]	3.54 kg	
— global warming potential, (during operation) [CO2 eq]	22.1 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.137 kg	
Ambient conditions		
Ambient temperature during operation		
<ul style="list-style-type: none"> • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. 	-30 °C 60 °C -30 °C 50 °C	
Altitude during operation relating to sea level		
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	2 000 m	
Absolute humidity		
<ul style="list-style-type: none"> • dew point, min. 	-60 °C; suitable for dry room applications	
Dimensions		
Width	20 mm	
Height	73 mm	
Depth	58 mm	
Weights		
Weight, approx.	40 g	
Classifications		
	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05
Approvals / Certificates		

General Product Approval



[Manufacturer Declaration](#)

[Miscellaneous](#)



General Product Approval

For use in hazardous locations



[China RoHS](#)



For use in hazardous locations

Maritime application

[EM](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application

Environment



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)



last modified:

2/1/2026