

Siemens  
EcoTech



SIMATIC DP, electronic module ET 200SP, F-AI 4xI0(4)..20 mA HF fail-safe analog inputs up to PL e (ISO 13849) up to SIL 3 (IEC 61508)

General information	
Product type designation	F-AI 4xI 0(4)..20mA 2-/4-wire HF
Firmware version	
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color-coded label	CC00
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V15 with HSP 203
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Calibration possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	No
Input current	
Current consumption (rated value)	0.38 A
Current consumption, max.	0.4 A
Encoder supply	
24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> </ul>	Yes; min. L+ (-1.5 V)
<ul style="list-style-type: none"> <li>Short-circuit protection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Output current, max.</li> </ul>	300 mA; total current of all encoders/channels
Power	
Power consumption from the backplane bus	70 mW
Power loss	
Power loss, typ.	2 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Inputs</li> </ul>	14 byte; S7-300/400F CPU, 13 byte
<ul style="list-style-type: none"> <li>Outputs</li> </ul>	5 byte; S7-300/400F CPU, 4 byte

Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> <li>• Electronic coding element type F</li> </ul>	Yes
Analog inputs	
Number of analog inputs	4
<ul style="list-style-type: none"> <li>• For current measurement</li> </ul>	4
permissible input current for current input (destruction limit), max.	35 mA
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>• 0 to 20 mA</li> <li>— Input resistance (0 to 20 mA)</li> </ul>	Yes 125 Ω
<ul style="list-style-type: none"> <li>• 4 mA to 20 mA</li> <li>— Input resistance (4 mA to 20 mA)</li> </ul>	Yes 125 Ω
Cable length	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> <li>• Integration time, parameterizable</li> <li>• Integration time (ms)</li> <li>• Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> </ul>	16 bit Yes 20 / 16,667 50 / 60 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> <li>• Number of smoothing levels</li> <li>• parameterizable</li> <li>• Step: None</li> <li>• Step: low</li> <li>• Step: Medium</li> <li>• Step: High</li> </ul>	7 Yes Yes; 1x conversion cycle time Yes; 2x / 4x conversion cycle time Yes; 8x / 16x conversion cycle time Yes; 32x / 64x conversion cycle time
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> <li>• for current measurement as 2-wire transducer</li> <li>— Burden of 2-wire transmitter, max.</li> <li>• for current measurement as 4-wire transducer</li> </ul>	Yes 650 Ω Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.1 %
Temperature error (relative to input range), (+/-)	0.023 %/K
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.1 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>• Current, relative to input range, (+/-)</li> </ul>	2 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>• Current, relative to input range, (+/-)</li> </ul>	0.1 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency	
<ul style="list-style-type: none"> <li>• Series mode interference (peak value of interference &lt; rated value of input range), min.</li> <li>• Common mode interference, min.</li> </ul>	40 dB 70 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> <li>• Limit value alarm</li> </ul>	Yes No
Diagnoses	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> <li>• Wire break</li> <li>• Short-circuit</li> </ul>	Yes Yes Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>• RUN LED</li> <li>• ERROR LED</li> </ul>	Yes; green LED Yes; red LED

<ul style="list-style-type: none"> <li>• Monitoring of the supply voltage (PWR-LED)</li> <li>• Channel status display</li> <li>• for channel diagnostics</li> <li>• for module diagnostics</li> </ul>	<p>Yes; green PWR LED</p> <p>Yes; green LED</p> <p>Yes; red LED</p> <p>Yes; green/red DIAG LED</p>	
<b>Potential separation</b>		
Potential separation channels		
<ul style="list-style-type: none"> <li>• between the channels</li> <li>• between the channels and backplane bus</li> <li>• between the channels and the power supply of the electronics</li> </ul>	<p>No</p> <p>Yes</p> <p>Yes</p>	
<b>Permissible potential difference</b>		
between the inputs (UCM)	10 Vpp	
<b>Isolation</b>		
Isolation tested with	707 V DC (type test)	
<b>Standards, approvals, certificates</b>		
Ecological footprint		
<ul style="list-style-type: none"> <li>• environmental product declaration</li> </ul>	Yes	
Global warming potential		
— global warming potential, (total) [CO2 eq]	88.3 kg	
— global warming potential, (during production) [CO2 eq]	13.1 kg	
— global warming potential, (during operation) [CO2 eq]	76.6 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-1.37 kg	
Highest safety class achievable in safety mode		
<ul style="list-style-type: none"> <li>• Performance level according to ISO 13849-1</li> <li>• Category according to ISO 13849-1</li> <li>• SIL acc. to IEC 61508</li> </ul>	<p>PLe</p> <p>Cat. 4</p> <p>SIL 3</p>	
Probability of failure (for service life of 20 years and repair time of 100 hours)		
— Low demand mode: PFDavg in accordance with SIL3	< 5.00E-05	
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h	
<b>Ambient conditions</b>		
Ambient temperature during operation		
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	<p>0 °C</p> <p>60 °C</p> <p>0 °C</p> <p>50 °C</p>	
<b>Dimensions</b>		
Width	15 mm	
Height	73 mm	
Depth	58 mm	
<b>Weights</b>		
Weight, approx.	48 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596

ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**



[Miscellaneous](#)



[Miscellaneous](#)



**General Product Approval**      **EMV**      **Test Certificates**



[Confirmation](#)



[Type Test Certificates/Test Report](#)

**Maritime application**      **other**



[Miscellaneous](#)

**other**      **Dangerous goods**      **Environment**

[Confirmation](#)

[Transport Information](#)

[Environmental Confirmations](#)



last modified:

10/23/2025