

Siemens  
EcoTech



SIMATIC ET 200eco PN, CM 8x IO-Link + DI 4x 24 V DC, M12-L, 8x M12, 4x port class A + 4x port class B, channel diagnostics, shared device with 2 controllers, prioritized startup, MRP, S2 redundancy, I&M0...3, multi-fieldbus, PN IO, Ethernet IP, Modbus TCP, degree of protection IP67 / IP69K

General information	
HW functional status	FS05
Firmware version	V5.2.x
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Manufacturer ID according to ODVA (VendorID)	04E3H
Device ID according to ODVA (Product code)	0FA9H
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> <li>Isochronous mode</li> <li>IRT</li> <li>Prioritized startup</li> </ul>	Yes; I&M0 to I&M3, I&M5 No Yes Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> <li>PROFINET from GSD version/GSD revision</li> <li>Multi Fieldbus Configuration Tool (MFCT)</li> </ul>	STEP 7 V17 or higher with HSP 0363 GSDML V2.4.x from V1.3 SP1
Operating mode	
<ul style="list-style-type: none"> <li>IO-Link</li> <li>DI</li> <li>DQ</li> <li>MSI</li> <li>MSO</li> </ul>	Yes Yes No No No
Supply voltage	
power supply according to NEC Class 2 required	No
Load voltage 1L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>permissible range, lower limit (DC)</li> <li>permissible range, upper limit (DC)</li> <li>Reverse polarity protection</li> </ul>	24 V 20.4 V 28.8 V Yes; against destruction
Load voltage 2L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>permissible range, lower limit (DC)</li> <li>permissible range, upper limit (DC)</li> <li>Reverse polarity protection</li> </ul>	24 V 20.4 V 28.8 V Yes; Against destruction; encoder power supply outputs applied with reversed polarity

Input current	
Current consumption (rated value)	70 mA; without load
from load voltage 1L+ (unswitched voltage)	12 A; Maximum value
from load voltage 2L+, max.	12 A; Maximum value
Encoder supply	
Number of outputs	8
24 V encoder supply	
• Short-circuit protection	Yes; per channel, electronic
• Output current, max.	0.5 A; Per channel
Power loss	
Power loss, typ.	5.5 W
Address area	
Address space per module	
• Inputs	264 byte; + 8 bytes for QI information
• Outputs	256 byte
Hardware configuration	
Submodules	
• Number of configurable submodules, max.	9
Digital inputs	
Number of digital inputs	4
Sourcing/sinking input	P-reading
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 60 °C, max.	4
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	typically 3 ms
— at "1" to "0", max.	typically 3 ms
Cable length	
• unshielded, max.	30 m
IO-Link	
Number of ports	8
• of which simultaneously controllable	8
IO-Link protocol 1.0	Yes
IO-Link protocol 1.1	Yes
Transmission rate	4.8 kBaud (COM1); 38.4 kBaud (COM2), 230 kBaud (COM3)
Cycle time, min.	2 ms
Size of process data, input per port	33 byte
Size of process data, input per module	264 byte
Size of process data, output per port	32 byte
Size of process data, output per module	256 byte
Memory size for device parameter	2 kbyte; for each port
Master backup	possible with LIOLink_Master function block
Configuration without S7-PCT	Possible; autostart/manual function
Cable length unshielded, max.	20 m
Operating modes	
• IO-Link	Yes
• DI	Yes
• DQ	Yes; max. 100 mA
Connection of IO-Link devices	
• Port type A	Yes; via 3-core cable

- Port type B Yes; additional device supply: max. 2 A per port, max. 6 A per module
- via three-wire connection Yes

## Interfaces

Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1

### 1. Interface

Interface type	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
Interface types	
• M12 port	Yes; 2x M12, 4-pin, D-coded
• Number of ports	2
• integrated switch	Yes
Protocols	
• PROFINET IO Device	Yes
• Open IE communication	Yes
PROFINET IO Device	
Services	
— IRT	Yes; 250 µs to 4 ms in 125 µs frame
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

### Interface types

M12 port	
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s

### Protocols

Supports protocol for PROFINET IO	Yes
PROFIsafe	No
EtherNet/IP	Yes
Modbus TCP	Yes

Redundancy mode	
• PROFINET system redundancy (S2)	Yes
— on S7-1500R/H	Yes
— on S7-400H	Yes
• PROFINET system redundancy (R1)	No
• H-Sync forwarding	Yes
Media redundancy	
— MRP	Yes
— MRPD	No

EtherNet/IP	
Services	
— CIP Implicit Messaging	Yes
— CIP Explicit Messaging	Yes
— CIP Safety	No
— Shared device	Yes; 2x EtherNet/IP Scanner
— Number of scanners with shared device, max.	2
Updating times	
— Requested Packet Interval (RPI)	2 ms
Redundancy mode	
— DLR (Device Level Ring)	No
Address area	
— Address space per module, max.	300 byte
— LargeForwardOpen (Class3)	No
Modbus TCP	
Services	
— read coils (code=1)	Yes
— read discrete inputs (code=2)	Yes
— Read Holding Registers (Code=3)	Yes
— write single coil (code=5)	Yes

— write multiple coils (code=15)	Yes
— Write Multiple Registers (Code=16)	Yes
— Parameter change by master	No
— Modbus TCP Security Protocol	No
<b>Address space per station</b>	
— Address space per station, max.	300 byte
— Access-consistent address space	2 byte
<b>Updating time</b>	
— I/O request interval	2 ms
<b>Connections</b>	
— number of connections per device	12
<b>Open IE communication</b>	
• TCP/IP	Yes; (only EtherNet/IP or Modbus TCP)
• SNMP	Yes
• LLDP	Yes
• ARP	Yes
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
• Maintenance interrupt	Yes; Parameterizable
<b>Diagnoses</b>	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes
— parameterizable	Yes
• Wire break	Yes
• Short-circuit encoder supply	Yes; Per channel
<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• NS LED	Yes; green/red LED
• MS LED	Yes; green/red LED
• IO LED	Yes; red/green/yellow LEDs
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• For load voltage monitoring	Yes; green LED
• Connection display LINK TX/RX	Yes; green LED, only link
<b>Potential separation</b>	
between the load voltages	Yes
between Ethernet and electronics	Yes
<b>Potential separation channels</b>	
• between the channels	No
• between the channels and the power supply of the electronics	No
<b>Isolation</b>	
tested with	
• 24 V DC circuits	707 V DC (type test)
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3
<b>Degree and class of protection</b>	
IP degree of protection	IP65/67/69K
<b>Standards, approvals, certificates</b>	
Suitable for safety-related tripping of standard modules	Yes; from FS01
Highest safety class achievable for safety-related tripping of standard modules	
• Performance level according to ISO 13849-1	PL d
• Category according to ISO 13849-1	Cat. 3
• SIL acc. to IEC 62061	SIL 2
• remark on safety-oriented shutdown	<a href="https://support.industry.siemens.com/cs/de/en/view/39198632">https://support.industry.siemens.com/cs/de/en/view/39198632</a>
Use in hazardous areas	

- Explosion protection category for gas
- Explosion protection category for dust

ATEX, UKEX, IECEx, CCCEX for Zone 2  
 ATEX, UKEX, IECEx, CCCEX for Zone 22

### Security

signed firmware update	Yes
safely removing data	Yes

### Ambient conditions

Ambient temperature during operation	
• min.	-40 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Ambient air temperature-barometric pressure-altitude	Up to max. 5 000 m, at installation height > 2 000 m additional restrictions, see manual for details

### Connection method

Design of electrical connection	4/5-pin M12 circular connectors
Design of electrical connection for the inputs and outputs	M12, 5-pin, A-coded
Design of electrical connection for supply voltage	M12, 4-pin, L-coded

### Dimensions

Width	45 mm
Height	200 mm
Depth	48 mm

### Weights

Weight, approx.	780 g
-----------------	-------

### Classifications

	Version	Classification
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

### Approvals / Certificates

#### General Product Approval



[Miscellaneous](#)

[Manufacturer Declaration](#)



#### General Product Approval

#### For use in hazardous locations



[China RoHS](#)

[CCC-Ex](#)



[Miscellaneous](#)

#### For use in hazardous locations

#### Maritime application

[CCC-Ex](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application	other	Food, Pharmaceutical, Medical	Environment
----------------------	-------	-------------------------------	-------------



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)



[Confirmation](#)



Environment	Industrial Communication
-------------	--------------------------



[PROFINET](#)

last modified:

5/15/2026