



SIMATIC ET 200MP. PROFIBUS connection IM 155-5 DP ST for max. 12 S7-1500 modules including PROFIBUS connection plug (6ES7972-0BB70-0XA0); product phase-out planned - see SIOS 109989704

General information	
Product type designation	IM 155-5 DP ST
HW functional status	from FS01
Firmware version	V2.0.0
• FW update possible	Yes
Vendor identification (VendorID)	81AAh
Product function	
• I&M data	Yes; I&M0 to I&M3
• Module swapping during operation (hot swapping)	No
• Isochronous mode	No
• IRT	No
• Tool changer	No
• Local coupling, IO data	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V13
• STEP 7 configurable/integrated from version	use GSD file
• PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
Configuration control	
via dataset	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption (rated value)	0.2 A; at 24 V DC and without load
Current consumption, max.	1.2 A; at 20.4 V DC and max. load
Inrush current, max.	4 A
I^2t	0.09 A ² ·s
from interface 5 V DC, max.	80 mA
Power	
Infeed power to the backplane bus	14 W
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	

• Address space per module, max.	64 byte; For input and output data respectively
Address space per station	
• Address space per station, max.	244 byte; For input and output data respectively
Hardware configuration	
Integrated power supply	Yes; 14 W
System power supply can be plugged in to left of IM	No
Number of permissible power segments	1; incl. interface module
Rack	
• Modules per rack, max.	12; I/O modules
Interfaces	
Number of PROFIBUS interfaces	1; 1 port
1. Interface	
Interface types	
• RS 485	Yes
• Number of ports	1
• integrated switch	No
• BusAdapter (PROFINET)	No
Protocols	
• PROFIBUS DP device	Yes
PROFINET IO Device	
Services	
— IRT	No
Interface types	
RS 485	
• Transmission rate, max.	12 Mbit/s
Protocols	
Supports protocol for PROFINET IO	No
PROFIsafe	Yes
PROFIBUS	Yes
EtherNet/IP	No
Modbus TCP	No
PROFIBUS DP	
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— DPV1	Yes
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Connection display DP	Yes; green LED
Potential separation	
between backplane bus and electronics	No
between PROFIBUS DP and all other circuit components	Yes
between supply and all other circuits	No
Permissible potential difference	
between different circuits	Safety extra low voltage SELV
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	

— global warming potential, (total) [CO2 eq]	64.1 kg
— global warming potential, (during production) [CO2 eq]	11.1 kg
— global warming potential, (during operation) [CO2 eq]	53.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.669 kg

Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	-25 °C; from FS04
• horizontal installation, max.	60 °C
• vertical installation, min.	-25 °C; from FS04
• vertical installation, max.	40 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Absolute humidity	
• dew point, min.	-60 °C; suitable for dry room applications

Connection method

ET-Connection	
• via BU/BA Send	No

Dimensions

Width	35 mm
Height	147 mm
Depth	129 mm

Weights

Weight, approx.	360 g
-----------------	-------

Classifications

	Version	Classification
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



[China RoHS](#)



General Product Approval

EMV

Maritime application



Maritime application

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

last modified:

2/4/2026 