

Power cable M8, PUR cable single-sided assembled with M8 socket, 4-pole, length 10 m



Figure similar

General information		
Product type designation	Power cable	
Product description	Flexible cable (4-core), preassembled at one end with 1x M8 female connector	
Suitability for use	For connection to ET 200AL for 24 V DC power supply	
Degree and class of protection		
IP degree of protection	IP65/67	
Ambient conditions		
Ambient temperature during assembly, min.	-25 °C	
Ambient temperature during assembly, max.	80 °C	
Ambient temperature during storage/transportation		
• min.	-25 °C	
• max.	80 °C	
Cables		
Cable designation	LIF9Y11YFHF 4x 0.50 mm ²	
Cable length	10 m	
Number of electrical cores	4	
Outer diameter of inner conductor	1 mm	
Outer diameter of core insulation	1.46 mm	
Outer diameter of cable sheath	5.1 mm	
Number of bending cycles	2 000 000; cable carrier compliant for 2 million bending cycles with a bending radius of 51 mm, a speed of 5 m/s and an acceleration of 5 m/s ²	
Permissible bending radius, single bend, min.	26 mm	
Permissible bending radius, multiple bends, min.	51 mm	
Bending radius for continuous bending	51 mm	
Color of cable sheath	gray	
Color of core insulation of energy core	white / brown / blue / black	
Weight per length	44 kg/km	
Mechanics/material		
Outgoing feeder type	180° cable outlet	
Material of cable sheath	PE-PUR	
Material of core insulation	PP	
Material property		
• Halogen-free	Yes	
• Silicone-free	Yes	
Classifications		
	Version	Classification
eClass	14	27-24-22-20

eClass	12	27-24-22-20
eClass	9.1	27-24-22-20
eClass	9	27-24-22-20
eClass	8	27-24-92-05
eClass	7.1	27-24-92-05
eClass	6	27-24-92-05
ETIM	10	EC000237
ETIM	9	EC000237
ETIM	8	EC000237
ETIM	7	EC000237
IDEA	4	3553
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[China RoHS](#)

last modified:

8/24/2021