



SIMATIC DP, connection module for PROFIBUS interface module ET 200 Pro; direct connection, integrated address setter and terminating resistor for PROFIBUS DP; product phase-out planned – see SIOS 109989704

**Input current**

from supply voltage 1L+, max.	16 A
from load voltage 2L+ (without load), max.	16 A

**Accessories**

Function description	Terminal module direct: PROFIBUS DP and 24 V power; up to 6 x M20 cable glands
belongs to product	ET 200pro; IM154-1/2 DP

**Dimensions**

Width	90 mm
Height	130 mm
Depth	100 mm

**Weights**

Weight, approx.	292 g
-----------------	-------

**Classifications**

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

**Approvals / Certificates**

**General Product Approval**

[Miscellaneous](#)

[Manufacturer Declaration](#)



**General Product Approval** **Maritime application**



[China RoHS](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

[KR \(Korean Register of Shipping\)](#)

last modified:

4/7/2025