



SIMATIC DP, connection module for PROFIBUS interface module ET 200 Pro; M12/7/8", 2x M12 and 2x 7/8", integrated address setter and terminating resistor for PROFIBUS DP; product phase-out planned – see SIOS 109989704

Input current

from supply voltage 1L+, max.	8 A
from load voltage 2L+ (without load), max.	8 A

Accessories

Function description	Terminal module M12 7/8": PROFIBUS DP and 24 V power; 2x M12 and 2x 7/8"
belongs to product	ET 200pro; IM154-1/2 DP

Dimensions

Width	60 mm
Height	130 mm
Depth	60 mm

Weights

Weight, approx.	440 g
-----------------	-------

Classifications

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[Miscellaneous](#)



General Product Approval	Maritime application
--------------------------	----------------------



[China RoHS](#)



Maritime application

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

last modified:

4/7/2025