



SIMATIC DP, connection module for power module PM-E ET 200 Pro ECOFAST
 CU DP, 1x ECOFAST connection RS-485; product phase-out planned – see SIOS
 109989704

Input current	
from load voltage 2L+ (without load), max.	10 A
Accessories	
Function description	Feeding of load voltage 2L+ within a station; 1x ECOFAST Cu
belongs to product	ET 200pro; PM-E DC24V
Dimensions	
Width	45 mm
Height	130 mm
Depth	60 mm
Weights	
Weight, approx.	125 g

Classifications			
		Version	Classification
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



General Product Approval	EMV	For use in hazardous locations	Maritime application
--------------------------	-----	--------------------------------	----------------------

[China RoHS](#)

[Manufacturer Declaration](#)



[FM](#)



Maritime application

Environment



[NK / Nippon Kaiji Kyokai](#)



[KR \(Korean Register of Shipping\)](#)



last modified:

4/7/2025