



SIMATIC S7-1200, CPU 1214C, compact CPU, AC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 75 KB

| General information | |
|--|---|
| Product type designation | CPU 1214C AC/DC/relay |
| Engineering with | |
| <ul style="list-style-type: none"> Programming package | STEP 7 V11 SP2 or higher |
| Supply voltage | |
| Rated value (AC) | |
| <ul style="list-style-type: none"> 120 V AC 230 V AC | Yes Yes |
| permissible range, lower limit (AC) | 85 V |
| permissible range, upper limit (AC) | 264 V |
| Line frequency | |
| <ul style="list-style-type: none"> permissible range, lower limit permissible range, upper limit | 47 Hz 63 Hz |
| Input current | |
| Current consumption (rated value) | 100 mA at 120 V AC; 50 mA at 240 V AC |
| Inrush current, max. | 20 A; at 264 V |
| Output current | |
| for backplane bus (5 V DC), max. | 1 600 mA; Max. 5 V DC for SM and CM |
| Encoder supply | |
| 24 V encoder supply | |
| <ul style="list-style-type: none"> 24 V | Permissible range: 20.4V to 28.8V |
| Power loss | |
| Power loss, typ. | 14 W |
| Memory | |
| Work memory | |
| <ul style="list-style-type: none"> integrated | 75 kbyte |
| Load memory | |
| <ul style="list-style-type: none"> integrated | 4 Mbyte |
| Backup | |
| <ul style="list-style-type: none"> present without battery | Yes; maintenance-free Yes |
| CPU processing times | |
| for bit operations, typ. | 0.085 µs; / instruction |
| for word operations, typ. | 1.7 µs; / instruction |
| for floating point arithmetic, typ. | 2.5 µs; / instruction |
| CPU-blocks | |
| Number of blocks (total) | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |

| | |
|---|--|
| OB | |
| • Number, max. | Limited only by RAM for code |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 10 kbyte |
| Flag | |
| • Size, max. | 8 kbyte; Size of bit memory address area |
| Address area | |
| I/O address area | |
| • Inputs | 1 024 byte |
| • Outputs | 1 024 byte |
| Process image | |
| • Inputs, adjustable | 1 kbyte |
| • Outputs, adjustable | 1 kbyte |
| Hardware configuration | |
| Number of modules per system, max. | 3 comm. modules, 1 signal board, 8 signal modules |
| • number of expansion boards (SB, CB, BB) | 1 |
| • number of signal modules (SM) | 8 |
| • number of communications modules (CM) | 3 |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • Backup time | 480 h; Typical |
| • Deviation per day, max. | 60 s/month at 25 °C |
| Digital inputs | |
| Number of digital inputs | 14; Integrated |
| • of which inputs usable for technological functions | 6; HSC (High Speed Counting) |
| Sourcing/sinking input | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 14 |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | 5 V DC at 1 mA |
| • for signal "1" | 15 V DC at 2.5 mA |
| Input current | |
| • for signal "1", typ. | 1 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |
| — at "0" to "1", min. | 0.2 ms |
| — at "0" to "1", max. | 12.8 ms |
| for interrupt inputs | |
| — parameterizable | Yes |
| for technological functions | |
| — parameterizable | Yes; Single phase : 3 at 100 kHz & 3 at 30 kHz, differential: 3 at 80 kHz & 3 at 30 kHz |
| Cable length | |
| • shielded, max. | 500 m; 50 m for technological functions |
| • unshielded, max. | 300 m; for technological functions: No |
| Digital outputs | |
| Number of digital outputs | 10; Relays |
| Short-circuit protection | No; to be provided externally |
| Switching capacity of the outputs | |
| • with resistive load, max. | 2 A |
| • on lamp load, max. | 30 W with DC, 200 W with AC |
| Output delay with resistive load | |
| • "0" to "1", max. | 10 ms; max. |
| • "1" to "0", max. | 10 ms; max. |

| | |
|---|--|
| Switching frequency | |
| • of the pulse outputs, with resistive load, max. | 1 Hz |
| Relay outputs | |
| • Number of relay outputs | 10 |
| • Number of operating cycles, max. | mechanically 10 million, at rated load voltage 100 000 |
| Cable length | |
| • shielded, max. | 500 m |
| • unshielded, max. | 150 m |
| Analog inputs | |
| Number of analog inputs | 2 |
| Input ranges | |
| • Voltage | Yes |
| Input ranges (rated values), voltages | |
| • 0 to +10 V | Yes |
| — Input resistance (0 to 10 V) | ≥100k ohms |
| Cable length | |
| • shielded, max. | 100 m; twisted and shielded |
| Analog outputs | |
| Number of analog outputs | 0 |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| • Resolution with overrange (bit including sign), max. | 10 bit |
| • Integration time, parameterizable | Yes |
| • Conversion time (per channel) | 625 μs |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| Interfaces | |
| Number of PROFINET interfaces | 1 |
| 1. Interface | |
| Interface type | PROFINET |
| Isolated | Yes |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| • RJ 45 (Ethernet) | Yes |
| Protocols | |
| • PROFINET IO Controller | Yes |
| Protocols | |
| Supports protocol for PROFINET IO | Yes |
| PROFIsafe | No |
| PROFIBUS | Yes |
| AS-Interface | Yes |
| Protocols (Ethernet) | |
| • TCP/IP | Yes |
| Open IE communication | |
| • TCP/IP | Yes |
| • ISO-on-TCP (RFC1006) | Yes |
| • UDP | Yes |
| Web server | |
| • supported | Yes |
| • User-defined websites | Yes |
| Further protocols | |
| • MODBUS | Yes |
| Communication functions | |
| S7 communication | |
| • supported | Yes |

| | |
|---|--|
| • as server | Yes |
| • as client | Yes |
| Test commissioning functions | |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing | |
| • Forcing | Yes |
| Diagnostic buffer | |
| • present | Yes |
| Integrated Functions | |
| Counter | |
| • Number of counters | 6 |
| • Counting frequency, max. | 100 kHz |
| Frequency measurement | Yes |
| controlled positioning | Yes |
| PID controller | Yes |
| Number of alarm inputs | 4 |
| Potential separation | |
| Potential separation digital inputs | |
| • Potential separation digital inputs | 500 V AC for 1 minute |
| • between the channels, in groups of | 1 |
| Potential separation digital outputs | |
| • Potential separation digital outputs | Relays |
| • between the channels | No |
| • between the channels, in groups of | 2 |
| Permissible potential difference | |
| between different circuits | 500 V DC between 24 V DC and 5 V DC |
| EMC | |
| Interference immunity against discharge of static electricity | |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes |
| — Test voltage at air discharge | 8 kV |
| — Test voltage at contact discharge | 6 kV |
| Interference immunity to cable-borne interference | |
| • Interference immunity on supply lines acc. to IEC 61000-4-4 | Yes |
| • Interference immunity on signal cables acc. to IEC 61000-4-4 | Yes |
| Interference immunity against voltage surge | |
| • Interference immunity on supply lines acc. to IEC 61000-4-5 | Yes |
| Interference immunity against conducted variable disturbance induced by high-frequency fields | |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class A, for use in industrial areas | Yes; Group 1 |
| • Limit class B, for use in residential areas | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |
| Degree and class of protection | |
| IP degree of protection | IP20 |
| Standards, approvals, certificates | |
| CE mark | Yes |
| CSA approval | Yes |
| UL approval | Yes |
| cULus | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| Marine approval | Yes |
| Ambient conditions | |

| | |
|---|---|
| Free fall | |
| • Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
| • min. | -20 °C |
| • max. | 60 °C |
| • horizontal installation, min. | -20 °C |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | -20 °C |
| • vertical installation, max. | 50 °C |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| • Operation, min. | 795 hPa |
| • Operation, max. | 1 080 hPa |
| • Storage/transport, min. | 660 hPa |
| • Storage/transport, max. | 1 080 hPa |
| Altitude during operation relating to sea level | |
| • Installation altitude, min. | -1 000 m |
| • Installation altitude, max. | 2 000 m |
| Relative humidity | |
| • Operation, max. | 95 %; no condensation |
| Vibrations | |
| • Vibration resistance during operation acc. to IEC 60068-2-6 | 2 g (m/s ²) wall mounting, 1 g (m/s ²) DIN rail |
| • Operation, tested according to IEC 60068-2-6 | Yes |
| Shock testing | |
| • tested according to IEC 60068-2-27 | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |
| Pollutant concentrations | |
| • SO ₂ at RH < 60% without condensation | SO ₂ : < 0.5 ppm; H ₂ S: < 0.1 ppm; RH < 60 % condensation-free |
| Configuration | |
| Programming | |
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — SCL | Yes |
| Cycle time monitoring | |
| • adjustable | Yes |
| Dimensions | |
| Width | 110 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weights | |
| Weight, approx. | 455 g |
| Classifications | |

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-22-07 |
| eClass | 12 | 27-24-22-07 |
| eClass | 9.1 | 27-24-22-07 |
| eClass | 9 | 27-24-22-07 |
| eClass | 8 | 27-24-22-07 |
| eClass | 7.1 | 27-24-22-07 |
| eClass | 6 | 27-24-22-07 |
| ETIM | 10 | EC000236 |
| ETIM | 9 | EC000236 |
| ETIM | 8 | EC000236 |

| | | |
|--------|----|-------------|
| ETIM | 7 | EC000236 |
| IDEA | 4 | 3565 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval



[China RoHS](#)



last modified:

5/16/2025