

*** spare part *** SIMATIC S7-200 CN, Digital I/O EM 223, only for S7-22X CPU, 4 DI/4 DO relay, 5-30 V DC, 250 V AC this S7-200 CN product only has CE approval

Power loss	
Power loss, typ.	2 W
Digital inputs	
Number of digital inputs	4
Input voltage	
• Type of input voltage	AC/DC
Input current	
• for signal "1", typ.	4 mA
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No
Output current	
• for signal "1" rated value	2 000 mA
Dimensions	
Width	46 mm
Height	80 mm
Depth	62 mm

Classifications	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates
General Product Approval
Maritime application



[Manufacturer Declaration](#)



[Manufacturer Declaration](#)

[China RoHS](#)



ABS

Maritime application



[CCS \(China Classification Society\)](#)

last modified:

7/17/2025 