



Figure similar

*** spare part *** SIMATIC S7-200 CN, Digital I/O EM 223, only for S7-22X CPU, 16 DI 24 V DC, sink/source, 16 DO relay, 2 A/channel this S7-200 CN product only has CE approval

Power loss	
Power loss, typ.	6 W
Digital inputs	
Number of digital inputs	16
Input voltage	
• Type of input voltage	DC
Input current	
• for signal "1", typ.	4 mA
Digital outputs	
Number of digital outputs	16; Relays
Short-circuit protection	No
Output current	
• for signal "1" rated value	2 000 mA
Dimensions	
Width	137.5 mm
Height	80 mm
Depth	62 mm

Classifications			
		Version	Classification
	eClass	14	27-24-22-04
	eClass	12	27-24-22-04
	eClass	9.1	27-24-22-04
	eClass	9	27-24-22-04
	eClass	8	27-24-22-04
	eClass	7.1	27-24-22-04
	eClass	6	27-24-22-04
	ETIM	10	EC001419
	ETIM	9	EC001419
	ETIM	8	EC001419
	ETIM	7	EC001419
	IDEA	4	3566
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	Maritime application



[Manufacturer Declaration](#)

[China RoHS](#)



Maritime application

[CCS \(China Classification Society\)](#)

last modified:

7/17/2025