



spare part SIMATIC S7-300, CPU 317F-2DP, central processing unit with 1.5 MB work memory, 1st interface MPI/DP 12 Mbps, 2nd interface DP master/slave Micro Memory Card required can be used with software package S7 Distributed Safety V5.2 SP1 or higher

| General information | |
|---|---|
| Product type designation | CPU 317F-2 DP |
| HW functional status | 01 |
| Firmware version | V3.3 |
| Engineering with | |
| <ul style="list-style-type: none"> Programming package | STEP 7 V5.5 + SP1 or higher or STEP 7 V5.2 + SP1 or higher with HSP 202 + Distributed Safety |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| external protection for power supply lines (recommendation) | 2 A min. |
| Input current | |
| Current consumption (rated value) | 870 mA |
| Current consumption (in no-load operation), typ. | 120 mA |
| Inrush current, typ. | 4 A |
| I ² t | 1 A ² ·s |
| Power loss | |
| Power loss, typ. | 4.5 W |
| Memory | |
| Work memory | |
| <ul style="list-style-type: none"> integrated | 1 536 kbyte |
| <ul style="list-style-type: none"> expandable | No |
| Load memory | |
| <ul style="list-style-type: none"> Plug-in (MMC) | Yes |
| <ul style="list-style-type: none"> Plug-in (MMC), max. | 8 Mbyte |
| <ul style="list-style-type: none"> Data management on MMC (after last programming), min. | 10 a |
| Backup | |
| <ul style="list-style-type: none"> present | Yes; Guaranteed by MMC (maintenance-free) |
| <ul style="list-style-type: none"> without battery | Yes; Program and data |
| CPU processing times | |
| for bit operations, typ. | 0.025 μs |
| for word operations, typ. | 0.03 μs |
| for fixed point arithmetic, typ. | 0.04 μs |
| for floating point arithmetic, typ. | 0.16 μs |
| CPU-blocks | |
| Number of blocks (total) | 2 048; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used. |
| DB | |

| | |
|--|--|
| <ul style="list-style-type: none"> • Number, max. • Size, max. | 2 048; Number range: 1 to 16000 64 kbyte |
| FB | |
| <ul style="list-style-type: none"> • Number, max. • Size, max. | 2 048; Number range: 0 to 7999 64 kbyte |
| FC | |
| <ul style="list-style-type: none"> • Number, max. • Size, max. | 2 048; Number range: 0 to 7999 64 kbyte |
| OB | |
| <ul style="list-style-type: none"> • Number, max. • Size, max. • Number of free cycle OBs • Number of time alarm OBs • Number of delay alarm OBs • Number of cyclic interrupt OBs • Number of process alarm OBs • Number of DPV1 alarm OBs • Number of isochronous mode OBs • Number of startup OBs • Number of asynchronous error OBs • Number of synchronous error OBs | see instruction list 64 kbyte 1; OB 1 1; OB 10 2; OB 20, 21 4; OB 32, 33, 34, 35 1; OB 40 3; OB 55, 56, 57 1; OB 61 1; OB 100 5; OB 80, 82, 85, 86, 87 2; OB 121, 122 |
| Nesting depth | |
| <ul style="list-style-type: none"> • per priority class • additional within an error OB | 16 4 |
| Counters, timers and their retentivity | |
| S7 counter | |
| <ul style="list-style-type: none"> • Number | 512 |
| Retentivity | |
| <ul style="list-style-type: none"> — adjustable — preset | Yes Z 0 to Z 7 |
| Counting range | |
| <ul style="list-style-type: none"> — lower limit — upper limit | 0 999 |
| IEC counter | |
| <ul style="list-style-type: none"> • present • Type • Number | Yes SFB Unlimited (limited only by RAM capacity) |
| S7 times | |
| <ul style="list-style-type: none"> • Number | 512 |
| Retentivity | |
| <ul style="list-style-type: none"> — adjustable — preset | Yes No retentivity |
| Time range | |
| <ul style="list-style-type: none"> — lower limit — upper limit | 10 ms 9 990 s |
| IEC timer | |
| <ul style="list-style-type: none"> • present • Type • Number | Yes SFB Unlimited (limited only by RAM capacity) |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 256 kbyte |
| Flag | |
| <ul style="list-style-type: none"> • Size, max. • Retentivity available • Retentivity preset • Number of clock memories | 4 096 byte Yes; From MB 0 to MB 4 095 MB 0 to MB 15 8; 1 memory byte |
| Data blocks | |
| <ul style="list-style-type: none"> • Retentivity adjustable • Retentivity preset | Yes; via non-retain property on DB Yes |

| | |
|---|---|
| Local data | |
| • per priority class, max. | 32 768 byte; Max. 2048 bytes per block |
| Address area | |
| I/O address area | |
| • Inputs | 8 192 byte |
| • Outputs | 8 192 byte |
| of which distributed | |
| — Inputs | 8 192 byte |
| — Outputs | 8 192 byte |
| Process image | |
| • Inputs | 8 192 byte |
| • Outputs | 8 192 byte |
| • Inputs, adjustable | 8 192 byte |
| • Outputs, adjustable | 8 192 byte |
| • Inputs, default | 1 024 byte |
| • Outputs, default | 1 024 byte |
| Subprocess images | |
| • Number of subprocess images, max. | 1 |
| Digital channels | |
| • Inputs | 65 536 |
| — of which central | 1 024 |
| • Outputs | 65 536 |
| — of which central | 1 024 |
| Analog channels | |
| • Inputs | 4 096 |
| — of which central | 256 |
| • Outputs | 4 096 |
| — of which central | 256 |
| Hardware configuration | |
| Number of expansion units, max. | 3 |
| Number of DP masters | |
| • integrated | 2 |
| • via CP | 4 |
| Number of operable FMs and CPs (recommended) | |
| • FM | 8 |
| • CP, PtP | 8 |
| • CP, LAN | 10 |
| Rack | |
| • Racks, max. | 4 |
| • Modules per rack, max. | 8 |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • retentive and synchronizable | Yes |
| • Backup time | 6 wk; At 40 °C ambient temperature |
| • Deviation per day, max. | 10 s; Typ.: 2 s |
| • Behavior of the clock following POWER-ON | Clock continues running after POWER OFF |
| • Behavior of the clock following expiry of backup period | the clock continues at the time of day it had when power was switched off |
| Operating hours counter | |
| • Number | 4 |
| • Number/Number range | 0 to 3 |
| • Range of values | 0 to 2 ³¹ hours (when using SFC 101) |
| • Granularity | 1 h |
| • retentive | Yes; Must be restarted at each restart |
| Clock synchronization | |
| • supported | Yes |
| • to MPI, master | Yes |
| • on MPI, device | Yes |
| • to DP, master | Yes; With DP slave only slave clock |

| | |
|--|---|
| • on DP, device | Yes |
| • in AS, master | Yes |
| • in AS, device | Yes |
| • on Ethernet via NTP | No |
| Digital inputs | |
| Number of digital inputs | 0 |
| Digital outputs | |
| Number of digital outputs | 0 |
| Analog inputs | |
| Number of analog inputs | 0 |
| Interfaces | |
| Number of PROFINET interfaces | 0 |
| Number of RS 485 interfaces | 2 |
| Number of RS 422 interfaces | 0 |
| 1. Interface | |
| Interface type | Integrated RS 485 interface |
| Isolated | Yes |
| Interface types | |
| • RS 485 | Yes |
| • Output current of the interface, max. | 200 mA |
| Protocols | |
| • MPI | Yes |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP device | Yes; A DP slave at both interfaces simultaneously is not possible |
| • Point-to-point connection | No |
| MPI | |
| • Transmission rate, max. | 12 Mbit/s |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | Yes |
| — S7 basic communication | Yes |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No; but via CP and loadable FB |
| — S7 communication, as server | Yes |
| PROFIBUS DP master | |
| • Transmission rate, max. | 12 Mbit/s |
| • max. number of DP devices | 124 |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | Yes; I blocks only |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes |
| — Equidistance | Yes |
| — Isochronous mode | No |
| — SYNC/FREEZE | Yes |
| — activation/deactivation of DP devices | Yes |
| — max. number of DP devices that can be activated/deactivated at the same time | 8 |
| — Direct data exchange (slave-to-slave communication) | Yes; as subscriber |
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 8 kbyte |
| — Outputs, max. | 8 kbyte |
| User data per DP device | |

| | |
|--|---|
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |
| PROFIBUS DP device | |
| • Transmission rate, max. | 12 Mbit/s |
| • automatic baud rate search | Yes; only with passive interface |
| • Address area, max. | 32 |
| • User data per address area, max. | 32 byte |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes; Only with active interface |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No |
| — S7 communication, as server | Yes; Connection configured on one side only |
| — Direct data exchange (slave-to-slave communication) | Yes |
| — DPV1 | No |
| Transfer memory | |
| — Inputs | 244 byte |
| — Outputs | 244 byte |
| 2. Interface | |
| Interface type | Integrated RS 485 interface |
| Isolated | Yes |
| Interface types | |
| • RS 485 | Yes |
| • Output current of the interface, max. | 200 mA |
| Protocols | |
| • MPI | No |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP device | Yes; A DP slave at both interfaces simultaneously is not possible |
| • Point-to-point connection | No |
| PROFIBUS DP master | |
| • Transmission rate, max. | 12 Mbit/s |
| • max. number of DP devices | 124 |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | Yes; I blocks only |
| — S7 communication | Yes; Only server, configured on one side |
| — S7 communication, as client | No; but via CP and loadable FB |
| — S7 communication, as server | Yes |
| — Equidistance | Yes |
| — Isochronous mode | Yes; OB 61 |
| — SYNC/FREEZE | Yes |
| — activation/deactivation of DP devices | Yes |
| — max. number of DP devices that can be activated/deactivated at the same time | 8 |
| — Direct data exchange (slave-to-slave communication) | Yes; as subscriber |
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 8 192 byte |
| — Outputs, max. | 8 192 byte |
| User data per DP device | |
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |
| PROFIBUS DP device | |
| • GSD file | The latest GSD file is available on the Internet |

(<http://www.siemens.com/profibus-gsd>)

- Transmission rate, max. 12 Mbit/s
- automatic baud rate search Yes; only with passive interface
- Address area, max. 32
- User data per address area, max. 32 byte

Services

- PG/OP communication Yes
- Routing Yes; Only with active interface
- Global data communication No
- S7 basic communication No
- S7 communication Yes; Only server, configured on one side
- S7 communication, as client No; but via CP and loadable FB
- S7 communication, as server Yes
- Direct data exchange (slave-to-slave communication) Yes
- DPV1 No

Transfer memory

- Inputs 244 byte
- Outputs 244 byte

Protocols

- PROFIsafe No

Communication functions

- PG/OP communication Yes
- Data record routing Yes

Global data communication

- supported Yes
- Number of GD loops, max. 8
- Number of GD packets, max. 8
- Number of GD packets, transmitter, max. 8
- Number of GD packets, receiver, max. 8
- Size of GD packets, max. 22 byte
- Size of GD packet (of which consistent), max. 22 byte

S7 basic communication

- supported Yes
- User data per job, max. 76 byte
- User data per job (of which consistent), max. 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)

S7 communication

- supported Yes
- as server Yes
- as client Yes; Via CP and loadable FB
- User data per job, max. See online help of STEP 7 (shared parameters of the SFBs/FBs and of the SFCs/FCs of S7 Communication)

S5 compatible communication

- supported Yes; via CP and loadable FC

Number of connections

- overall 32
- usable for PG communication 31
 - reserved for PG communication 1
 - adjustable for PG communication, min. 1
 - adjustable for PG communication, max. 31
- usable for OP communication 31
 - reserved for OP communication 1
 - adjustable for OP communication, min. 1
 - adjustable for OP communication, max. 31
- usable for S7 basic communication 30
 - reserved for S7 basic communication 0
 - adjustable for S7 basic communication, min. 0
 - adjustable for S7 basic communication, max. 30
- usable for routing X1 as a MPI, max. 10; X1 as DP Master max. 24; X1 as DP Slave (active) max.

14; X2 as DP Master max. 24; X2 as DP Slave (active) max. 14

S7 message functions

| | |
|--|--|
| Number of login stations for message functions, max. | 32; Depending on the configured connections for PG/OP and S7 basic communication |
| Process diagnostic messages | Yes |
| simultaneously active Alarm_S blocks, max. | 300 |

Test commissioning functions

| | |
|-----------------------|-----------------------------|
| Status block | Yes; Up to 2 simultaneously |
| Single step | Yes |
| Number of breakpoints | 4 |

| | |
|--|---|
| Status/control | |
| <ul style="list-style-type: none"> • Status/control variable | Yes |
| <ul style="list-style-type: none"> • Variables | Inputs, outputs, memory bits, DB, times, counters |
| <ul style="list-style-type: none"> • Number of variables, max. | 30 |
| <ul style="list-style-type: none"> — of which status variables, max. | 30 |
| <ul style="list-style-type: none"> — of which control variables, max. | 14 |

| | |
|---|-----------------|
| Forcing | |
| <ul style="list-style-type: none"> • Forcing | Yes |
| <ul style="list-style-type: none"> • Forcing, variables | Inputs, outputs |
| <ul style="list-style-type: none"> • Number of variables, max. | 10 |

| | |
|---|---|
| Diagnostic buffer | |
| <ul style="list-style-type: none"> • present | Yes |
| <ul style="list-style-type: none"> • Number of entries, max. | 500 |
| <ul style="list-style-type: none"> — adjustable | No |
| <ul style="list-style-type: none"> — of which powerfail-proof | 100; Only the last 100 entries are retained |
| <ul style="list-style-type: none"> • Number of entries readable in RUN, max. | 499 |
| <ul style="list-style-type: none"> — adjustable | Yes; From 10 to 499 |
| <ul style="list-style-type: none"> — preset | 10 |

| | |
|---|-----|
| Service data | |
| <ul style="list-style-type: none"> • can be read out | Yes |

Ambient conditions

| | |
|--|-------|
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • min. | 0 °C |
| <ul style="list-style-type: none"> • max. | 60 °C |

Configuration

| | |
|---|--|
| Configuration software | |
| <ul style="list-style-type: none"> • STEP 7 | Yes; STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203 |
| <ul style="list-style-type: none"> • STEP 7 Lite | No |

| | |
|--|----------------------|
| Programming | |
| <ul style="list-style-type: none"> • Command set | see instruction list |
| <ul style="list-style-type: none"> • Nesting levels | 8 |
| <ul style="list-style-type: none"> • System functions (SFC) | see instruction list |
| <ul style="list-style-type: none"> • System function blocks (SFB) | see instruction list |

| | |
|--|-----|
| Programming language | |
| <ul style="list-style-type: none"> — LAD | Yes |
| <ul style="list-style-type: none"> — FBD | Yes |
| <ul style="list-style-type: none"> — STL | Yes |
| <ul style="list-style-type: none"> — SCL | Yes |
| <ul style="list-style-type: none"> — CFC | Yes |
| <ul style="list-style-type: none"> — GRAPH | Yes |
| <ul style="list-style-type: none"> — HiGraph® | Yes |

| | |
|---|----------------------------|
| Know-how protection | |
| <ul style="list-style-type: none"> • User program protection/password protection | Yes |
| <ul style="list-style-type: none"> • Block encryption | Yes; With S7 block Privacy |

Dimensions

| | |
|--------|--------|
| Width | 40 mm |
| Height | 125 mm |
| Depth | 130 mm |

Weights

Weight, approx.

360 g

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-22-07 |
| eClass | 12 | 27-24-22-07 |
| eClass | 9.1 | 27-24-22-07 |
| eClass | 9 | 27-24-22-07 |
| eClass | 8 | 27-24-22-07 |
| eClass | 7.1 | 27-24-22-07 |
| eClass | 6 | 27-24-22-07 |
| ETIM | 10 | EC000236 |
| ETIM | 9 | EC000236 |
| ETIM | 8 | EC000236 |
| ETIM | 7 | EC000236 |
| IDEA | 4 | 3565 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[Miscellaneous](#)



General Product Approval

EMV

For use in hazardous locations



[China RoHS](#)

[Manufacturer Declaration](#)



[FM](#)

For use in hazardous locations

Functional Safety



[Miscellaneous](#)

[CCC-Ex](#)

[TUEV](#)

Functional Safety

Maritime application

[Type Examination Certificate](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application

other

Industrial Communication



[CCS \(China Classification Society\)](#)



last modified:

4/7/2025