



Figure similar

spare part SIMATIC S7-300, digital output SM 322, isolated, 8 DO, 120/230 V AC, 1 A, 1x 20-pole

Supply voltage	
Load voltage L1	
• Rated value (AC)	230 V; 120/230 V AC
• permissible range, lower limit (AC)	93 V
• permissible range, upper limit (AC)	264 V
• permissible frequency range, lower limit	47 Hz
• permissible frequency range, upper limit	63 Hz
Input current	
from load voltage L1 (without load), max.	2 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	8.6 W
Digital outputs	
Number of digital outputs	8
Short-circuit protection	Yes; Fuse 8 A, 250 V; per group
• required current for fuse shutdown, min.	40 A
• Response time, max.	300 ms
Controlling a digital input	Yes
Size of motor starters according to NEMA, max.	5 NEMA compliant
Spare fuses	8 A / quick response
Zero-crossing switch	Yes; Max. 60 V
Switching capacity of the outputs	
• on lamp load, max.	50 W
Output voltage	
• for signal "1", min.	L1 (-1.5 V)
• for signal "1" (at max. current), min.	L1 (-1.5 V)
• for signal "1" (at min. current), min.	L1 (-8.5 V)
Output current	
• for signal "1" rated value	2 A
• for signal "1" permissible range for 0 to 40 °C, min.	10 mA
• for signal "1" permissible range for 0 to 40 °C, max.	2 A
• for signal "1" permissible range for 40 to 60 °C, min.	10 mA
• for signal "1" permissible range for 40 to 60 °C, max.	1 A
• for signal "1" minimum load current	10 mA
• for signal "1" permissible surge current, max.	20 A; max. 1 AC cycle
• for signal "0" residual current, max.	2 mA
Output delay with resistive load	
• "0" to "1", max.	1 AC cycle

• "1" to "0", max.	1 AC cycle	
Parallel switching of two outputs		
• for uprating	No	
• for redundant control of a load	Yes	
Switching frequency		
• with resistive load, max.	10 Hz	
• with inductive load, max.	0.5 Hz	
• with inductive load (acc. to IEC 60947-5-1, AC15), max.	0.5 Hz	
• on lamp load, max.	1 Hz	
Total current of the outputs (per group)		
horizontal installation		
— up to 40 °C, max.	4 A	
— up to 60 °C, max.	2 A	
vertical installation		
— up to 40 °C, max.	2 A	
Cable length		
• shielded, max.	1 000 m	
• unshielded, max.	600 m	
Interrupts/diagnostics/status information		
Alarms	No	
Diagnostics function	Yes; Fuse blown or load voltage missing	
Alarms		
• Diagnostic alarm	No	
Diagnoses		
• Wire break	No	
• Short-circuit	No	
• Fuse blown	Yes	
• missing load voltage	Yes	
Diagnostics indication LED		
• Rated load voltage PWR (green)	Yes	
• Fuse OK FSG (green)	Yes	
• Group error SF (red)	Yes	
• Status indicator digital output (green)	Yes	
Potential separation		
Potential separation digital outputs		
• between the channels	Yes	
• between the channels, in groups of	4	
• between the channels and backplane bus	Yes; Optocoupler	
Isolation		
Isolation tested with	1 500 V AC	
Connection method		
required front connector	20-pin	
Dimensions		
Width	40 mm	
Height	125 mm	
Depth	120 mm	
Weights		
Weight, approx.	275 g	
Classifications		
	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04

ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval **EMV** **For use in hazardous locations**

[China RoHS](#)

[Manufacturer Declaration](#)



[EM](#)

Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025