



Figure similar

spare part SIMATIC S7-300, digital output SM 322, isolated, 8 DO (relay), 1x 40-pole, 24 V DC, 5 A or 230 V AC, 5 A, connectors with spring-loaded terminal can be used as of 6ES7392-1BM01-0AA0

Supply voltage	
Load voltage L+	
• Rated value (DC)	120 V
Load voltage L1	
• Rated value (AC)	230 V
Input current	
from supply voltage L+, max.	125 mA
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	3.2 W
Digital outputs	
Number of digital outputs	8; Relays
Short-circuit protection	No; to be provided externally
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	1 500 W; 230 V AC
• Low energy/fluorescent lamps with electronic control gear	10x 58 W
• Fluorescent tubes, conventionally compensated	1x 58 W
• Fluorescent tubes, uncompensated	10x 58 W
Output current	
• for signal "1" rated value	5 A
• for signal "1" minimum load current	5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	2 Hz
• with inductive load, max.	0.5 Hz
• With inductive load (to IEC 60947-5-1, DC13/AC15), max.	0.5 Hz
• on lamp load, max.	2 Hz
• mechanical, max.	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 60 °C, max.	5 A
vertical installation	
— up to 40 °C, max.	5 A
Relay outputs	
• Rated supply voltage of relay coil L+ (DC)	24 V

<ul style="list-style-type: none"> Contact connection (internal) Number of operating cycles, max. 	No 300 000; 300 000 (24 V DC, at 2 A); 200 000 (120 V AC, at 3 A); 100 000 (230 V AC, at 3 A)	
Switching capacity of contacts		
— with inductive load, max.	3 A; 3 A (230 V DC), 2 A (24 V AC)	
— with resistive load, max.	8 A; 8 A (230 V DC), 5 A (24 V AC)	
— Thermal continuous current, max.	8 A	
Cable length		
• shielded, max.	1 000 m	
• unshielded, max.	600 m	
Interrupts/diagnostics/status information		
Alarms	No	
Diagnostics function	No	
Alarms		
• Diagnostic alarm	No	
Diagnoses		
• Wire break	No	
• Short-circuit	No	
• Fuse blown	No	
• missing load voltage	No	
Diagnostics indication LED		
• Rated load voltage PWR (green)	No	
• Fuse OK FSG (green)	No	
• Status indicator digital output (green)	Yes	
Potential separation		
Potential separation digital outputs		
• between the channels	Yes	
• between the channels, in groups of	1	
• between the channels and backplane bus	Yes; Optocoupler	
Isolation		
Isolation tested with	2 000 V AC	
Connection method		
required front connector	40-pin	
Dimensions		
Width	40 mm	
Height	125 mm	
Depth	120 mm	
Weights		
Weight, approx.	320 g	
Classifications		
	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05
Approvals / Certificates		
General Product Approval	Test Certificates	other



[Confirmation](#)

[Miscellaneous](#)

[Confirmation](#)

other

Environment



[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

last modified:

4/7/2025