



Figure similar

spare part SIMATIC S7-300, positioning module FM 351 for rapid/slow traverse drives incl. configuration package on CD

Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> permissible range, lower limit (DC) 	20.4 V
<ul style="list-style-type: none"> permissible range, upper limit (DC) 	28.8 V
Input current	
Current consumption, max.	350 mA
from backplane bus 5 V DC, max.	150 mA
Encoder supply	
5 V encoder supply	
<ul style="list-style-type: none"> 5 V 	Yes
<ul style="list-style-type: none"> Output current, max. 	350 mA
<ul style="list-style-type: none"> Cable length, max. 	32 m
24 V encoder supply	
<ul style="list-style-type: none"> 24 V 	Yes
<ul style="list-style-type: none"> Output current, max. 	400 mA; Per channel
<ul style="list-style-type: none"> Cable length, max. 	100 m
Power loss	
Power loss, typ.	7.9 W
Digital inputs	
Number of digital inputs	8
Functions	Reference cams, reversing cams, flying actual value setting, start/stop positioning
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> for signal "0" 	-3 to +5V
<ul style="list-style-type: none"> for signal "1" 	+11 to +30V
Input current	
<ul style="list-style-type: none"> for signal "0", max. (permissible quiescent current) 	2 mA
<ul style="list-style-type: none"> for signal "1", typ. 	6 mA
Digital outputs	
Number of digital outputs	8
Functions	Rapid traverse, creep, run right, run left
Short-circuit protection	Yes
Output voltage	

<ul style="list-style-type: none"> Rated value (DC) for signal "1", min. 	24 V UP - 0.8 V	
Output current		
<ul style="list-style-type: none"> for signal "1" permissible range for 0 to 60 °C, min. for signal "1" permissible range for 0 to 60 °C, max. for signal "0" residual current, max. 	5 mA; with UPmax 600 mA; with UPmax 0.5 mA	
Encoder		
Connectable encoders		
<ul style="list-style-type: none"> Incremental encoder (symmetrical) Incremental encoder (asymmetrical) Absolute encoder (SSI) 2-wire sensor — permissible quiescent current (2-wire sensor), max. 	Yes Yes Yes Yes 2 mA; on signal "0", max. 2 mA; on signal "1", max. 6 mA	
Encoder signals, incremental encoder (symmetrical)		
<ul style="list-style-type: none"> Trace mark signals Zero mark signal Input voltage Input frequency, max. 	A, notA, B, notB N, notN 5 V difference signal (phys. RS 422) 0.5 MHz	
Encoder signals, incremental encoder (asymmetrical)		
<ul style="list-style-type: none"> Trace mark signals Zero mark signal Input voltage Input frequency, max. 	A, B N 24 V 50 kHz; 50 kHz for 25 m cable length; 25 kHz for 100 m cable length	
Encoder signals, absolute encoder (SSI)		
<ul style="list-style-type: none"> Input signal Data signal Clock signal Telegram length, parameterizable Clock frequency, max. Gray code Cable length, shielded, max. 	5 V difference signal (phys. RS 422) DATA, notDATA CL, notCL 13 or 25 bit 1.5 MHz Yes 200 m; At max. 188 kHz	
Potential separation		
Potential separation digital inputs		
<ul style="list-style-type: none"> Potential separation digital inputs 	Yes	
Potential separation digital outputs		
<ul style="list-style-type: none"> Potential separation digital outputs 	Yes	
Ambient conditions		
Ambient temperature during operation		
<ul style="list-style-type: none"> min. max. 	0 °C 60 °C	
Ambient temperature during storage/transportation		
<ul style="list-style-type: none"> min. max. 	-40 °C 70 °C	
Connection method		
required front connector	1x 20-pin	
Dimensions		
Width	80 mm	
Height	125 mm	
Depth	120 mm	
Weights		
Weight, approx.	550 g	
Classifications		
	Version	Classification
eClass	14	27-24-22-05
eClass	12	27-24-22-05
eClass	9.1	27-24-22-05
eClass	9	27-24-22-05

eClass	8	27-24-22-05
eClass	7.1	27-24-22-05
eClass	6	27-24-22-05
ETIM	10	EC001422
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422
IDEA	4	3567
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval

EMV

For use in hazardous locations



[China RoHS](#)



[FM](#)



For use in hazardous locations

Maritime application



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025