



Figure similar

spare part SIMATIC S7-300, connection IM 361 in expansion rack for connection to central rack (IM360), supply voltage 24 V DC, with C-bus

| Supply voltage | |
|------------------------------------|--------|
| Rated value (DC) | Yes |
| • 24 V DC | |
| Input current | |
| from supply voltage L+, max. | 500 mA |
| Power loss | |
| Power loss, typ. | 5 W |
| Hardware configuration | |
| Number of interfaces per CPU, max. | 3 |
| Dimensions | |
| Width | 80 mm |
| Height | 125 mm |
| Depth | 120 mm |
| Weights | |
| Weight, approx. | 505 g |

| Classifications | | | |
|-----------------|--------|---------|----------------|
| | | Version | Classification |
| | eClass | 14 | 27-24-22-08 |
| | eClass | 12 | 27-24-22-08 |
| | eClass | 9.1 | 27-24-22-08 |
| | eClass | 9 | 27-24-22-08 |
| | eClass | 8 | 27-24-22-08 |
| | eClass | 7.1 | 27-24-22-08 |
| | eClass | 6 | 27-24-22-08 |
| | ETIM | 10 | EC001423 |
| | ETIM | 9 | EC001423 |
| | ETIM | 8 | EC001423 |
| | ETIM | 7 | EC001423 |
| | IDEA | 4 | 3564 |
| | UNSPSC | 15 | 32-15-17-05 |

| Approvals / Certificates | |
|--------------------------|--|
| General Product Approval | |



[Manufacturer Declaration](#)



General Product Approval EMV For use in hazardous locations

[Manufacturer Declaration](#)



[EM](#)



For use in hazardous locations Maritime application



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025