



SIMATIC S7-1500, analog input module AI 16x1 BA, 16-bit resolution accuracy 0.5%, 16 channels in groups of 16, common mode voltage 4 V DC, diagnostics, hardware interrupts; delivery including infeed element, shield bracket and shield terminal: front connector (screw terminals or push-in) to be ordered separately

| General information | |
|---|------------------------|
| Product type designation | AI 16x1 BA |
| HW functional status | from FS01 |
| Firmware version | V1.0.0 |
| • FW update possible | Yes |
| Product function | |
| • I&M data | Yes; I&M0 to I&M3 |
| • Isochronous mode | No |
| • Prioritized startup | No |
| • Measuring range scalable | No |
| • Scalable measured values | No |
| • Adjustment of measuring range | No |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated from version | V16 with HSP 312 / V17 |
| • STEP 7 configurable/integrated from version | V5.5 SP3 / - |
| • PROFIBUS from GSD version/GSD revision | V1.0 / V5.1 |
| • PROFINET from GSD version/GSD revision | V2.3 / - |
| Operating mode | |
| • Oversampling | No |
| • MSI | Yes |
| CiR - Configuration in RUN | |
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN | No |
| Input current | |
| Current consumption, max. | 0 mA |
| Power | |
| Power consumption from the backplane bus | 0.85 W |
| Power loss | |
| Power loss, typ. | 1.2 W |
| Address area | |
| Address space per module | |
| • Inputs | 32 byte |
| • Outputs | 0 byte |
| Analog inputs | |
| Number of analog inputs | 16 |
| • For current measurement | 16 |
| permissible input current for current input (destruction limit), max. | 40 mA |
| Analog input with oversampling | No |

| | |
|---|---|
| Standardization of measured values | No |
| Input ranges (rated values), currents | |
| <ul style="list-style-type: none"> ● 0 to 20 mA <ul style="list-style-type: none"> — Input resistance (0 to 20 mA) ● -20 mA to +20 mA <ul style="list-style-type: none"> — Input resistance (-20 mA to +20 mA) ● 4 mA to 20 mA <ul style="list-style-type: none"> — Input resistance (4 mA to 20 mA) | <p>Yes 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC</p> <p>Yes 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC</p> <p>Yes 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC</p> |
| Cable length | |
| <ul style="list-style-type: none"> ● shielded, max. | 800 m |
| Analog value generation for the inputs | |
| Measurement principle | integrating |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> ● Resolution with overrange (bit including sign), max. ● Integration time, parameterizable ● Integration time (ms) ● Basic conversion time, including integration time (ms) ● Interference voltage suppression for interference frequency f_1 in Hz | <p>16 bit</p> <p>Yes</p> <p>2,5 / 16,67 / 20 / 100 ms</p> <p>10 / 24 / 27 / 107 ms</p> <p>400 / 60 / 50 / 10 Hz</p> |
| Smoothing of measured values | |
| <ul style="list-style-type: none"> ● Number of smoothing levels ● parameterizable ● Step: None ● Step: low ● Step: Medium ● Step: High | <p>4</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> |
| Encoder | |
| Connection of signal encoders | |
| <ul style="list-style-type: none"> ● for voltage measurement ● for current measurement as 2-wire transducer ● for current measurement as 4-wire transducer ● for resistance measurement with two-wire connection ● for resistance measurement with three-wire connection ● for resistance measurement with four-wire connection | <p>No</p> <p>Yes; with external supply</p> <p>Yes</p> <p>No</p> <p>No</p> <p>No</p> |
| Errors/accuracies | |
| Linearity error (relative to input range), (+/-) | 0.1 % |
| Temperature error (relative to input range), (+/-) | 0.006 %/K |
| Crosstalk between the inputs, max. | -50 dB |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-) | 0.1 % |
| Operational error limit in overall temperature range | |
| <ul style="list-style-type: none"> ● Current, relative to input range, (+/-) | 0.5 % |
| Basic error limit (operational limit at 25 °C) | |
| <ul style="list-style-type: none"> ● Current, relative to input range, (+/-) | 0.3 % |
| Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency | |
| <ul style="list-style-type: none"> ● Series mode interference (peak value of interference < rated value of input range), min. ● Common mode voltage, max. ● Common mode interference, min. | <p>40 dB</p> <p>4 V</p> <p>60 dB</p> |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| <ul style="list-style-type: none"> ● Diagnostic alarm ● Limit value alarm | <p>Yes</p> <p>Yes; two upper and two lower limit values in each case</p> |
| Diagnoses | |
| <ul style="list-style-type: none"> ● Monitoring the supply voltage ● Wire break ● Short-circuit ● Group error ● Overflow/Underflow | <p>No</p> <p>Yes; Only for 4 ... 20 mA</p> <p>No</p> <p>No</p> <p>Yes</p> |

| | | | |
|--|--------|--|-----------------------|
| Diagnostics indication LED | | | |
| • RUN LED | | Yes; green LED | |
| • ERROR LED | | Yes; red LED | |
| • MAINT LED | | No | |
| • Monitoring of the supply voltage (PWR-LED) | | No | |
| • Channel status display | | Yes; green LED | |
| • for channel diagnostics | | Yes; red LED | |
| • for module diagnostics | | Yes; red LED | |
| Potential separation | | | |
| Potential separation channels | | | |
| • between the channels | | No | |
| • between the channels, in groups of | | 16 | |
| • between the channels and backplane bus | | Yes | |
| Permissible potential difference | | | |
| between the inputs (UCM) | | 8 V DC | |
| Between the inputs and MANA (UCM) | | 4 V DC | |
| Isolation | | | |
| Isolation tested with | | 707 V DC (type test) | |
| Standards, approvals, certificates | | | |
| Siemens Eco Profile (SEP) | | Siemens EcoTech | |
| Suitable for applications according to AMS 2750 | | No | |
| Suitable for applications according to CQI-9 | | No | |
| Ecological footprint | | | |
| • environmental product declaration | | Yes | |
| Global warming potential | | | |
| — global warming potential, (total) [CO2 eq] | | 38.6 kg | |
| — global warming potential, (during production) [CO2 eq] | | 14.4 kg | |
| — global warming potential, (during operation) [CO2 eq] | | 24.6 kg | |
| — global warming potential, (after end of life cycle) [CO2 eq] | | -0.44 kg | |
| Security | | | |
| signed firmware update | | No | |
| safely removing data | | No | |
| data integrity | | No | |
| Ambient conditions | | | |
| Ambient temperature during operation | | | |
| • horizontal installation, min. | | -30 °C | |
| • horizontal installation, max. | | 60 °C | |
| • vertical installation, min. | | -30 °C | |
| • vertical installation, max. | | 40 °C | |
| Altitude during operation relating to sea level | | | |
| • Installation altitude above sea level, max. | | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual | |
| Absolute humidity | | | |
| • dew point, min. | | -60 °C; suitable for dry room applications | |
| Dimensions | | | |
| Width | | 35 mm | |
| Height | | 147 mm | |
| Depth | | 129 mm | |
| Weights | | | |
| Weight, approx. | | 250 g | |
| Classifications | | | |
| | | Version | Classification |
| | eClass | 14 | 27-24-22-01 |
| | eClass | 12 | 27-24-22-01 |
| | eClass | 9.1 | 27-24-22-01 |
| | eClass | 9 | 27-24-22-01 |

| | | |
|--------|-----|-------------|
| eClass | 8 | 27-24-22-01 |
| eClass | 7.1 | 27-24-22-01 |
| eClass | 6 | 27-24-22-01 |
| ETIM | 10 | EC001420 |
| ETIM | 9 | EC001420 |
| ETIM | 8 | EC001420 |
| ETIM | 7 | EC001420 |
| IDEA | 4 | 3562 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



General Product Approval

EMV

Test Certificates



[Confirmation](#)



[Miscellaneous](#)

Maritime application

other



other

Environment

[Confirmation](#)

[Environmental Confirmations](#)



[Environmental Confirmations](#)

last modified:

5/8/2026