

Siemens
EcoTech



SIMATIC S7-1500 Analog input module, AI 8xU/I/R/RTD BA, 16 bit resolution, Accuracy 0.5%, 8 channels in groups of 8; Common mode voltage 4 V DC, Diagnostics; Hardware interrupts; Delivery including infeed element, shield bracket and shield terminal: Front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	AI 8xU/I/R/RTD BA
HW functional status	FS01
Firmware version	V1.0.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Prioritized startup	No
• Measuring range scalable	No
• Scalable measured values	No
• Adjustment of measuring range	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V15.1 / V16
• STEP 7 configurable/integrated from version	V5.5 SP3 / -
• PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
• PROFINET from GSD version/GSD revision	V2.3 / -
Operating mode	
• Oversampling	No
• MSI	Yes
CIR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	No
Input current	
Current consumption, max.	0 mA
Power	
Power consumption from the backplane bus	0.85 W
Power loss	
Power loss, typ.	0.9 W
Address area	
Address space per module	
• Inputs	16 byte
• Outputs	0 byte
Analog inputs	
Number of analog inputs	8
• For current measurement	8

<ul style="list-style-type: none"> • For voltage measurement 	8
<ul style="list-style-type: none"> • For resistance/resistance thermometer measurement 	8
permissible input voltage for voltage input (destruction limit), max.	12 V; 12 V continuous, 30 V for max. 1 s
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	230 ... 370 μ A
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Analog input with oversampling	No
Standardization of measured values	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • 0 to +5 V 	No
<ul style="list-style-type: none"> • 0 to +10 V 	No
<ul style="list-style-type: none"> • 1 V to 5 V <ul style="list-style-type: none"> — Input resistance (1 V to 5 V) 	Yes 10 M Ω
<ul style="list-style-type: none"> • -1 V to +1 V <ul style="list-style-type: none"> — Input resistance (-1 V to +1 V) 	Yes 10 M Ω
<ul style="list-style-type: none"> • -10 V to +10 V <ul style="list-style-type: none"> — Input resistance (-10 V to +10 V) 	Yes 10 M Ω
<ul style="list-style-type: none"> • -2.5 V to +2.5 V 	No
<ul style="list-style-type: none"> • -25 mV to +25 mV 	No
<ul style="list-style-type: none"> • -250 mV to +250 mV 	No
<ul style="list-style-type: none"> • -5 V to +5 V <ul style="list-style-type: none"> — Input resistance (-5 V to +5 V) 	Yes 10 M Ω
<ul style="list-style-type: none"> • -50 mV to +50 mV <ul style="list-style-type: none"> — Input resistance (-50 mV to +50 mV) 	Yes 10 M Ω
<ul style="list-style-type: none"> • -500 mV to +500 mV <ul style="list-style-type: none"> — Input resistance (-500 mV to +500 mV) 	Yes 10 M Ω
<ul style="list-style-type: none"> • -80 mV to +80 mV 	No
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA <ul style="list-style-type: none"> — Input resistance (0 to 20 mA) 	Yes 25 Ω ; Plus approx. 42 ohms for overvoltage protection by PTC
<ul style="list-style-type: none"> • -20 mA to +20 mA <ul style="list-style-type: none"> — Input resistance (-20 mA to +20 mA) 	Yes 25 Ω ; Plus approx. 42 ohms for overvoltage protection by PTC
<ul style="list-style-type: none"> • 4 mA to 20 mA <ul style="list-style-type: none"> — Input resistance (4 mA to 20 mA) 	Yes 25 Ω ; Plus approx. 42 ohms for overvoltage protection by PTC
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> • Type B 	No
<ul style="list-style-type: none"> • Type C 	No
<ul style="list-style-type: none"> • Type E 	No
<ul style="list-style-type: none"> • Type J 	No
<ul style="list-style-type: none"> • Type K 	No
<ul style="list-style-type: none"> • Type L 	No
<ul style="list-style-type: none"> • Type N 	No
<ul style="list-style-type: none"> • Type R 	No
<ul style="list-style-type: none"> • Type S 	No
<ul style="list-style-type: none"> • Type T 	No
<ul style="list-style-type: none"> • Type U 	No
<ul style="list-style-type: none"> • Type TXK/TXK(L) to GOST 	No
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> • Cu 10 	No
<ul style="list-style-type: none"> • Cu 10 according to GOST 	No
<ul style="list-style-type: none"> • Cu 50 	No
<ul style="list-style-type: none"> • Cu 50 according to GOST 	No
<ul style="list-style-type: none"> • Cu 100 	No
<ul style="list-style-type: none"> • Cu 100 according to GOST 	No
<ul style="list-style-type: none"> • Ni 10 	No
<ul style="list-style-type: none"> • Ni 10 according to GOST 	No
<ul style="list-style-type: none"> • Ni 100 	Yes; Standard/climate

— Input resistance (Ni 100)	10 MΩ
• Ni 100 according to GOST	No
• Ni 1000	Yes; Standard/climate
— Input resistance (Ni 1000)	10 MΩ
• Ni 1000 according to GOST	No
• LG-Ni 1000	Yes; Standard/climate
— Input resistance (LG-Ni 1000)	10 MΩ
• Ni 120	No
• Ni 120 according to GOST	No
• Ni 200	No
• Ni 200 according to GOST	No
• Ni 500	No
• Ni 500 according to GOST	No
• Pt 10	No
• Pt 10 according to GOST	No
• Pt 50	No
• Pt 50 according to GOST	No
• Pt 100	Yes; Standard/climate
— Input resistance (Pt 100)	10 MΩ
• Pt 100 according to GOST	No
• Pt 1000	Yes; Standard/climate
— Input resistance (Pt 1000)	10 MΩ
• Pt 1000 according to GOST	No
• Pt 200	No
• Pt 200 according to GOST	No
• Pt 500	No
• Pt 500 according to GOST	No
Input ranges (rated values), resistors	
• 0 to 150 ohms	No
• 0 to 300 ohms	No
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	No
• 0 to 6000 ohms	Yes
— Input resistance (0 to 6000 ohms)	10 MΩ
• PTC	Yes
— Input resistance (PTC)	10 MΩ
Cable length	
• shielded, max.	200 m; 50 m at 50 mV
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	2,5 / 16,67 / 20 / 100 ms
• Basic conversion time, including integration time (ms)	10 / 24 / 27 / 107 ms
— additional conversion time for wire-break monitoring	4 ms (to be considered in R/RTD/U 1 to 5 V measurement)
— additional conversion time for resistance measurement	8 ms
• Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 / 10 Hz
Smoothing of measured values	
• Number of smoothing levels	4
• parameterizable	Yes
• Step: None	Yes
• Step: low	Yes
• Step: Medium	Yes
• Step: High	Yes
Encoder	

Connection of signal encoders	
<ul style="list-style-type: none"> • for voltage measurement 	Yes
<ul style="list-style-type: none"> • for current measurement as 2-wire transducer 	Yes; with external supply
<ul style="list-style-type: none"> • for current measurement as 4-wire transducer 	Yes
<ul style="list-style-type: none"> • for resistance measurement with two-wire connection 	Yes; Only for PTC
<ul style="list-style-type: none"> • for resistance measurement with three-wire connection 	Yes; All measuring ranges except PTC; internal compensation of the cable resistances
<ul style="list-style-type: none"> • for resistance measurement with four-wire connection 	No
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.1 %
Temperature error (relative to input range), (+/-)	0.006 %/K
Crosstalk between the inputs, max.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.1 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	0.5 %
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.5 %
<ul style="list-style-type: none"> • Resistance, relative to input range, (+/-) 	0.5 %
<ul style="list-style-type: none"> • Resistance thermometer, relative to input range, (+/-) 	Ptxxx Standard: ±1.2 K, Ptxxx Climate: ±0.8 K, Nixxx Standard: ±0.8 K, Nixxx Climate: ±0.8 K
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	0.3 %
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.3 %
<ul style="list-style-type: none"> • Resistance, relative to input range, (+/-) 	0.3 %
<ul style="list-style-type: none"> • Resistance thermometer, relative to input range, (+/-) 	Ptxxx Standard: ±1.0 K, Ptxxx Climate: ±0.5 K, Nixxx Standard: ±0.5 K, Nixxx Climate: ±0.5 K
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
<ul style="list-style-type: none"> • Series mode interference (peak value of interference < rated value of input range), min. 	40 dB
<ul style="list-style-type: none"> • Common mode voltage, max. 	4 V
<ul style="list-style-type: none"> • Common mode interference, min. 	60 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes
<ul style="list-style-type: none"> • Limit value alarm 	Yes; two upper and two lower limit values in each case
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage 	No
<ul style="list-style-type: none"> • Wire break 	Yes; Only for 1 ... 5 V, 4 ... 20 mA, R, and RTD
<ul style="list-style-type: none"> • Short-circuit 	No
<ul style="list-style-type: none"> • Group error 	No
<ul style="list-style-type: none"> • Overflow/Underflow 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • RUN LED 	Yes; green LED
<ul style="list-style-type: none"> • ERROR LED 	Yes; red LED
<ul style="list-style-type: none"> • MAINT LED 	No
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	No
<ul style="list-style-type: none"> • Channel status display 	Yes; green LED
<ul style="list-style-type: none"> • for channel diagnostics 	Yes; red LED
<ul style="list-style-type: none"> • for module diagnostics 	Yes; red LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels, in groups of 	8
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
Permissible potential difference	
between the inputs (UCM)	8 V DC
Between the inputs and MANA (UCM)	4 V DC
Isolation	
Isolation tested with	707 V DC (type test)

Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
Suitable for applications according to AMS 2750	No
Suitable for applications according to CQI-9	No
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	38.6 kg
— global warming potential, (during production) [CO2 eq]	14.4 kg
— global warming potential, (during operation) [CO2 eq]	24.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.44 kg
Security	
signed firmware update	No
safely removing data	No
data integrity	No
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C; From FS05
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C; From FS05
• vertical installation, max.	40 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Absolute humidity	
• dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	250 g
Classifications	

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)

[Miscellaneous](#)



General Product Approval

For use in hazardous locations



[China RoHS](#)

[Manufacturer Declaration](#)



[FM](#)

For use in hazardous locations

[CCC-Ex](#)



[Type Examination Certificate](#)

[Miscellaneous](#)

[CCC-Ex](#)

Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

Environment



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)



last modified:

5/8/2026